

## ExStik® II DO/pH/Conductivity Kit

User friendly kit economically measures 6 parameters

### Features:

- Convenient DO/pH/Conductivity Kit with all the accessories and carrying case for easy travel
- Measures 6 parameters including Dissolved Oxygen, pH, Conductivity, TDS, Salinity, and Temperature
- Designed for water, wastewater, groundwater, aquaculture and fisheries professionals

Kit includes:

- EC500 pH/Conductivity ExStik® II meter with combination high accuracy multi-ranging Conductivity sensor for Conductivity, TDS, Salinity, pH and Temperature measurements
- DO600 Dissolved Oxygen ExStik® II meter with electrode, replacement membrane cap, and electrolyte
- Meters waterproof to IP57 standard

Accessories included:

- Sample pH buffers - Single use pouches for pH4, pH7, pH10, and rinse solutions
- Weighted base with 2 cups and caps, four 3V CR-2032 batteries and neckstrap with each meter, and carrying case



Specifications:	
Conductivity:	0 to 199µS, 200 to 1999µS, 2.00 to 19.99mS
TDS/Salinity:	0 to 99.9ppm (mg/L), 100 to 999ppm (mg/L) 1.0 to 9.99ppt (g/L)
pH:	0.00 to 14.00pH
DO (saturation mode)	0 to 200.0%
DO (concentration mode)	0 to 20.00ppm (mg/L)
Temperature:	32 to 149°F (0 to 65°C)
DO (concentration mode)	0 to 20.00ppm (mg/L)
Automatic Temp Compensation: Yes	
Max Resolution:	DO600: 0.1%, 0.01ppm (mg/L) EC500: 0.1µS, 0.01ppm (mg/L)
Basic Accuracy:	DO600: ±2.0%FS, 0.4ppm (mg/L) ±1.8°F/1°C EC500: ±2.0%FS, 0.01pH, ±1.8°F/1°C
Dimensions	9.5x 6.8x2.8" (241 x173 x 71mm)
Weight:	1.56 lbs. (708g)

### Ordering Information:

- DO610** .....ExStik® II DO/pH/Conductivity Kit  
**EX010** .....Extension Cable, 3ft (1 Meter) with probe weight for ExStik  
**EX050** .....Extension Cable, 16ft (5 Meters) with probe weight for ExStik

**EXTECH INSTRUMENTS CORPORATION**  
 285 Bear Hill Road, Waltham, MA 02451-1064, U.S.A.  
 Phone: 781-890-7440 • FAX 781-890-7864

ISO 9001:2000 CERTIFIED

**"Make mine an Extech!"™**  
[www.extech.com](http://www.extech.com)



10/28/05 - R2