


## Heat Stress WBGT Meter

### Wet Bulb Globe Temperature (WBGT)

considers the effects of temperature, humidity and direct or radiant sunlight

#### Features:

- Heat Stress Index measures how hot it feels when humidity is combined with temperature, air movement, and radiant heat
- Black Globe Temperature (TG) monitors the effects of direct solarradiation on an exposed surface
- Air Temperature (TA) plus Relative Humidity (RH)
- Selectable units of °F and °C
- In/Out Function displays the WBGT value with or without direct sun exposure
- Auto Power Off with override
- Built-in RS-232 interface with optional Windows<sup>®</sup> compatible software
- Complete with two AAA batteries



Optional Windows<sup>®</sup> compatible PC software (407752) for further data analysis and to generate reports

#### Applications:

- Athletic training
- Monitor outdoor working conditions
- Manufacturing

Specifications	Range	Basic Accuracy
Wet Bulb Globe Temperature (WBGT)	32 to 122°F (0 to 50°C)	±4°F/2°C
Black Globe Temperature (TG)	-22 to 1022°F (-30 to 550°C)	±4°F/2°C
Air Temperature (TA)	32 to 122°F (0 to 50°C)	±1.1°F/0.6°C
Humidity	0 to 100%RH	±3%RH
Dimensions	Meter: 10x1.9x1.1" (254x48.7x29.4mm) Ball: 1.6" dia, 1.4" high (40mm diameter, 35mm high)	
Weight	4.8oz (136g)	

#### Ordering Information:

HT30 .....Heat Stress WBGT Meter  
407752 .....PC software and cable

