








testo 445

Suitable probes at a glance

Probes	Illustration	Probe type	Meas. range	Accuracy	Part no.
Vane probe, Ø 12 mm, can be attached to handle or telescopic handle	 180 mm Ø 12 mm	Vane	+0.6 to +20 m/s Oper. temp. -30 to +140 °C	±(0.2 m/s ±1% of mv) (+0.6 to +20 m/s)	0635 9443
Vane/temperature probe, Ø 16 mm, attachable to handle or telescopic handle	 180 mm Ø 16 mm	Vane Type K (NiCr-Ni)	+0.4 to +60 m/s -30 to +140 °C	±(0.2 m/s ±1% of mv) (+0.4 to +60 m/s)	0635 9540
Vane/temperature probe, Ø 25 mm, can be attached to handle or telescopic handle	 180 mm Ø 25 mm	Vane Type K (NiCr-Ni)	+0.4 to +40 m/s -30 to +140 °C	±(0.2 m/s ±1% of mv) (+0.4 to +40 m/s)	0635 9640
Bendable vane probe (can be bent by 90°), Ø 60 mm, attachable to handle or telescopic handle, for measurements on ventilation outlets	 Ø 60 mm	Vane	+0.25 to +20 m/s Oper. temp. 0 to +60 °C	±(0.1 m/s ±1.5% of mv) (+0.25 to +20 m/s)	0635 9440
Bendable vane probe (can be bent by 90°), Ø 100 mm, attachable to handle or telescopic handle, for measurements on ventilation outlets	 Ø 100 mm	Vane	+0.1 to +15 m/s Oper. temp. 0 to +60 °C	±(0.1 m/s ±1.5% of mv) (+0.1 to +15 m/s)	0635 9340
Affordable, robust hot bulb probe, Ø 3 mm, for measurements in the lower velocity range, with handle	 150 mm Ø 4 mm Ø 3 mm	Hot bulb NTC	0 to +10 m/s -20 to +70 °C	±(0.03 m/s ±5% of mv) (0 to +10 m/s)	0635 1549
Robust hot bulb probe, Ø 3 mm, with handle and telescopic handle for measurements in the lower velocity range	 850 mm Ø 3 mm	Hot bulb NTC	0 to +10 m/s -20 to +70 °C	±(0.03 m/s ±5% of mv) (0 to +10 m/s)	0635 1049
Quick-action hot wire probe, Ø 10 mm, with telescopic handle, for measurements in the lower velocity range with direction recognition	 760 mm Ø 10 mm	Hot wire NTC	0 to +20 m/s -20 to +70 °C	±(0.03 m/s ±4% of mv) (0 to +20 m/s)	0635 1041
Vane probe, Ø 16 mm, with telescopic handle, Tmax +60°C	 700 mm Ø 16 mm	Vane	+0.6 to +40 m/s	±(0.2 m/s ±1.5% of mv) (+0.6 to +40 m/s)	0628 0005
Vane probe, Ø 60 mm, with telescopic handle, for integrating velocity measurement	 1100 mm Ø 60 mm	Vane	+0.25 to +20 m/s	±(0.1 m/s ±1.5% of mv) (+0.25 to +20 m/s)	0635 9449
High temperature vane probe, Ø 25 mm, with handle for continuous measurements up to +350°C	 560 mm Ø 25 mm	Vane Type K (NiCr-Ni)	+0.6 to +20 m/s -40 to +350 °C	±(0.3 m/s ±1% of fsv) (+0.6 to +20 m/s)	0635 6045
Precision pressure probe, 100 Pa, measures differential pressure and velocities (in connection with Pitot tube)		Differential pressure probe	0 to +100 Pa	±(0.3 Pa ±0.5% of mv) (0 to +100 Pa)	0638 1345
Pressure probe, 10 hPa, measures differential pressure and velocities (in connection with Pitot tube)		Differential pressure probe	0 to +10 hPa	±0.03 hPa (0 to +10 hPa)	0638 1445