

## TC640 Thermal Camera



- 640x480 resolution
- 4.3" LCD colour touchscreen
- -20°C~550°C temperature measurement
- IR, VIS, PIP, MIF temperature details
- 13 MP visible light photo and video recording
- Laser ranging
- Share files via mobile app
- Video streaming, real-time data transmission with PC analysis software

### DESCRIPTION

The Megger TC640 thermal camera comes with a high-sensitivity IR detector with a maximum resolution of 640 x 480, a 13 MP visible light camera, and 5 focusing modes. This high-precision Thermal Camera is designed specifically for industrial-use, helping users to intuitively view high definition images and temperature details of target subjects. A 30 Hz infrared frame rate provides for fast and accurate access to more temperature data of moving targets and further detailed analysis.

### FEATURES

- New generation IR sensor with 640 x 480 resolution
- Algorithms for pixel point details and hidden hazards
- A 13 MP visible light camera and dual spotlight illuminators for easy location of faults
- Up to 30 Hz IR video frame rate for temperature analysis
- IP54 waterproof and dustproof and 2 m drop resistance with military-grade quality
- OTA online upgrades to keep the device up to date
- Built-in Wifi module for easy transfer of images to the cloud and remote instant download and analysis

### APPLICATIONS

- Electrical circuits, distribution boards and cabling
- Commercial or industrial circuits
- Industrial distribution boards
- Motor, generator and rotating machine maintenance
- Powergeneration and substations
- Air conditioning maintenance
- CHP systems
- Commercial Heating systems (central heating, underfloor, heat pumps etc)
- Commercial and industrial solar PV systems
- Full heat loss surveys and building insulation
- IT systems
- Component level heat analysis on PCB's
- Air leaks and moisture issues
- Medical use
- Firefighting & other Rescue services
- Law enforcement
- Veterinary and Wildlife

## TC640 Thermal Camera

### SPECIFICATIONS

#### Imaging and optics

<b>Detector type</b>	VOx, 7.5 – 14 µm
<b>Infrared resolution</b>	640 × 480@12 µm
<b>Super resolution</b>	Upgrade images to to 1280 × 960
<b>NETD</b>	30 mK
<b>Frame rate</b>	30 Hz/9 Hz
<b>Focal length</b>	17.7 mm
<b>Field of view</b>	25 ° × 19 ° / 24 ° × 18 °
<b>IFOV</b>	0.68 mrad / 0.66 mrad
<b>Min. object distance</b>	0.15 m
<b>D:S</b>	1470:1
<b>Focusing mode</b>	Manual / Automatic / Touch autofocus / Continuous autofocus
<b>Digital zoom</b>	1.1x to 20x
<b>Measurement and analysis</b>	
<b>Measurement range</b>	Support auto-switching: -40°C to 150°C, 0°C to 650°C
<b>Measurement accuracy</b>	±2°C or ±2%, whichever is greater
<b>Analyzed target</b>	16 in total (Spot/Line/Area)
<b>Alarm</b>	Full screen temperature threshold alarm (image, voice and flash)
<b>Other settings</b>	Isothermals, Smart Stroke, Area calculation
<b>Image display</b>	
<b>Screen size</b>	4.3" LCD, colour touchscreen, 800×480
<b>Image mode</b>	InfraRed, Visible Light, Multi-Image Fusion and Picture-in-Picture
<b>Color palettes</b>	15: White Hot, Iron Red, Arctic, Rainbow 2, Hot Iron, Rainbow 1, Fulgurite, Medical, Tint, Black Hot, Blue Hot, Sepia, Green Hot, Ice and Fire, Amber; Customized
<b>Image adjustment</b>	Level span mode: Automatic, Semi-automatic, Manual
<b>Digital camera</b>	13 MP
<b>Functions</b>	
<b>Laser</b>	Laser (indication, ranging 0.1 m to 40 m)
<b>Recording function</b>	Photo (image stitching) and Video (infrared & visible light)
<b>Cloud services</b>	Available
<b>Other</b>	2 Customized buttons, OTA update

#### Storage and transmission

<b>Storage media</b>	Built-in (64 GB) and external SD card (up to 256 GB)
<b>Image file type</b>	JPG with temp info
<b>Video file type</b>	MP4 format (without temp info) can be used to record audio synchronously; Irgd (with temp info), up to 30 Hz (optional) for temperature analysis
<b>External interface</b>	USB-C, SD card slot, Tripod socket
<b>Wifi</b>	Wifi connection to the mobile terminal for image and real-time video transmission

#### Power system

<b>Battery type</b>	Interchangeable rechargeable lithium-ion battery (2 pcs)
<b>Operating time</b>	4 hours

#### Environmental parameters

<b>Working temperature</b>	-20°C to 50°C
<b>IP rating</b>	IP54
<b>Drop</b>	2 m drop test

#### Physical parameters

<b>Hardware</b>	Spotlight x 2, Microphone, Speaker, Electronic compass, GPS
<b>Weight</b>	1.2 kg (with battery)
<b>Size</b>	292 × 125 × 125 mm
<b>Software kit</b>	PC: ThermoLink app iOS/android: Thermography app

#### Box contents

<b>Box contents</b>	TC640 Thermal camera (with lens), Lens front and back cover, Lithium-ion battery (2 pcs), Soft protective case that fits inside hard transport case, Desktop charger, Power adapter, Adapter plug, USB-C to USB-C Cable, USB-A to USB-C Cable, RJ45 Ethernet Patch Cable, USB-C to Ethernet Adapter, SD card (64 GB), Wrist strap, Shoulder strap, Quick Start Guide, Calibration certificate
---------------------	--

#### Optional accessories

<b>Optional accessories</b>	Lithium-ion battery pack
-----------------------------	--------------------------

# TC640

## Thermal Camera

### ORDERING INFORMATION

Description	Part number
TC640 Thermal Camera	1016-974
<b>Included Accessories</b>	
Wrist Strap	
Camera neck/shoulder Strap	
Desktop Battery charger with adapter plugs x 3 (UK, EU and AU/NZ/CN)	
Lithium-ion battery (2 pcs)	
Hard transport case	
Soft protective case with shoulder strap (fits inside hard transport case)	
Lens front and back cover	
USB-C power adapter	
USB-C to USB-C Cable	
USB-A to USB-C Cable	
RJ45 Ethernet Patch Cable	
USB-C to Ethernet Adapter	
SD card (64 GB)	
Quick Start Guide	
Calibration certificate	

**SALES OFFICE**  
Megger Limited

**TC640\_DS\_EN\_V01**

ISO 9001  
The word 'Megger' is a registered trademark

**Megger**<sup>®</sup>