



1170 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **The hand-held electronics protection solution**
- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Stainless steel hardware



CONFIGURATIONS



1170
Standard



1170NF
No Foam



1170WF
With Foam

DIMENSIONS

Interior (LxWxD)	10.54 x 6.04" x 3.16 (26.8 x 15.3 x 8 cm)
Exterior (LxWxD)	11.64 x 8.34" x 3.78 (29.6 x 21.2 x 9.6 cm)
Lid Depth	1.08" (2.7 cm)
Bottom Depth	2.08" (5.3 cm)
Total Depth	3.16" (8 cm)
Int Volume	0.12 ft³ (0.003 m³)
Padlock Hole Diameter	0.19" (0.5 cm)


MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven


COLORS



Black
Silver



Desert Tan
Yellow



Orange



OD Green

WEIGHT

Weight With Foam	2.10 lbs (1 kg)
Weight Empty	1.96 lbs (0.9 kg)
Buoyancy	7.25 lbs (3.3 kg)
Master Pack Weight	12.79 lbs (5.8 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

CERTIFICATIONS

IP67

OTHER

Master Pack	6
--------------------	---

ACCESSORIES



1171
3 pc. Replacement Foam Set



1173
Replacement O-ring



1507
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel



1500CI
Corrosion Intercept Kit