

# 1750

## Protector

Long Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the artic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- · Strong polyurethane wheels with stainless steel bearings
- · Watertight, crushproof, and dustproof
- 3-piece foam set
- Automatic Pressure Equalization Valve balances interior pressure, keeps water out
- · Easy open Double Throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors



## **CONFIGURATIONS**



**1750** Standard



1750NF No Foam



1750WF With Foam

#### **DIMENSIONS**

 Interior (L×W×D)
 50.50 x 13.50" x 5.25 (128.3 x 34.3 x 13.3 cm)

 Exterior (L×W×D)
 53.00 x 16.00" x 6.12 (134.6 x 40.6 x 15.5 cm)

 Lid Depth
 1.75" (4.4 cm)

 Bottom Depth
 3.50" (8.9 cm)

 Total Depth
 5.25" (13.3 cm)

 Int Volume
 2.07 ft³ (0.059 m³)

 Padlock Hole Diameter
 5/16" (12.7 cm)

## **MATERIALS**

**Body** Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

**Purge Vent** 3 Micron Hydrophobic Non-Woven

## **COLORS**

Black Desert Tan OD Green

## WEIGHT

 Weight With Foam
 25.57 lbs (11.6 kg)

 Weight Empty
 23.59 lbs (10.7 kg)

 Buoyancy
 187.39 lbs (85 kg)

 Master Pack Weight
 25.65 lbs (11.6 kg)

## **TEMPERATURE**

Minimum Temperature -40°F (-40 °C)
Maximum Temperature 210°F (98.9 °C)

## **CERTIFICATIONS**

IP67

Def Stan 81-41 STANAG 4280

## FOAM PROPERTIES

 Layer 1 (Lid)
 1.63" Pad

 Layer 2 (Base)
 1.63" Pad

 Layer 3 (Base)
 1.63" Pad

## OTHER

Wheels2Master Pack1NameplateyesMilitaryyes

## **ACCESSORIES**







1753 Replacement O-ring



**1506TSA** TSA Lock



**1500D** Desiccant Silica Gel



PL2 Padlock (2 pack)