

Gooseneck Hex Connecting Bar

Provides extra leverage when positioning steel beams and aligning bolt holes. The forged fit-up bar is pointed on one end while the 45° angle of the chisel-end both combine for greater leverage.



GN3243

Cat. No	UPC Code 0-92644+	Description	Overall Length
GN3243	66509-7	7/8" (22 mm) Gooseneck Hex Connecting Bar	30" (762 mm)

Ironworker's Pliers

Use to twist and snip soft annealed rebar tire wire. The knurled jaws also aid in easy twisting and turning. These pliers feature a hook-bend in the handle for added grip and leverage. Unique handle tempering helps absorb the "snap" when cutting wire.



D201-7CST



- New knurled head for better gripping and longer lasting teeth pattern.

Cat. No.	UPC Code 0-92644+	Nose Type	Handle Finish	Jaw Length	Jaw Thickness	Jaw Width	Knife Length	Overall Length
201-7CST	70300-3	Square	Plain	1-9/32" (33 mm)	1/2" (13 mm)	1-5/32" (29 mm)	5/8" (16 mm)	9-1/8" (232 mm)
D201-7CST	70302-7		Plastic-Dipped					9-1/4" (235 mm)
D20007CST*	70378-2							

*Cuts ACSR, screws, nails and most hardened wire.

Tool Tether

Falling objects are the #3 leading cause of disabling workplace injuries, according to OSHA. Keep your tools close at hand when working at height with this handy tool tether.



TT1

Cat. No	UPC Code 0-92644+	Maximum Load Limit	Relaxed Length	Stretched Length
TT1	46000-5	10 lbs (4.5 kg)	32" (813 mm)	60" (1524 mm)

⚠ WARNINGS:

- Inspect for wear before each use.
- Do not use for human support.
- Maximum Working Capacity 10 lbs. (4.5 kg). Never connect over 5 lbs. (2.3 kg) to a person.
- Do not use around moving or rotating equipment.

⚠ WARNINGS:

- Tether extends to length of 5' (1.5 m). Rig to avoid contact with objects below.
- Always ensure cinch remains snug while in use.
- Always attach carabiner end to anchor point.
- Do not attach tether back onto itself.
- Do not tie knots in tether.

Bull Pins with Tether Holes

Manufactured for durability, Klein bull pins are machined from quality alloy steel that is heat-treated for strength. The tether hole allows you to keep bull pins connected for easy access and safety when working at height.

- Standard design includes a vertical slot to protect the loop-end of the tether when connected.
- Broad-Head design will not mushroom.
- Rust resistant.



Cat. No.	UPC Code 0-92644+	Material	Length	Point Diameter	Top Diameter
Broad-Head					
3255TT	48001-0	Steel	13-3/4" (349 mm)	5/16" (8 mm)	1-1/4" (32 mm)
3256TT	48002-7	Steel	10" (254 mm)	1/4" (6 mm)	1-1/16" (27 mm)
Standard					
3259TT	48003-4	Steel	12" (305 mm)	7/16" (11 mm)	1-5/16" (33 mm)
3259TTS	48004-1	Stainless Steel			



3255TT

3259TTS