



Meets ANSI/ESD S20.20 tested per ANSI/ESD S1.1 and ESD TR53.

The 2200 Series Coil Cord is for use with Single-Wire Wrist Straps and SCS Workstation Continuous Monitors (sold separately). The Coil Cord features a segmented strain relief and a single bundle of tinsel conductors which provide long cord life and flexible movement. It has a 1 megohm current limiting resistor (at the socket end to attach to the wristband). An alligator clip is included but best to plug banana plug into a banana jack ground.



| Specifications | Typical Value |
|-----------------------|----------------------------|
| Tensile strength | > 15 lbs. (6.8 kg) |
| Flex life bending | 1,000,000 cycles |
| Resistance end-to-end | 1 Megohm \pm 20% |
| Plug | 3.4mm straight banana plug |
| Socket | 4mm female snap socket |
| Color | Black |

| Item | Description |
|----------------------|------------------|
| 2210 | 5 ft. Coil Cord |
| 2220 | 10 ft. Coil Cord |

Unless otherwise noted, tolerance \pm 10%

Specifications and procedures subject to change without notice.

Made in the United States of America with Globally Sourced Materials.

2200 SERIES COIL CORD

SCS

**DRAWING
NUMBER**
2200 Series

DATE
July
2017