

# 2300, 2401 & 2701 Series

# **Mechanical Length Measuring Unit**



Heavy duty measuring unit, dual measuring wheels for better stability and contact, frame/ bulkhead mounted.

These rugged instruments have a wide range of applications where an accurate record of length is required. They are strong, heavy duty units for use on calendars, tenters, rolling, ribbon winding, textile machinery and almost all other continuous manufacturing processes. The 2701 (twin wheel) and the 2401 (single wheel) units are mounted or hung from a supplied stay rod, 17.99" (457mm). The 2300 bolts directly onto a bulkhead or frame member. All models incorporate a hinge arrangement on the stayrod so they can be positioned at any angle. Incorporates the 3602 counter and measuring wheels.

## **Key Features**

Uses standard measuring wheels

Find Quality Products Online at:

- Can be tilted out of the way when not in use
- The 2300 bolts directly onto a bulkhead or frame
- The integral hinge arrangement allows the unit to be positioned at any angle
- The measuring wheels supplied can be 0.5m or 0.3m (18in or 12in) circumference (specify when
- The weight of the assembly holds it in contact with the material being measured

# **Specification**

6 digit 0.25" (6.4mm) Display Measurment Options Imperial or metric

Max speed of travel 3,000 RPM Mechanical

**Shaft Diameter** 7<sub>mm</sub>

Units of Metres/centimetres, yards/

Measurement eigths or feet/inches

(other measurements may be

available to special order)

**Packed Dimensions** 2300: 180mm (7.09in) x 200mm (7.87in) x 270mm (10.63in)

**2401/2701**: 500mm (19.69in) x 250mm (9.81in) x 100mm

(3.94in)

www.GlobalTestSupply.com


sales@GlobalTestSupply.com

2701: 4.4lb (2.0kg)




### **Dimensions**

#### **Product Dimensions 2300**



# 23.8/mm min./198.1 mm max.

#### Product Dimensions 2401 | 2701



# **Length Measuring Ordering Information**

To order a 2300, 2401 or 2701:

- 1. Select from the three different basic units,
- 2. Select the wheel surface type
- 3. Select the wheel circumference from option
- 4. Select the unit of measurement
- 5. Select the direction of travel

#### 1. Select one of the units available from below

2300 Measuring counter with hinged bracket and two

wheels

**2401** Measuring counter with stand, stay rod, counter

mounting bracket and one wheel

**2701** Measuring counter with stand, stay rod, counter

mounting bracket and two wheels

## 2. Select one of the measuring wheels listed below

- -1 Rubber covered plastic wheel(s)
- -3 Polyurethane covered plastic wheel(s)
- -5 Knurled aluminum wheel(s)

# 3. Select the circumference for the wheel(s)

- 1 1/2 metre wheel(s)
- 2 1/3 metre wheel(s)
- 3 18 inch wheel(s)
- 4 12 inch wheel(s)

#### 4. Select reading

MY Yards & 1/8ths
MFY Full Yards
MF Feet & Inches
MFF Full Feet

MC Metres & Centimeters

**MFM** Full Metres

## 5. Select direction of travel

C Top comingG Top going

#### Example of full order code

2701 Unit (stand, stayrod and 2 wheels) with 18" rubber covered plastic wheels, reading yards & 1/8ths, direction top going.

The full order code is: 2701-13MYG

# **Measuring Wheel Ordering Information**

Material	Width	12" circumference	18" circumference	1/3m circumference	1/2m circumference
Rubber Covered Plastic	5/8" (16mm)	007571	007573	007905	007574
	5/8" (16mm)	011105	011106	444	
Knurled Aluminum	5/8" (16mm)	001558	001622		
					101 (10)



Trumeter (Europe)
Pilot Mill

**Trumeter (The Americas)** 702 S. Military Trail

Innovative Design Technologies Sdn. Bhd Lot 5881, Lorong Iks Bukit Minyak 1

Find Quality Products Online at:

www.GlobalTestSupply.com

sales@GlobalTestSupply.com