



		MODELS 61, 62, 63		WEATHERPROOF™ WIRE-NUT® WIRE CONNECTORS	
FEATURES/BENEFITS:					
		<ul style="list-style-type: none">-EASY TO APPLY, PRE-FILLED TWIST-ON WIRE CONNECTORS-SILICONE-BASED SEALANT PROTECTS AGAINST MOISTURE AND CORROSION-UL LISTED FOR INTERIOR AND EXTERIOR DAMP/WET LOCATIONS-WIDE WIRE RANGE ENABLES USE ON VARIETY OF APPLICATIONS INCLUDING OUTDOOR POWER OUTLETS, OUTDOOR SIGNAGE, AND EXTERIOR AREA LIGHTING			
ELECTRICAL:			APPLICATION TOOLING:		
<p>VOLTAGE:</p> <p>GENERAL: 600 V MAX</p> <p>SIGN/LUMINAIRES: 1000 V MAX</p>			<p>- Spin-Twist® Wire Connector Socket</p>		
PHYSICAL:			STANDARDS & SPECIFICATIONS:		
<p>HOUSING: GRAY THERMOPLASTIC POLYESTER</p> <p>INSERT: STEEL</p> <p>PLATING: ZINC</p> <p>TEMPERATURE: 105°C (221°F)</p> <p>SEALANT: 100% SILICONE</p>			<p>UL 486C</p> <p>UL 486D DAMP & WET LOCATIONS</p> <p>UL 94V-2 FLAME RATING</p> <p>CSA- C22.2 NO. 188</p> <p>CSA- C22.2 NO. 198.2 DAMP & WET LOCATIONS</p> <p>RoHS COMPLIANT</p> <p>IEC 998-2-4</p> <p>IP 55 TESTED</p>		
<p>WIRE RANGE:</p> <ul style="list-style-type: none">- Solid and/or stranded wire combinations unless stated otherwise- Consult factory for other combinations not listed					
MODEL 61 (GRAY/ORANGE)		MODEL 62 (GRAY/RED)		MODEL 63 (GRAY/DARK BLUE)	
STRIP LENGTH: 3/8" (9,5 mm)		STRIP LENGTH: 1/2" (12,7 mm)		STRIP LENGTH: 5/8" (15,9 mm)	
<p>1 or 2 #14</p> <p>2 #16</p> <p>1 to 4 #18 Str.</p> <p>2 to 4 #18 Sol.</p> <p>2 to 4 #20</p>		<p>1 to 2 #10</p> <p>1 to 3 #12</p> <p>1 to 5 #14</p> <p>1 to 6 #16</p> <p>3 to 6 #18</p>		<p>1 or 2 #8</p> <p>2 to 5 #10</p> <p>2 to 6 #12</p> <p>1 to 3 # 14</p>	
DIMENSIONS:					
 <p>MODEL 61</p>		 <p>MODEL 62</p>		 <p>MODEL 63</p>	
ORDERING INFO:					
CATALOG #	MODEL	COLOR	PACKAGE TYPE:	WEIGHT LBS (KG):	
30-1361	61	Gray/Orange	Box of 1,000	5.3 (2,4)	
30-1362	62	Gray/red	Box of 1,000	12.3 (5,6)	
30-1363	63	Gray/Dark Blue	Box of 1,000	17.9 (8,1)	
FACTORY CONTACT:			SALES CONTACT:		

REVISION: SEPTEMBER 2015