

Adjustable-Head Construction Wrench



- Eliminates the need to carry several fixed-size wrenches.
- Forged from select alloy steel with continuous-taper handle.
- Industrial black finish for corrosion resistance.
- Handy lanyard hole (Cat. No. 3227).

Cat. No.	Max. Size Capacity	Length	Weight
3239	1-1/2" (38 mm)	16" (406 mm)	2.36 lbs. (1.07 kg)
3227	1-5/16" (33 mm)	11" (279 mm)	1.19 lbs. (0.54 kg)



Broad Head Bull Pins

- Forged, heat-treated bull pin increases efficiency and safety by providing a larger striking surface.
- Angled head and smooth blending of radii increase strength and reduce the danger of chipping.
- Below the head, squared-off shoulders have been forged to provide a surface for applying wrench to loosen wedged bull pins.
- Long, even taper reduces binding and hang-up.
- Added resistance to "mushrooming" permitting much longer use than is possible with conventional designs.
- Heat-treated for strength, black finish for rust resistance.



Cat. No.	Top Diameter	Point Diameter	Length	Weight
3255	1-1/4" (32 mm)	5/16" (8 mm)	13-3/4" (349 mm)	2.90 lbs. (1.32 kg)
3256	1-1/16" (27 mm)	1/4" (6 mm)	10" (254 mm)	1.60 lbs. (0.73 kg)

Note: OSHA 1926.301 (c) specifically states: "Impact tools, such as drift pins, wedges and chisels, shall be kept free of mushroomed heads."

Ironworker's Pliers

- Twists and cuts soft annealed rebar tie wire.
- Hook bend handle.
- Spring-loaded action for self-opening.
- Heavy-duty knurled jaws.



Cat. No.	Overall Length	Jaw Length	Jaw Width	Knife Length	Weight
D2000-7CST	9-1/4" (235 mm)	1-9/32" (33 mm)	1-5/32" (29 mm)	5/8" (16 mm)	0.70 lbs. (0.32 kg)
D2000-9ST	9-3/8" (238 mm)	1-19/32" (41 mm)	1-1/4" (32 mm)	25/32" (20 mm)	1.10 lbs. (0.50 kg)

