

10-piece Lighted Probe Extension Kit for BITE3

These lighted probe extensions are mounted on the end of the BITE3 pistol probe. This allows the BITE3 to measure either battery cells and/or intercell connection straps located in small, tight spaces. Cat. No. 35865 extensions can reach up to 27 inches.



Cat. No.: 35865
Length: 12 in., extends to 27 in.
Weight: 1.0 lbs
Material: ABS plastic
Includes: (2) 12 in. extension rods
(2) 6 in. extension rods
(2) rod - receiver adapter assemblies
(2) pointed tips

CT Miniature Current Sensor for BITE2/2P, 1/2 in. Opening, 2-1/2 ft. Lead

The mini CT is plugged into the BITE2/2P receiver and used to measure the test current from the BITE2/2P transmitter. Its small size allows for use in confined areas where space is limited.



Cat. No.: 246034
Dimensions: 4.44 x 1.34 in.
Weight: 5.6 oz
Current Range: 0 A to 150 A

CT Extension Cable for BITE2/2P

The CT extension cable connects the CT, used to measure the test current, and the BITE2/2P receiver, increasing its length to 20 ft. This is ideal for long battery strings.



Cat. No.: 33864-2
Length: 20 ft.
Gauge: 22 AWG
Material: Polypropylene

Bar Code Scanner with Preprinted Code Sheet for BITE2/2P

The bar code scanner identifies the battery string to be tested by the BITE2, tagging the individual test data to a particular battery string.



Cat. No.: 246201
Dimensions: 5.98 x 2.84 x 0.866 in.
Weight: 2.89 oz

Tip Kit for BITE3

The tip kit contains replacement tips for the BITE3 pistol probes.



Cat. No.: BI-10017
Dimensions: 1.42 x .156 in.
Material: Gold plated over nickel
Includes: (4) waffle tips

Quick Disconnect Lead Set for BITE3

The quick disconnect lead allows the BITE3 to be used in strings utilizing spade lugs in their configuration.



Cat. No.: BI-10006
Length: 54 in. (typical)
Tip Type: Female spade terminal

Kelvin Clip Lead Set for BITE3

The Kelvin clip allows the BITE3 to be clipped directly to the battery terminals and straps when performing the measurements.



Cat. No.: BI-10005
Length: 54 in. (typical)
Tip Type: Kelvin

AMP/Burndy Lead Set for BITE3

The burndy leads allow the BITE3 to be used in strings utilizing 2-pin amp connectors in their configuration.



Cat. No.: BI-10004
Length: 54 in. (typical)
Tip Type: 2-pin male amp connector

Dual Point Lead Set, 6 ft.

The dual point lead set is designed for measuring battery straps up to six-ft long for battery rooms with split string design. They are six feet from probe to probe.



Cat. No.: 36616
Length: Probe to unit, 84 in. (typical)
Probe to probe, 80 in. (typical)
Tip Type: Dual-tip waffle