



COBALT

MAXIMUM LIFE IN STAINLESS STEEL



**Made in
USA**



34401C

Dual-Flute

Two cutting edges share the load resulting in faster drill times with less force



34403C

New split point tip

Eliminates walking and penetrates quickly up to 10GA stainless steel



30008C

Cobalt HSS

Engineered for maximum life on stainless steel

Steam Oxide Finish

Runs cooler and extends the life of the bit

CUTS CLEAN, SMOOTH HOLES

Dual-edge design enables fast drilling with less force

Cobalt High Speed Steel reduces wear of bit and maximizes heat resistance



SPECIFICATIONS

Stainless Steel Capacity Up to 10GA

Accessories Greenlee 462 Series Cutting Oil

Also cuts mild steel, copper, brass, aluminum, fiberglass, plastic, wood and laminates

CAT. NO.	# STEPS	MIN DIAMETER	INCREMENTS	MAX DIAMETER	HEX SHANK
34401C	13	1/8"	1/32"	1/2"	3/8"
34403C	12	3/16"	1/16"	7/8"	3/8"
30008C	3	1/2"	-	1-1/8"	3/8"
35884C	Includes all 3 step bit sizes in a case				

ORDERING INFORMATION

CAT. NO.	UPC NO.	DESCRIPTION
34401C	05789	XT Cobalt Step Bit, 1/2"
34403C	05790	XT Cobalt Step Bit, 7/8"
30008C	05792	XT Cobalt Step Bit, 1-1/8"
3584C	05793	XT Cobalt Step Bit, 1/2", 7/8", 1-1/8"

