



**2-1/2" 4025** DC Moving Coil

**2-1/2" 4026** AC Repulsion

### Features

- Handsomely styled to meet the most demanding appearance requirements.
- 4 hole mounting to provide for interchanging with other similar size meters.
- UL Recognized meters available.
- Special Dials are available with the following options: additional Colors, Scales, Special Legends, Logo and Mirrors.
- **DC Ranges:** Microammeter, Milliammeter, Ammeter, Millivoltmeter, Voltmeter.
- **AC Ranges:** Milliammeter, Ammeter, Voltmeter, Frequency Meter, Motor Load Meter.

### Specifications

Overload: Voltmeters (AC and DC): 50% momentary; 20% sustained.  
Ammeters (AC and DC): momentary - 10 X rated current,  
10 consecutive intervals of 1/2 second with a 1 minute interval  
between successive applications; sustained - 20% for 6 hours.

Accuracy:  $\pm 2\%$  full scale value.

Resistance:  $\pm 15\%$ .

Dials: 100 or 90 degree arc, black lettering on white background.  
Special dial colors and artwork are available as an option.

Pointer: Knife Edge

Movement: Pivot and Jewel, AC Iron Vane or Taut Band.

Mounting: Specify (S) Surface mount.

Case: Bakelite.

Operating Temp.: 32°F to 104°F ( 0°C to 40°C).

Storage Temp.: -4°F to 131°F (-20°C to 55°C).

Meter Approvals: ANSI C39.1, RoHS, REACH.

Origin: Made in USA.

### Dimensions

