

# Traceable® Jumbo Humidity/Temperature Meter

**Jumbo 1-inch digits display humidity, temperature—read from 35 feet away**



**MIN/MAX Memory permit monitoring conditions overnight, on weekends, or for any time period**

- Simultaneously displays ambient relative humidity and (internal probe and external probe) temperatures °F/°C with dual-recall memories
- Both sensor and 10-foot cable perform accurately when under water
- Fulfills CLIA specification 493.1207

## Features:

- Quick-response sensor
- Self-contained, stable, accurate unit requires no adjustment or maintenance
- Individually serialized, calibrated, and certified Traceable® to NIST

## Displays:

- Ambient Relative Humidity
- Ambient Temperature (IN)
- External (Probe) Temperature (OUT)
- Comfort/DRY/WET humidity level within preset parameters

## Traceable to NIST for accuracy

An individually-numbered Traceable® Certificate is provided which assures accuracy from an ISO/IEC 17025 (1750.01) calibration laboratory accredited by A2LA. It indicates traceability to standards provided by NIST (National Institute of Standards and Technology).

Cat. No. 4184 Traceable® Jumbo Humidity/Temperature Meter



**Convenient unit sits on bench, hung on the wall, or temperature probe may be placed anywhere**

## Product Specifications

- ▶ **Humidity**
  - Range:** 25 to 95% RH
  - Resolution:** 1% RH
  - Accuracy:** ±2% RH mid-range to ±4% RH elsewhere
- ▶ **Probe Temperature**
  - Range:** -58 to 158°F (-50 to 70°C)
  - Resolution:** 1°
  - Accuracy:** ±1°C
- ▶ **Ambient Temperature**
  - Range:** 32 to 131°F (0 to 50°C)
  - Resolution:** 1°
  - Accuracy:** ±1°C
- ▶ **Supplied:** Traceable® Certificate, flip-open stand, wall mount, and batteries



Find Quality Products Online at:

[www.GlobalTestSupply.com](http://www.GlobalTestSupply.com)

[sales@GlobalTestSupply.com](mailto:sales@GlobalTestSupply.com)