

# YELLOW JACKET®

## Series 41 2-Valve Manifold with 2-1/2" (63.5 mm) Gauges - °F



Forged body is solid brass for durability. Full porting maximizes capacity. Metal valve handles are full size for easy operation. Hose anchors are forged into back of body at 45°.

Flutterless™ technology means surge protector and silicone dampened movement helps minimize needle pulsation for easier, more accurate readings.

Sliding double "O" ring pistons reduces wear. Easy-to-read 2-1/2" (63.5 mm) steel case gauges with 3-2-3% accuracy (Class B).

Limited lifetime warranty on manifold bar and valves - not gauges. See warranty information for details.

Made in the USA



*Distributed by:*

| Box        | Clamshell |                                                          |             |                                                |
|------------|-----------|----------------------------------------------------------|-------------|------------------------------------------------|
| UPC#       | UPC#      | Description - °F/°C - Solar Gauges                       | Scale       | Refrigerant                                    |
|            | 41612     | Manifold only                                            | bar/psi/MPa | R-22/134a/404A/<br>407C/409A/410A/<br>438A/507 |
|            | 41615     | With 60" PLUS II™ standard fittings                      | bar/psi/MPa |                                                |
| UPC#       | UPC#      | Description - °F - Red/Blue                              | Scale       | Refrigerant                                    |
|            | 41212     | Manifold only                                            | psi         | R-12/22/502                                    |
| 41213      | -         | With 36" PLUS II™ standard fittings                      | psi         |                                                |
| 41220      | -         | With 48" PLUS II™ standard fittings                      | psi         |                                                |
|            | 41215     | With 60" PLUS II™ standard fittings                      | psi         |                                                |
|            | 41219     | With 72" PLUS II™ standard fittings                      | psi         |                                                |
|            | 44215     | With 60" PLUS II™ SealRight fittings                     | psi         |                                                |
| 44219      | -         | With 72" PLUS II™ SealRight fittings                     | psi         |                                                |
| 42215      | -         | With 60" PLUS II™ compact ball valve fittings            | psi         |                                                |
| 42219      | -         | With 72" PLUS II™ compact ball valve fittings            | psi         |                                                |
| <b>NEW</b> | 41202     | Manifold only                                            | psi         | R-22/134a/404A                                 |
|            | 41209     | With 36" PLUS II™ standard fittings                      | psi         |                                                |
|            | 41211     | With 60" PLUS II™ standard fittings                      | psi         |                                                |
|            | 41312     | Manifold only                                            | psi         | R-134a/404A/507                                |
| 41313      | -         | With 36" RYB                                             | psi         |                                                |
| 41311      | -         | With 48" RYB                                             | psi         |                                                |
|            | 41315     | With 60" PLUS II™ standard fittings                      | psi         |                                                |
|            | 41319     | With 72" PLUS II™ standard fittings                      | psi         |                                                |
| 43313      | -         | With 36" PLUS II™ standard fittings                      | psi         |                                                |
| 44313      | -         | With 36" PLUS II™ SealRight fittings                     | psi         |                                                |
|            | 44315     | With 60" PLUS II™ SealRight fittings                     | psi         |                                                |
| 44319      | -         | With 72" PLUS II™ SealRight fittings                     | psi         | R-410A                                         |
| 42315      | -         | With 60" PLUS II™ compact ball valve fittings            | psi         |                                                |
|            | 41712     | Manifold only                                            | bar/psi     |                                                |
|            | 41709     | With 60" PLUS II™ standard fittings                      | bar/psi     | R-410A                                         |
| 41715*     | -         | With 60" PLUS II™ standard fittings for R-410A           | bar/psi     |                                                |
| 41710      | -         | With HCA 60" PLUS II™ standard fittings                  | bar/psi     |                                                |
| 41702      | -         | With HCABV 60" PLUS II™ standard fittings                | bar/psi     |                                                |
| 42715      | -         | With 60" PLUS II™ compact ball valve fittings            | bar/psi     |                                                |
| 41711*     | -         | With 60" PLUS II™ compact ball valve fittings for R-410A | bar/psi     |                                                |

\* Special R-410A hose – R/B hoses are 1/4" x 45° 5/16" end; Y hose is 1/4" x 45° 1/4" end.

