Canvas Pouch with Connection Points

features bull pin loops on each side for easy access. Double bottom provides additional strength. Two D-rings on the front of the pouch and four on the inside offer plenty of space to connect tethers.

Cat. No	UPC Code 0-92644-	Belt Capacity	Belt Connection	Length	Width
54160CT0	55387-5	up to 3" (76 mm) wide	loop	5" (127 mm)	9" (229 mm)



54160CT0


Load Rated Bucket with Connection Points

is made of heavy-duty canvas to withstand harsh job site conditions. Bucket features web straps extending down the sides for additional strength.

- Six small D-rings sewn to the interior of the bucket provide secure connection points for tethers.
- Extra large hook to fit onto oversized rigging equipment.
- Leather reinforced bottom.
- High-density polyethylene top ring provides strength and chemical resistance.



Cat. No	UPC Code 0-92644-	Height	Diameter
51040CT0	61000-4	17" (432 mm)	12" (305 mm)



100 lbs.

Bull Pins with Tether Holes

Manufactured for durability, Klein bull pins are machined from quality alloy steel. The tether hole allows you to keep bull pins connected for easy access and added protection in the event of an accidental drop.

Broad Head

- Head design reduces chance of pin slipping and provides a larger striking surface.
- Black finish for rust resistance.



Standard

- · Available with black finish or stainless steel for rust resistance.
- Vertical slot protects the loop end of the tether when connected.





51040CTO WLB\$ (45kg)

3259TT

Cat. No.	UPC Code 0-92644-	Туре	Material	Top Diameter	Point Diameter	Length
3256TT	48002-7	Broad Head	Steel	1-1/16" (27 mm)	1/4" (6 mm)	10" (254 mm)
3255TT	48001-0	Broad Head	Steel	1-1/4" (32 mm)	5/16" (8 mm)	13-3/4" (349 mm)
3259TT	48003-4	Standard	Steel	1-5/16" (33 mm)	7/16" (11 mm)	12" (305 mm)
3259TTS	∆ 8∩∩ ∆ -1	Standard	Stainless Steel	1-5/16" (33 mm)	7/16" (11 mm)	12" (305 mm)

 $\wedge \Rightarrow \Box$