

# Light Powered NSF Remote Reading Thermometers

## 25SD



<b>CASE:</b>	1" x 4" Surface Mounting, Black or White
<b>MASK:</b>	Black or Silver Mask / Custom logo on request
<b>RANGE:</b>	40-0-160°F or 40-0-70°C factory set
<b>DISPLAY:</b>	3/8" LCD
<b>LIGHT RATING:</b>	30 Lux to 50,000 Lux
<b>SENSOR LENGTH:</b>	3 Ft. or 5 Ft.
<b>ENVIRONMENT:</b>	Splash Proof (optional black or white gasket)
<b>ACCURACY:</b>	NSF Accuracy for food zone applications. (±2°F between -20 to +60°F)

## 56SD



<b>CASE:</b>	2" Round Back (56mm Square Front)
<b>MOUNTING:</b>	Front Flange or U-Clamp
<b>RANGE:</b>	40-0-230°F and 40-0-110°C (field switchable)
<b>DISPLAY:</b>	3/8" LCD (1/10° display up to 200°F)
<b>LIGHT RATING:</b>	15 Lux to 50,000 Lux
<b>SENSOR LENGTH:</b>	3 Ft. or 5 Ft.
<b>ENVIRONMENT:</b>	Waterproof from Front
<b>OPTIONS:</b>	U-Clamp Case, Model 56SD-U
<b>ACCURACY:</b>	NSF Accuracy for food zone applications. (1% of reading ±1°F or ±.5°C)

## 72SD



<b>CASE:</b>	2 1/2" Round Back (72mm Square Front)
<b>MOUNTING:</b>	Front Flange or U-Clamp
<b>RANGE:</b>	40-0-160°F or 40-0-70°C, factory set
<b>DISPLAY:</b>	1/2" LCD - 1/10° display
<b>LIGHT RATING:</b>	30 Lux to 50,000 Lux
<b>SENSOR LENGTH:</b>	3 Ft. or 5 Ft.
<b>ENVIRONMENT:</b>	Splash Proof (optional gasket)
<b>OPTIONS:</b>	U-Clamp Case, Model 72SD-U
<b>ACCURACY:</b>	NSF Accuracy for food zone applications. (±2°F between -20 to +60°F)

## 20SD



<b>CASE:</b>	2" Round, Stainless Steel
<b>RANGE:</b>	40-0-160°F or 40-0-70°C, factory set
<b>DISPLAY:</b>	3/8" LCD
<b>LIGHT RATING:</b>	50 Lux to 50,000 Lux
<b>BATTERY ASSIST:</b>	15 LUX @ 10 years
<b>SENSOR LENGTH:</b>	3 Ft. or 5 Ft.
<b>ENVIRONMENT:</b>	Splash Proof from the Front
<b>ACCURACY:</b>	NSF Accuracy for food zone applications. (±2°F between -20 to +60°F)