5882A

1kV Megohmmeter



Data Hold Button

Facilitates Accurate Capture of Readings



Convenient Kick Stand

Allowing the Tester to be Kept Upright

Non-Skid Over Molded Rubber Holster

Protects the Meter Against Debris





Molded in Magnetic Mount

For Convenient Hands-Free Measurements

Large, Bright Digital Display

With an Illuminating Blue Backlight

Compact, Well-Spaced Buttons

Minimizes Incorrect Function Selections

Rotary Selector

Aids the User in Selecting the Correct Operating Function from 10 Different Positions

5882A

ORDERING INFORMATION

CAT. NO.	UPC NO.	DESCRIPTION
5882A	07154	Megohmmeter 1kV, 2 Red & Black Leads, 2 Red & Black Test Alligator Clips, 1 Black Test Probe and Soft Carrying Case
5882A-C	08481	Megohmmeter 1kV, 2 Red & Black Leads, 2 Red & Black Test Alligator Clips, 1 Black Test Probe and Soft Carrying Case with Calibration Certificate
5882A-LK	08567	Test Lead Kit (2) Red & Black Leads, (2) Red & Black Test Probes, (2) Red & Black Alligator Clips
5882A-B	08776	1kV Soft Carrying Case

5882A SPECIFICATIONS

WEIGHT:	1.07 lbs
PRE-SET TEST VOLTAGES:	50V, 100V, 250V, 500V, 1kV
RESISTANCE MEASUREMENT:	0 to $4M\Omega$
FREQUENCY MEASUREMENT:	15.3 to 800Hz
VOLTAGE MEASUREMENT:	.3 to 700V
OPERATING TEMPERATURE:	-4F to 131F
STORAGE TEMPERATURE:	-22°F − 176 °F
CONTINUITY CHECKING:	>100Ω
SAFETY VOLTAGE RATING:	CAT IV, 600V
WARRANTY:	Lifetime Limited
STANDBY MODE:	After 5 Minutes of Inactivity
BATTERY POWER SUPPLY:	Six 1.5V AA



For Your Safety

5882A

1kV Megohmmeter

 Molded in magnetic mount and non-slip pads integrated into the back

Safety

- Safety Voltage Rating, CAT IV, 600V
- Automatic discharge after every insulation test
- CE/cETLus certified for safety and environmental standards
- Hazardous Voltage Icon indicates above 70V
- Three preset alarms: Continuity, Resistance and Voltage

Accuracy

- Highly accurate timer on board to ensure accuracy of the data
- Extensive data storage (300 entries) facilitating reporting and comparison to prior readings

Productivity

- Selectable automatic 5-minute standby-by mode extending battery life, supporting productivity
- Industry leading low temperature operation (-4F) to minimize weather interference aiding in productivity

Durability

- Backed by the Greenlee Lifetime Limited Warranty
- Non-skid over molded rubber holster protecting the meter from debris
- Rugged design (IP54/IEC rating) protects against environmental extremes such as dust and water







