



KANOMAX
The Ultimate Measurements

ANEMOMASTER LITE MODEL 6006

Palm-size and feather-weight standard hot-wire anemometer

Anemomaster™ LITE is a compact and lightweight hot-wire anemometer unit. It offers research-grade accuracy at an affordable, industry competitive price. It comes in a dark metallic blue casing with anti-slip gripping.

Applications

- ⚙ HVAC Testing
- ⚙ Facility Maintenance
- ⚙ Critical Environment Certification
- ⚙ IAQ Investigations




FEATURES AND BENEFITS

- ⚙ Lightweight and compact - great for keeping in the tool kit.
- ⚙ Research quality at a contractor-friendly price.
- ⚙ Extended 2 year warranty.
- ⚙ Single switch operation in a comfortable ergonomic design.
- ⚙ Includes 4 pcs. AA batteries, carrying case, and NIST Certificate.

FEATURE		VALUE
Air Velocity	Range	20 to 3940 FPM (0.01 to 20.0 m/s)
	Accuracy Resolution	+/- 5.0% of reading or 0.015 m/s whichever is greater 0.01 m/s (0.01 to 9.99 m/s), 0.1 m/s (10.0 to 20.0 m/s)
Temperature	Range Accuracy Resolution	-4 to 158°F (-20 to 70°C) +/- 1.0°F (0.5°C) 1.0°F (0.1°C)
Power Supply		4x AA batteries
Operation Range	Main Unit Probe Storage	41 to 104°F (5 to 40°C) with no visible condensation -4 to 158°F (-20 to 70°C) with no visible condensation 14 to 122°F (-10 to 50°C) with no visible condensation
Weight		0.4 lbs (180 g)
Dimensions	Main Body Probe	2.4 x 4.7 x 1.2 inches (60 x 120 x 34 mm) Probe Length: 8.1 inches (205 mm) Probe Diameter of Tip: 0.24 inches (6.1 mm)
Warranty		2 years

DISTRIBUTED BY:



Copyright © 2019 Kanomax USA, Inc.