

# K-60SP SECTIONAL MACHINE

## CLEARs 1¼" TO 4" (32 TO 100 MM) DRAIN LINES

The ½ HP motor on the RIDGID® K-60SP sectional machine is ideal for institutional, commercial or residential jobs. Its rear handle makes it easier to carry up ladders to clear rooftop vent stacks and it's quickly become a favorite of septic tank vacuum truck operators.

▶ **RECOMMENDED USAGE**

7/8" (22 mm) cable (C-10) cleans 2" to 4" (50 to 100 mm) lines through 150' (45.7 m)

5/8" (16 mm) cable (C-7, C-8, C-9) cleans 1¼" to 4" (32 to 100 mm) lines through 125' (38.1 m)

▶ **INSTANT-ACTING CABLE CLUTCH**

Maximizes operator control

Pull handle down and cable spins. Release handle and cable stops instantly

▶ **POWERFUL MOTOR**

½ HP motor

▶ **EASY ACCESS**

Remove two bolts to access jaw set for cleaning or replacement as well as access to belt drive

▶ **ADJUST IN SECONDS**

Simple adjustment knob allows unit to spin both 7/8" (22 mm) and 5/8" (16 mm) diameter cable

CATALOG NO.	MODEL NO.	DESCRIPTION
66492	K-60SP	Machine with A-1 Operator's Mitt, A-12 Pin Key, and A-60-12 Rear Guide Hose
66497	K-60SP-SE	Machine with A-1 Operator's Mitt, A-12 Pin Key, and A-60-12 Rear Guide Hose, plus: A-61 Tool Kit and A-62 Cable Kit



# DRAIN CLEANING SECTIONAL MACHINES



APPLICATION CHART	SINK LINES		FLOOR/SECONDARY DRAINS			
			LATERALS & MAIN LINES			
	LINE SIZE:	3/4" - 4"	1 1/4" - 4"	2" - 8"	2" - 8"	2" - 10"
SPEED:	400 RPM	600 RPM	700 RPM	710 RPM	600 RPM	600 RPM
MOTOR TYPE HORSEPOWER:	1/2 HP	1/2 HP	3/4 HP	3/4 HP	1 HP	6 HP Gas
WEIGHT:	37 Lbs.	41 Lbs.	55 Lbs.	135 Lbs.	141 Lbs.	190 Lbs.

## CABLES FOR SECTIONAL MACHINES

PRODUCTS:	K-50		K-60SP		K-5208, K-1500, K-1500SP & K-1500G	
	CABLE DIAMETER:	5/8"		5/8", 7/8"		7/8", 1 1/4"
AVAILABLE LENGTHS:	7 1/2', 10'		7 1/2', 10', 15'		15'	
CABLE TYPE:	Tight Wound, All-Purpose Wound, Heavy-Duty Wound		Tight Wound, All-Purpose Wound, Heavy-Duty Wound, Plastic Core		All-Purpose Wound, Plastic Core, Extra Heavy-Duty Wound, Heavy-Duty Wound, Extra Flexibility	

**Tight Wound** Cable provides good rigidity in a hollow core cable.

**All Purpose Wound** Provides excellent flexibility, yet rigid enough for fast tough cleaning.

**Heavy-Duty Wound** Open wind especially good for long runs.

**Extra Heavy-Duty Wound** Designed for 4' to 10' long runs.

**Plastic Core** Standard all-purpose wind with plastic core to help prevent buildup inside cable.

**Extra Flexibility** Recommended for 3" to 6" lines and ideal for 4" traps.