

1- & 2-channel Loop Powered Isolators for Separation of 0(4)-20 mA Signals

IsoPAQ-11L and IsoPAQ-12L are 1- and 2-channel loop powered isolators used for electrical isolation of 0(4)-20 mA signals to avoid measurement errors due to different voltage potentials or ground loops in an instrument installation.

The 2-channel version, IsoPAQ-12L offers a very cost effective alternative combined with a high-density mounting.

The isolators need no power supply, which contributes to reduced installation costs compared to isolation transmitters.

The high reliability ensures a safe system operation and low maintenance costs.



- Input to output galvanic isolation**
Protection against erroneous measurements due to parasitic voltages or ground loops
- 1- and 2-channel versions**
Allows for optimal cost efficiency
- No power supply required**
Reduced wiring saves installation costs
- Low voltage drop**
Input voltage drop of less than 2 V reduces impact on the primary current loop
- High accuracy**
Negligible additional measurement errors in the loop
- High-density DIN-rail mounting**
12.5 mm (0.5") housing combined with very low self heating allows for high density mounting
- Plug-in screw terminals**
Simplifies installation and maintenance



Specifications: IsoPAQ-11L/-12L

Input

Input signal	0(4)-20 mA/max. 30 V
Operating current	< 20 μ A
Voltage drop	< 2 V
Overload	\leq 100 mA, \leq 30 V

Output

Output signal	0(4)-20 mA/max. 28 V
Response time (10 to 90 % of end value)	2 ms @ 250 Ω load/6 ms @ 750 Ω load
Ripple	< 0.07 % of measured value, ~100 kHz


General data

Transmission error	\pm 0.1 % of end value
Load error	\pm 0.03 % of measured value/100 Ω load
Temperature coefficient ¹⁾	\pm 0.0015 %/K of measured value/100 Ω load
Test voltage	1.5 kV, 50 Hz
Ambient temperature	Operation: -20 to +70 °C (-4 to +158 °F) Transport and storage: -35 to +85 °C (-31 to +185 °F)
EMC ²⁾	EN 61326-1
Construction	12.5 mm (0.5") housing, protection class: IP20
Connection	\leq 2.5 mm ² , AWG 14
Weight	Approx. 100 g

1) Average TC in specified operating temperature range

2) Minor deviations possible during interference


Block diagram/Connections



Ordering information

Product	Input / Output	Part No.
IsoPAQ-11L	1-channel, 0(4)-20 mA	70ISL11001
IsoPAQ-12L	2-channel, 0(4)-20 mA	70ISL12001

Dimensions



mm/inch