## **Metal Stud Punches**



#### **SPECIFICATIONS**

Capacity

709 - 1-5/8" (41.3 mm) and wider studs. 20 gauge (0.9 mm) steel studs. 710 - 2-1/2" (63.4 mm) and wider studs. 20 gauge (0.9 mm) steel studs.

- Punch up through 20 gauge (0.9 mm) steel studs in one stroke
- Aluminum head provides strength with minimum weight, reducing operator fatigue
- · Contoured handle design gives better operator leverage and makes it possible to punch in tight places
- Self-stripping design eliminates punch hang-ups
- · Automatically centers holes on standard studs
- · Conversion kit available to upgrade early models from 24 gauge to 20 gauge maximum capacity

	24 gauge to 20 gauge maximum capacity			WEIGHT	
	CAT NO.	UPC NO.	DESCRIPTION	LBS	KG
	709	22280	7/8" (22.2 mm) Diameter Stud Punch	7	3.2
	710	21285	1-11/32" (34.1 mm) Diameter Stud Punch	7.5	3.5
	30968	30968	Conversion Kit – Upgrades Early Model 709 or		
			710 from 24 to 20 Gauge Maximum Capacity		
R	121AV	04006	Punch for 709		
R	22286	22286	Die for 709		
R	24823	24823	Punch for 710		
R	21297	21297	Die for 710		
	06015	06015	Pin Kit		
	36617	36617	Link		
	05932	05932	Link and Pin Kit (709/710)		
	21557	21557	Compression Spring		

# **Bushings for Metal Stud Punches**





712A1000





- · Triple lock design holds bushing securely
- Locks securely into metal studs from 24 gauge to 12 gauge (0.6 mm to 2.5 mm)
- Helps protect wire insulation from sharp edges of metal studs
- Makes pulling smooth and easy by preventing hang-ups of cable on raw metal edges

			WEIG	пі
CAT NO.	UPC NO.	DESCRIPTION	LBS	KG
711C	22288	100 Bushings for Hole Punched by 709 for 7/8" (22.2 mm) Diameter Hole	.5	.23
711M	22289	1,000 Bushings for Hole Punched by 709 for 7/8" (22.2 mm) Diameter Hole	3.7	1.7
712A100	05927	100 Bushings for Pre-Punched Hole or 1-11/32" (34.1 mm) Diameter Hole Punched by 710	1.4	.64
712A1000	05928	1,000 Bushings for Pre-Punched Hole or 1-11/32" (34.1 mm) Diameter Hole Punched by 710	15.5	7.0

## **Manual Stud Punch**



- Punch up through 20 gauge (0.9 mm) steel studs in one stroke
- Unique patented punch rolls the edge over for smooth installation of armored cable; cable won't hang up
- Contoured handle design gives better operator leverage and makes it possible to punch in tight places
- Automatically centers holes on standard studs

	CAT NO.	UPC NO.	DESCRIPTION
	724	10415	Manual Stud Punch
R	10419	10419	Punch for 724

### **SPECIFICATIONS**

**Actual Hole Size** 1-1/4" (31.7 mm) Weight 4.0 LBS (1.8 KG Length 16-3/4" (426 mm) Height 4-1/2" (247 mm) Capacity 24-20 GA (0.9 mm)