

Humidity Temperature Meters



725



720

Specifications

models

Accessories

One Year Warranty

SUPPLIED:	Model 725 : Datalogging meter, Instruction manual, Battery, Carry case, PC Software, RS-232 Cable, and K-type Bead Probe Model 720 : Meter, Instruction manual, Battery, Padded pouch, and K-type Bead Probe
OPTIONAL:	BE-9 AC Adapter, AK-720 TestLink Software w/RS232 Cable (Model 720) See page 87 for K-type Thermocouple Probes

Model 725

Datalogging Humidity/Temp Meter w/ Dual Input

Model 720

Humidity/Temp Meter w/ Dual Input

State of the art dual function meters with two environmental sensors housed in a remote wand. The sensors can be placed right where they are needed. Both meters feature triple LCD displays, RH and temperature readings simultaneously, and a second K-type thermocouple port.

Model 725 has datalogging feature and records up to 16,300 data points. With an adjustable interval setting, you can record from 4 hours to 678 days worth of data. Both units feature RS-232 output ports (software optional on Model 720). Either download data for analysis or control the meter in real-time from your PC. With the optional TestLink software and RS-232 cable (AK-720), even Model 720 becomes a real-time datalogging meter when attached to a PC.

These meters are ideal for environmental testing, lab monitoring, process control and building maintenance.

Additional features include:

- Tripod Mounting Lug
- Auto Power Off
- Real Time Clock (Model 725)
- Δ Relative Function (Model 720)
- Min/Max function



Tripod Mountable (tripod not included)



Easy to read -
Triple Display