8150-BR-KIT CamView IP Pro 5 HD CCTV Camera Tester with Borescope

Adds a borescope function to your security camera tester for inspecting behind walls and hard-to-reach areas

8150 Features:

- 8MP tester (1080p) with HDMI, BNC, and RJ45 ports
- Works with IP cameras, analog cameras, TVI, CVI, AHD cameras, as well as for testing 4K H.264 /H.265
- · WiFi for connecting to WiFi cameras and to create a WiFi hotspot
- Has PoE (24W) and DC power output (12V/3A)
- Auto-recognize HD coax camera type and resolution
- RJ45 TDR cable test and cable quality test
- UTP cable test detects opens, shorts and miswires
- · 4 hour run time with 2-3-hour charge
- · Compact and lightweight
- Includes SBR2M Security Camera Borescope accessory, 7.4V Li-ion battery, AC adapter/charger, DC power cable, BNC cable, RS485 cable, audio cable, wrist strap and carrying case

SBR2M Borescope Features:

- · Waterproof (IP67) 8mm camera (Lens only)
- 8mm lens diameter with 2m cable (6.5t)
- · 6 adjustable LEDs with thumbwheel control
- Power provided by the camera tester (12V 1/2/3A) no batteries needed
- Utilizes the display resolution of your camera tester
- Image snapshot and Video record functions
- · Compatible with most camera testers

Applications:

Designed for the maintenance and installation of IP cameras, analog cameras, TVI, CVI, AHD cameras, as well as for testing 4K H.264 /H.265. The 1920 x 1200 resolution enables it to display network HD cameras and analog cameras in high resolution.

Borescope for inspecting behind walls and hard-toreach areas; checking cable connections on the back of installed equipment; Insect or rodent infestation; Anywhere you need to see underneath and behind difficult to move objects

Ordering Information:

8150-BR-KIT CamView IP Pro 5 HD CCTV Camera Tester with Borescope

SBR2M Security Camera Tester Borescope, 2M



Specifications	
----------------	--

8MP AHD 8MP TVI 8MP CVI 4k IP / Analog Wifi Connect to WiFi cameras & create a WiFi hotspot HDMI Output (1080p) DC 12V 3A Power Output 48V PoE Output Advanced UTP cable test Power Rechargeable 7.4V 3350mAh Li-ion battery Dimensions 7.2 x 4.3 x 1.4" (183 x 110 x 36.5mm) Weight 11.3oz (320g) SBR2M Camera 8mm Field of View 60° Depth of View 1.2 to 4" (3 to 10cm) Cable Length Resolution 640 x 480 Illumination 6 adjustable LEDs Still Image Capture Video Recording dependent on camera tester Video Recording Power 12V 1/2/3A (provided by camera tester) Interface BNC	Specifications	8150
8MP CVI 4k IP / Analog Wifi Connect to WiFi cameras & create a WiFi hotspot HDMI Output (1080p) DC 12V 3A Power Output 48V PoE Output Advanced UTP cable test Power Rechargeable 7.4V 3350mAh Li-ion battery Dimensions 7.2 x 4.3 x 1.4" (183 x 110 x 36.5mm) Weight 11.3oz (320g) SBR2M Camera 8mm Field of View 60° Depth of View 1.2 to 4" (3 to 10cm) Cable Length Resolution 640 x 480 Illumination 6 adjustable LEDs Still Image Capture Video Recording dependent on camera tester Video Recording Power 12V 1/2/3A (provided by camera tester)	8MP AHD	√
4k IP / Analog Wifi Connect to WiFi cameras & create a WiFi hotspot HDMI Output (1080p) DC 12V 3A Power Output 48V PoE Output Advanced UTP cable test Power Rechargeable 7.4V 3350mAh Li-ion battery Dimensions 7.2 x 4.3 x 1.4" (183 x 110 x 36.5mm) Weight 11.3oz (320g) SBR2M Camera 8mm Field of View 60° Depth of View 1.2 to 4" (3 to 10cm) Cable Length Resolution 640 x 480 Illumination 6 adjustable LEDs Still Image Capture Video Recording dependent on camera tester Video Recording Power 12V 1/2/3A (provided by camera tester)	8MP TVI	
Wifi Connect to WiFi cameras & create a WiFi hotspot HDMI Output (1080p) DC 12V 3A Power Output 48V PoE Output Advanced UTP cable test Power Rechargeable 7.4V 3350mAh Li-ion battery Dimensions 7.2 x 4.3 x 1.4" (183 x 110 x 36.5mm) Weight 11.3oz (320g) SBR2M Camera 8mm Field of View 60° Depth of View 1.2 to 4" (3 to 10cm) Cable Length 2m (6.5ft) Resolution 640 x 480 Illumination 6 adjustable LEDs Still Image Capture dependent on camera tester Video Recording dependent on camera tester Power 12V 1/2/3A (provided by camera tester)	8MP CVI	√
HDMI Output (1080p) DC 12V 3A Power Output 48V PoE Output Advanced UTP cable test Power Rechargeable 7.4V 3350mAh Li-ion battery Dimensions 7.2 x 4.3 x 1.4" (183 x 110 x 36.5mm) Weight 11.3oz (320g) SBR2M Camera 8mm Field of View 60° Depth of View 1.2 to 4" (3 to 10cm) Cable Length Resolution 640 x 480 Illumination 6 adjustable LEDs Still Image Capture Video Recording dependent on camera tester Video Recording Power 12V 1/2/3A (provided by camera tester)	4k IP / Analog	
DC 12V 3A Power Output 48V PoE Output Advanced UTP cable test Power Rechargeable 7.4V 3350mAh Li-ion battery Dimensions 7.2 x 4.3 x 1.4" (183 x 110 x 36.5mm) Weight 11.3oz (320g) SBR2M Camera 8mm Field of View 60° Depth of View 1.2 to 4" (3 to 10cm) Cable Length Resolution 640 x 480 Illumination 6 adjustable LEDs Still Image Capture Video Recording dependent on camera tester Power 12V 1/2/3A (provided by camera tester)	Wifi	Connect to WiFi cameras & create a WiFi hotspot
48V PoE Output Advanced UTP cable test Power Rechargeable 7.4V 3350mAh Li-ion battery Dimensions 7.2 x 4.3 x 1.4" (183 x 110 x 36.5mm) Weight 11.3oz (320g) SBR2M Camera 8mm Field of View 60° Depth of View 1.2 to 4" (3 to 10cm) Cable Length Resolution 640 x 480 Illumination 6 adjustable LEDs Still Image Capture Video Recording dependent on camera tester Power 12V 1/2/3A (provided by camera tester)	HDMI Output (1080p)	
Advanced UTP cable test Power Rechargeable 7.4V 3350mAh Li-ion battery Dimensions 7.2 x 4.3 x 1.4" (183 x 110 x 36.5mm) Weight 11.3oz (320g) SBR2M Camera 8mm Field of View 60° Depth of View 1.2 to 4" (3 to 10cm) Cable Length 2m (6.5ft) Resolution 640 x 480 Illumination 6 adjustable LEDs Still Image Capture Video Recording dependent on camera tester Power 12V 1/2/3A (provided by camera tester)	DC 12V 3A Power Output	√
Power Rechargeable 7.4V 3350mAh Li-ion battery Dimensions 7.2 x 4.3 x 1.4" (183 x 110 x 36.5mm) Weight 11.3oz (320g) SBR2M Camera 8mm Field of View 60° Depth of View 1.2 to 4" (3 to 10cm) Cable Length 2m (6.5ft) Resolution 640 x 480 Illumination 6 adjustable LEDs Still Image Capture dependent on camera tester Video Recording dependent on camera tester Power 12V 1/2/3A (provided by camera tester)	48V PoE Output	
Dimensions 7.2 x 4.3 x 1.4" (183 x 110 x 36.5mm) Weight 11.3oz (320g) SBR2M Camera 8mm Field of View 60° Depth of View 1.2 to 4" (3 to 10cm) Cable Length 2m (6.5ft) Resolution 640 x 480 Illumination 6 adjustable LEDs Still Image Capture Video Recording dependent on camera tester Power 12V 1/2/3A (provided by camera tester)	Advanced UTP cable test	
Weight 11.3oz (320g) SBR2M Camera 8mm Field of View 60° Depth of View 1.2 to 4" (3 to 10cm) Cable Length 2m (6.5ft) Resolution 640 x 480 Illumination 6 adjustable LEDs Still Image Capture dependent on camera tester Video Recording dependent on camera tester Power 12V 1/2/3A (provided by camera tester)	Power	Rechargeable 7.4V 3350mAh Li-ion battery
SBR2M Camera 8mm Field of View 60° Depth of View 1.2 to 4" (3 to 10cm) Cable Length 2m (6.5ft) Resolution 640 x 480 Illumination 6 adjustable LEDs Still Image Capture dependent on camera tester Video Recording dependent on camera tester Power 12V 1/2/3A (provided by camera tester)	Dimensions	7.2 x 4.3 x 1.4" (183 x 110 x 36.5mm)
Camera 8mm Field of View 60° Depth of View 1.2 to 4" (3 to 10cm) Cable Length 2m (6.5ft) Resolution 640 x 480 Illumination 6 adjustable LEDs Still Image Capture dependent on camera tester Video Recording dependent on camera tester Power 12V 1/2/3A (provided by camera tester)	Weight	11.3oz (320g)
Field of View 60° Depth of View 1.2 to 4" (3 to 10cm) Cable Length 2m (6.5ft) Resolution 640 x 480 Illumination 6 adjustable LEDs Still Image Capture Video Recording dependent on camera tester Power 12V 1/2/3A (provided by camera tester)		SBR2M
Depth of View 1.2 to 4" (3 to 10cm) Cable Length 2m (6.5ft) Resolution 640 x 480 Illumination 6 adjustable LEDs Still Image Capture dependent on camera tester Video Recording dependent on camera tester Power 12V 1/2/3A (provided by camera tester)	Camera	8mm
Cable Length 2m (6.5ft) Resolution 640 x 480 Illumination 6 adjustable LEDs Still Image Capture dependent on camera tester Video Recording dependent on camera tester Power 12V 1/2/3A (provided by camera tester)	Field of View	60°
Resolution 640 x 480 Illumination 6 adjustable LEDs Still Image Capture dependent on camera tester Video Recording dependent on camera tester Power 12V 1/2/3A (provided by camera tester)	Depth of View	1.2 to 4" (3 to 10cm)
Illumination 6 adjustable LEDs Still Image Capture dependent on camera tester Video Recording dependent on camera tester Power 12V 1/2/3A (provided by camera tester)	Cable Length	2m (6.5ft)
Still Image Capture dependent on camera tester Video Recording dependent on camera tester Power 12V 1/2/3A (provided by camera tester)	Resolution	640 x 480
Video Recording dependent on camera tester Power 12V 1/2/3A (provided by camera tester)	Illumination	6 adjustable LEDs
Power 12V 1/2/3A (provided by camera tester)	Still Image Capture	dependent on camera tester
12V 1/2/3A (provided by Garriera tester)	Video Recording	dependent on camera tester
Interface BNC	Power	12V 1/2/3A (provided by camera tester)
	Interface	BNC
Dimensions Camera & Cable: 6.5ft x 0.3" (2m x 8mm)	Dimensions	Camera & Cable: 6.5ft x 0.3" (2m x 8mm)
LED Thumbwheel: 2x0.5x0.25" (51x13x6.4mm)		LED Thumbwheel: 2x0.5x0.25" (51x13x6.4mm)
Weight 5.6oz (159g)	Weight	5.6oz (159g)





