Wohler VIS 350 Service Camera

TECHNICAL DATA

Monitor

Dimensions housing	7" x 4.5" x 1.3"
TFT-Display	7" / 16:9 format
Video-Out	FBAS signal
Weight	1 lbs

Power Supply

Power supply	Space for 2 rechargeable batteries, each 12 V or via power pack
Battery operating time	Max. 2 rechargeable batteries, each 120 mins. = 4 h (battery status in display)

Pan & tilt 1.5" dia color camera head

Type	1/3" COLOR CMOS
Pixels	656 x 492 (NTSC)
Light sensitivity	0.5 Lux
Lens	f = 0.09", F = 2.5
Viewing angle	115°
Light source	12 white LEDs
Degree of protection	Waterproof to IP 67
Dimensions	1 1/2" dia x 2"
Operating temperature	32...104 °F, RH 95 % MAX
Storage temperature	-4...122 °F, RH 95 % MAX

Locator transmitter

Transmission frequency	8.9 kHz

Push rod

Length	100 ft.
Diameter	0.33"

Plastic case

Dimensions	20" x 17" x 7" (l x w x h)
Weight	18 lbs

Distance measurement

Wohler VIS 350 / VIS 300	Electronic meter counter

Locator receiver

Display	Graphic visualization of transmitted position

Output impedance

Headphones	32 Ohm
Power supply	12 V MiMH battery (rechargeable)
Operating temperature	32...104 °F
Storage temperature	14 °F...104 °F
Weight	1.3 lbs
Dimensions	13" x 6" x 3" cm (l x w x h)

Memory (Wohler VIS 350)

Recording	4 GB SD card (2.5 h recording capacity)
Interface	Mini USB port

Find Quality Products Online at: www.GlobalTestSupply.com sales@GlobalTestSupply.com