



HYDROCARBON MANIFOLDS WITH THERMOPLASTIC SERVICE HOSES



33518-TP



93518-TP



92518-53-1/4TP



44241-TPC

BRASS R600a, R290 & R134a 2-WAY MANIFOLD GAUGE SETS

- Large 3 1/8" gauges (PSI/F) with easy to read temperatures scales
- Includes 2 mm thermoplastic service hoses with 1/4" SAE female swivel fittings for maximum precision on small capacity systems

| | |
|---|---|
| <<POPULAR>> 33518-TP | Brass 2-way manifold gauge set with (3) 18" thermoplastic service hoses packaged in a clamshell |
| 33524-TP | Brass 2-way manifold gauge set with (3) 24" thermoplastic service hoses packaged in a clamshell |
| 33503 | Brass 2-way manifold with 3 1/8" gauges only |
| 51350 | R600a, R290, R134a (PSI/F) low side (3 1/8") replacement gauge |
| 51500 | R600a, R290, R134a (PSI/F) high side (3 1/8") replacement gauge |

ALUMINUM R600a, R290 & R134a 2-WAY MANIFOLD GAUGE SETS

- Large 3 1/8" gauges (PSI/F) with easy to read temperatures scales
- Includes 2 mm thermoplastic service hoses with 1/4" SAE female swivel fittings for maximum precision on small capacity systems

| | |
|-----------------|--|
| 93518-TP | Aluminum 2-way manifold gauge set with (3) 18" thermoplastic service hoses packaged in a clamshell |
| 93524-TP | Aluminum 2-way manifold gauge set with (3) 24" thermoplastic service hoses packaged in a clamshell |
| 51303 | Aluminum 2-way manifold with 3 1/8" gauges only |
| 51350 | R600a, R290, R134a (PSI/F) low side (3 1/8") replacement gauge |
| 51500 | R600a, R290, R134a (PSI/F) high side (3 1/8") replacement gauge |

ALUMINUM R600a, R290 & R134a SINGLE BALL VALVE MANIFOLD

- Large 3 1/8" gauges (PSI/F) with easy to read temperatures scales
- Includes 2 mm thermoplastic service hoses with 1/4" SAE female swivel fittings with depressor for maximum precision on small capacity systems

| | |
|---|---|
| <<POPULAR>> 92518-53-1/4TP | 1/4" single ball valve manifold with (1) 18" thermoplastic service hose packaged in a clamshell |
| 92524-53-1/4TP | 1/4" single ball valve manifold with (1) 24" thermoplastic service hose packaged in a clamshell |
| 92103-53-1/4 | 1/4" single ball valve manifold |
| 51350 | R600a, R290, R134a (PSI/F) low side (3 1/8") replacement gauge |

THERMOPLASTIC SERVICE HOSE ASSEMBLIES - 1/4" SAE FEMALE SWIVEL FITTING

- EN 1736 and ISO 13971 - Class 2
- Inner Diameter 2 mm
- Outer Diameter 5.9 mm
- Tolerances 0.1 mm
- Bending Radius 10 mm
- Max Allowable Pressure 60 bar (870 psi)
- Working Temperature 120°C
- Min/Max Allowable Temperature -40 to 130°C
- Weight 25 g/m

| | |
|--|--|
| <<POPULAR>> 44180-TPC | Set of 3-18" (450 mm) thermoplastic service hoses with 1/4" SAE female swivel fittings |
| 44240-TPC | Set of 3-24" (600 mm) thermoplastic service hoses with 1/4" SAE female swivel fittings |
| 44181-TPC | 18" (450 mm) thermoplastic service hose with 1/4" SAE female swivel fittings |
| 44241-TPC | 24" (600 mm) thermoplastic service hose with 1/4" SAE female swivel fittings |

* All gauges above are available with shock resistant gauge protectors – to order, add -G after the Part#