

SC2500w Recirculating Cooler

The SemiChill series offers powerful recirculating coolers. These units have been especially designed for applications in the semiconductor industry. Five models are available, with cooling capacities from 2.5 to 10 kW (air- or water-cooled). Working temperature ranges from +5 to +35 °C which can optionally be extended from -20 to +130 °C.

Also available is a selection of powerful pumps. The units can be modified to provide heater capacities up to 5 kW. Selection between different electronic modules to conform to simple or high demands such as, for example flow rate and conductivity measurement, external temperature control or integration of the coolers via analogue signals, RS232, devicenet or ethernet. A large range of accessories and options including DI filters, microfilters, USB adapters, etc. is available.



Your advantages

- For the most demanding applications
- No side vents, instruments can be placed right next to other equipment
- Handles and castor make relocation easy
- Industrial grade mains power switch and emergency cut-off
- Pressure Indicator
- Front filling port
- Low noise level
- Precise PID temperature control
- ATC3 3-Point-Calibration
- Warning and safety functions
- Modular design allows selection between different options

Technical data

Available voltage versions		Bath	
Order No.	9 5XX 026	Bath tank	Stainless steel
Available voltage versions:			
9 5XX 026.03			
9 5XX 026.13			
Cooling		Other	
Cooling of compressor	1-stage Water	Sound pressure level dbA	65
Cooling water pressure max. bar	6	Classification	Classification III (FL)
Cooling water difference pressure bar	3.5 ... 6	IP Code	IP 21
Cooling water consumption l/min	5	Pump type	Immersion Pump
Electronics		Dimensions and volumes	
Temperature setting	Keypad	Weight kg	122.5
		Cooling Water Connection in	G¾
		Barbed fittings inner diameter	¾"
		Dimensions cm (W x L x H)	49 x 62 x 105
		Filling volume l	21 ... 33
		Pump connections	NTP¾" male
Temperature values			
Working temperature range °C	-20 ... +80		
Temperature stability °C	±0.1		
Ambient temperature °C	5 ... 40		

Performance values

230V/50Hz (Schuko Plug - CEE 7/4 Plug Type F)

230V/50Hz				
Heating capacity			depends on options	
Cooling capacity (Ethanol)				
°C	20	0	-10	
kW	2.5	1.5	0.9	
Pump capacity flow rate			depends on options	
Pump capacity flow pressure			depends on options	
Viscosity max. cST			30	
Refrigerant			R452A	
Filling volume g			750	
Global Warming Potential for R452A			2140	
Carbon dioxide equivalent t			1.605	

208-230V/60Hz (Nema N6-20 Plug)

208V/60Hz				
Heating capacity			depends on options	
Cooling capacity (Ethanol)				
°C	20	0	-10	
kW	2.5	1.5	0.9	
Pump capacity flow rate			depends on options	
Pump capacity flow pressure			depends on options	
Viscosity max. cST			30	
Refrigerant			R452A	
Filling volume g			750	
Global Warming Potential for R452A			2140	
Carbon dioxide equivalent t			1.605	

230V/60Hz				
Heating capacity			depends on options	
Cooling capacity (Ethanol)				
°C	20	0	-10	
kW	2.5	1.5	0.9	
Pump capacity flow rate			depends on options	
Pump capacity flow pressure			depends on options	
Viscosity max. cST			30	
Refrigerant			R452A	
Filling volume g			750	
Global Warming Potential for R452A			2140	
Carbon dioxide equivalent t			1.605	

All Benefits



100 % Cooling capacity
‘Active Cooling Control’ for cooling available throughout the entire working temperature range, fast cool-down even at higher temperatures



Process. Under control.
Full regulation of the dynamics control, access to all important control parameters for individual process optimization.



Intelligent temperature control.
Intelligent cascade control - automatic and self-optimizing adaptation of the PID control parameters with external stability of +/- 0.05 °C.



For higher demands
PID Temperature control with drift compensation and adjustable parameters, improved temperature stability for external applications, temperature stability ±0.01 °C internal, <±0.1 °C external.




Control from the external application
External Pt100 sensor connection for precise measurement and control directly in the external application



ATC3. Calibration.
'Absolute Temperature Calibration' for compensating a physically caused temperature difference, 3-point calibration.



Early warning system for high/low temperature limits
Maximum safety for applications, optical and audible alarm, convertible to automated cut-off function



Connection of additional equipment
Stakei connections for solenoid valve, HSP booster pump and HST booster heater



For flammable bath fluid
Classification III (FL) according to DIN 12876-1



Precise
PID Temperature control with set control parameters, temperature stability $\pm 0.02 \dots \pm 0.2$ °C



Services 24/7.



Quick start.
Individual JULABO consultation and comprehensive manuals at your disposal.



100% Checked.
100% testing. 100% quality. Each JULABO Circulator undergoes thorough quality testing before leaving the factory.



Satisfied customers.
11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified JULABO support.



Green technology.
Development consistently applied environmentally friendly materials and technologies.



JULABO. Quality.
Highest standards of quality for a long product life.



Clever pump system
Reliable and consistent pump capacity, electronically adjustable pump stages