

FL601 Recirculating Coolers for installation below a lab bench

The compact FL models are suited for a wide variety of cooling tasks. Installation under a lab bench saves valuable space. 2 variants: Air-cooled (FL) and water-cooled (FLW).



Your advantages

- Ergonomic design and easy operation
- Splash-proof keypad
- Large, bright LED display
- Reliable Microprocessor PID temperature control
- Powerful immersion pumps, suitable for continuous operation
- Permissible temperature in return line +80°C
- Easy filling and Drain tap easily accessible
- Low liquid level protection with optical and audible alarm signal
- Integrated stainless steel bath tanks
- Removable ventilation grid
- Front drain
- No side vents, instruments can be placed right next to other equipment
- RS232 interface for PC connection
- IP class according to IEC 60529: 21
- Alarm output, potential-free change-over contact (max. 30 VA)

Technical data

Available voltage versions		Bath	
Order No.	9 661 006	Bath tank	Stainless steel
Available voltage versions:			
9 661 006.13	230V/60Hz (Nema N6-20 Plug)		
9 661 006.02	115V/60Hz (Nema N5-15 Plug)		
9 661 006.03	230V/50Hz (Schuko Plug - CEE 7/4 Plug Type F)		
9 661 006.04	230V/50Hz (UK Plug Type BS1363A)		
9 661 006.05	230V/50Hz (CH Plug Type SEV 1011)		
Cooling		Other	
Cooling of compressor	1-stage Air	Sound pressure level dbA	55
Electronics		Classification	Classification I (NFL)
Temperature control	PID1	IP Code	IP 21
Temperature display	LED	Pump type	Centrifugal Pump
Temperature setting	Keypad	Dimensions and volumes	
Temperature values		Weight lbs	105.8
Setting the resolution of the temperature display °C	0.1	Barbed fittings inner diameter	8/12 mm
Return flow temperature max. °C	80	Dimensions in. (W × L × H)	12.6 x 19.7 x 24.4
Working temperature range °C	-20 ... +40	Filling volume l	5.5 ... 8
Temperature stability °C	±0.5	Pump connections	M16x1 male

Ambient temperature °C 5 ... 40

Temperature display resolution °C 0.1

Performance values

230V/60Hz (Nema N6-20 Plug)

230V/60Hz

Cooling capacity

°C	20	10	0	-10	-20
kW	0.6	0.5	0.4	0.33	0.2

Refrigerant R449A

Filling volume g 240

Global Warming Potential for R449A 1397

Carbon dioxide equivalent t 0.335

Pump capacity flow rate l/min 23

Pump capacity flow pressure bar 14.5

115V/60Hz (Nema N5-15 Plug)

115V/60Hz

Cooling capacity (Water Glycol)

°C	20	10	0	-10	-20
kW	0.6	0.5	0.4	0.32	0.1

Refrigerant R449A

Filling volume g 260

Global Warming Potential for R449A 1397

Carbon dioxide equivalent t 0.363

Pump capacity flow rate l/min 23

Pump capacity flow pressure bar 14.5

230V/50Hz (Schuko Plug - CEE 7/4 Plug Type F)

230V/50Hz

Cooling capacity (Water Glycol)

°C	20	10	0	-10	-20
kW	0.6	0.5	0.4	0.33	0.2

Refrigerant R452A

Filling volume g 325

Global Warming Potential for R452A 2140

Carbon dioxide equivalent t 0.696

Pump capacity flow rate l/min 23

Pump capacity flow pressure bar 14.5

230V/50Hz (UK Plug Type BS1363A)

230V/50Hz

Cooling capacity

°C	20	10	0	-10	-20
kW	0.6	0.5	0.4	0.33	0.2

Refrigerant R452A

Filling volume g 325

Global Warming Potential for R452A 2140

Carbon dioxide equivalent t 0.696

Pump capacity flow rate l/min 23

Pump capacity flow pressure bar 14.5

230V/50Hz (CH Plug Type SEV 1011)

230V/50Hz

Cooling capacity (Water Glycol)

°C	20	10	0	-10	-20
kW	0.6	0.5	0.4	0.33	0.2

Refrigerant R452A

Filling volume g 325

Global Warming Potential for R452A 2140

Carbon dioxide equivalent t 0.696

Pump capacity flow rate l/min 23

Pump capacity flow pressure bar 14.5

All Benefits

**100% Checked.**

100% testing. 100% quality. Each JULABO Circulator undergoes thorough quality testing before leaving the factory.

**Green technology.**

Development consistently applied environmentally friendly materials and technologies.

**JULABO. Quality.**

Highest standards of quality for a long product life.

**Quick start.**

Individual JULABO consultation and comprehensive manuals at your disposal.

**Precise**

PID Temperature control with set control parameters, temperature stability $\pm 0.02 \dots \pm 0.2$ °C