



Anemometers



Model AVM440

Velometer® Thermal Anemometers Model AVM410

The Model AVM410 is a solid choice for a digital Air Velocity Meter, without compromising accuracy or precision. Excellent for troubleshooting HVAC systems and conducting commissioning work.

Models AVM430 and AVM440

The Model AVM430 and AVM440 are like having multiple meters for the price of one, yet they are simple to operate. Purchase instruments with a straight or articulated probe—all in one compact package.

Features and Benefits

- Accurate air velocity measurement
- Large, easy to read display
- Calibration certificate included

Models AVM430 and AVM440

- Simultaneously measures temperature and velocity
- Displays up to three measurements simultaneously
- Calculates volumetric flow, and actual/standard velocity
- Articulated probe versions available
- Data logging and LogDat2™ downloading software included
- Measures humidity (AVM440)

Applications

- HVAC system performance
- Commissioning
- Plant maintenance
- Critical environment certification
- Duct traverses

Rugged. Reliable. Professional.



Find Quality Products Online at:

www.GlobalTestSupply.com

sales@GlobalTestSupply.com

Anemometers

Thermal Anemometers

Models AVM410, AVM430 and AVM440

Specifications

Models AVM410, AVM430 and AVM440

Velocity

Range (AVM410) 0 to 4,000 ft/min (0 to 20 m/s)

Range (AVM430, AVM440)

0 to 6,000 ft/min (0 to 30 m/s)

Accuracy (AVM410)^{1&2}

±5% of reading or ±5 ft/min (±0.025 m/s),
whichever is greater

Accuracy (AVM430, AVM440)^{1&2}

±3% of reading or ±3 ft/min (±0.015 m/s),
whichever is greater

Resolution

1 ft/min (0.01 m/s)

Duct Size (AVM430, AVM440)

Dimensions

1 to 250 inches in increments of 0.1 in.
(1 to 635 cm in increments of 0.1 cm)

Volumetric Flow Rate (AVM430, AVM440)

Range

Actual range is a function of velocity, and duct size

Temperature

Range (AVM410, AVM430)

0 to 200°F (-18 to 93°C)

Range (AVM440)

14 to 140°F (-10 to 60°C)

Accuracy³

±0.5°F (±0.3°C)

Resolution

0.1°F (0.1°C)

Relative Humidity (AVM440 only)

Range

0 to 95% RH

Accuracy⁴

±3% RH

Resolution

0.1% RH

Wet Bulb Temperature (AVM440 only)

Range

40 to 140°F (5 to 60°C)

Resolution

0.1°F (0.1°C)

Dew Point (AVM440 only)

Range

5 to 120°F (-15 to 49°C)

Resolution

0.1°F (0.1°C)

Instrument Temperature Range

Operating (Electronics)

40 to 113°F (5 to 45°C)

Model AVM410, AVM430 Operating (Probe)

0 to 200°F (-18 to 93°C)

Model AVM440 Operating (Probe)

14 to 140°F (-10 to 60°C)

Storage

-4 to 140°F (-20 to 60°C)

Data Storage Capabilities (AVM430, AVM440)

Range

12,700+ samples and 100 test IDs

Logging Interval (AVM430, AVM440)

1 second to 1 hour

Time Constant (AVM430, AVM440)

User selectable

External Meter Dimensions

3.3 in. x 7.0 in. x 1.8 in. (8.4 cm x 17.8 cm x 4.4 cm)

Meter Weight with Batteries

0.6 lbs. (0.27 kg)

Meter Probe Dimensions

Probe Length 40 in. (101.6 cm)

Probe Diameter of Tip

0.28 in. (7.0 mm)

Probe Diameter of Base

0.51 in. (13.0 mm)

Articulating Probe Dimensions

Articulating Section Length

7.8 in. (19.7 cm)

Diameter of Articulating Knuckle

0.38 in. (9.5 mm)

Power Requirements

Four AA-size batteries or AC adapter

	AVM410	AVM430, AVM430-A	AVM440, AVM440-A
Velocity range 0 to 4000 ft/min (0 to 20.00 m/s)	•		
Velocity range 0 to 6000 ft/min (0 to 30.00 m/s)		•	•
Temperature	•	•	•
Flow		•	•
Humidity, wet bulb, dew point			•
Probe	Straight	Straight or -A articulated	Straight or -A articulated
Variable time constant		•	•
Manual data logging		•	•
Auto save data logging			•
Statistics		•	•
Review data		•	•
LogDat2 downloading software		•	•
Certificate of Calibration	•	•	•

¹ Temperature compensated over an air temperature range of 40 to 150°F (5 to 65°C).

² The accuracy statement begins at 30 ft/min through 4,000 ft/min (0.15 m/s through 20 m/s) for the Model AVM410, and 30 ft/min through 6,000 ft/min (0.15 m/s through 30 m/s) for Models AVM430 and AVM440.

³ Accuracy with instrument case at 77°F (25°C), add uncertainty of 0.05°F/°F (0.03°C/°C) for change in instrument temperature.

⁴ Accuracy with probe at 77°F (25°C). Add uncertainty of 0.1% RH/°F (0.2% RH/°C) for change in probe temperature. Includes 1% hysteresis.

Specifications subject to change without notice.

Alnor Products, TSI Incorporated - 500 Cardigan Road Shoreview, MN 55126-3996 USA
USA Tel: +1 800 424 7427 E-mail: customerservice@alnor.com



Contact your local Alnor Distributor or visit our website www.alnor.com for more detailed specifications.

Find Quality Products Online at:

www.GlobalTestSupply.com

sales@GlobalTestSupply.com