

# Universal AC / DC Photoelectric Sensors

## BX Series



### Features

- Built-in sensitivity adjuster
- Timer function (built-in timer model)
  - ON Delay, OFF Delay, One-shot Delay
- NPN / PNP open collector simultaneous output (DC power Type)
- Self-diagnosis function  
(green lights up in the stable level)
- Built-in reverse power protection circuit and  
output short overcurrent protection circuit
- Wide power supply range:  
Universal 24-240 VDC $\equiv$  / 24-240 VAC $\sim$
- IP66 protection rating (IEC standard)

### Specifications

Model	BX15M-T□-□	BX5M-M□-□	BX3M-P□-□	BX700-D□-□
Sensing type	Through-beam	Retroreflective	Polarized retroreflective	Diffuse reflective
Sensing distance	15 m	0.1 to 5 m <sup>01)</sup>	0.1 to 3 m <sup>02)</sup>	700 mm <sup>03)</sup>
Sensing target	Opaque materials	Opaque materials	Opaque materials	Opaque, translucent materials
Min. sensing target	≥ Ø 15 mm	≥ Ø 60 mm	≥ Ø 60 mm	-
Hysteresis	-	-	-	≤ 20 % of sensing distance
Response time	AC/DC power, relay contact output model: ≤ 20 ms DC power, solid state (transistor) output model: ≤ 1 ms			
Light source	Infrared	Infrared	Red	Infrared
Peak emission wavelength	850 nm	940 nm	660 nm	940 nm
Sensitivity adjustment	YES (Adjuster)	YES (Adjuster)	YES (Adjuster)	YES (Adjuster)
Timer mode <sup>04)</sup>	OFF, ON Delay, OFF Delay, One Shot Delay mode selectable (Switch): 0.1 to 5 sec (Adjuster)			
Operation mode	Light ON mode - Dark ON mode selectable (Switch)			
Indicator	Operation indicator (yellow), self-diagnosis indicator (green), power indicator (yellow) <sup>05)</sup>			
Approval	CE ENEC	CE ENEC	CE ENEC	CE ENEC
Unit weight	Based on the standard model, timer model: weight + 1 g			
AC/DC power	≈ 225 g	≈ 130 g	≈ 148 g	≈ 115 g
DC power	≈ 211 g	≈ 123 g	≈ 141 g	≈ 116 g

01) Reflector (MS-2)

02) Reflector (MS-3)

03) Non-glossy white paper 200 × 200 mm

04) Only for the timer model

05) Only for the emitter

Output method	AC/DC power, relay contact output	DC power, Transistor solid state output
Power supply	24-240 VAC $\sim$ ± 10 % 50/60 Hz 24-240 VDC $\equiv$ ± 10 % (ripple P-P: ≤ 10 %)	12-24 VDC $\equiv$ ± 10 % (ripple P-P: ≤ 10 %)
Power / current consumption	≤ 3 VA	It depends on the sensing type
Through-beam		Emitter: ≤ 50 mA, receiver: ≤ 50 mA
Reflective		≤ 50 mA
Control output	Relay contact output	NPN open collector - PNP open collector simultaneous output
Contact capacity	250 VAC $\sim$ 3 A of resistance load, 30 VDC $\equiv$ 3 A of resistance load	-
Contact composition	1c	
Relay life cycle	Mechanical: ≥ 50,000,000 Electrical: ≥ 100,000	
Load voltage	-	≤ 30 VDC $\equiv$
Load current		≤ 200 mA
Residual voltage		NPN: ≤ 1 VDC $\equiv$ , PNP: ≤ 2.5 VDC $\equiv$
Self-diagnosis output	-	NPN open collector output <sup>01)</sup>
Protection circuit	-	Reverse power protection circuit, output short overcurrent protection circuit

01) Load voltage: ≤ 30 VDC $\equiv$ , load current: ≤ 50 mA, residual voltage: ≤ 1 VDC $\equiv$  (50 mA), ≤ 0.4 VDC $\equiv$  (16 mA)



View product detail

<b>Insulation resistance</b>	≥ 20 MΩ (500 VDC≡ megger)	
<b>Insulation type</b>	Double or strong insulation (dielectric voltage between the measured input and the power : 1.5 kV)	-
<b>Noise immunity</b>	± 1,000 VDC≡ the square wave noise (pulse width: 1 μs) by the noise simulator	±240 VDC≡ the square wave noise (pulse width: 1 μs) by the noise simulator
<b>Dielectric strength</b>	1,500 VAC~ 50/60 Hz for 1 min	
<b>Vibration</b>	1.5 mm double amplitude at frequency of 10 to 55 Hz (for 1 min) in each X, Y, Z direction for 2 hours	
<b>Vibration (malfunction)</b>	1.5 mm double amplitude at frequency of 10 to 55 Hz (for 1 min) in each X, Y, Z direction for 10 min	
<b>Shock</b>	500 m/s <sup>2</sup> (≈ 50 G) in each X, Y, Z direction for 3 times	
<b>Shock (malfunction)</b>	100 m/s <sup>2</sup> (≈ 10 G) in each X, Y, Z direction for 3 times	
<b>Ambient illuminance (receiver)</b>	Sunlight: ≤ 11,000 lx, incandescent lamp: ≤ 3,000 lx	
<b>Ambient temperature</b>	-20 to 55 °C, storage: -25 to 70 °C (no freezing or condensation)	
<b>Ambient humidity</b>	35 to 85 %RH, storage: 35 to 85 %RH (no freezing or condensation)	
<b>Protection rating</b>	IP66 (IEC standard)	
<b>Connection</b>	Terminal type	
<b>Material</b>	Case, lens cover: PC, sensing part: Acrylic, bracket: SPCC, bolt: SCM, nut: SCM	