

Residential/Commercial Combustion Analyzer for Oil-Fired Appliances

C165+011

Residential/Commercial Combustion Analyzer for Oil-Fired Appliances





10 YEAR VARRANTY



Functions

- Measures: CO, CO2, Differential Pressure, Flue and Inlet Temperature
- Calculates: Differential Temperature, Efficiency (Net, Gross), Excess Air
- Kit Measures: Flue Gas Smoke to see if it is within normal range

Features

- · Backed by UEi Service+
- Up to 10-Year warranty with annual recertification
- LINK to wireless probes
- Flow and Return Probes
- 4 types of sensor protection
- NOx filtered & H2 Compensated CO sensor (10,000ppm range)
- Over-range protection pump
- Low Flow Detection to protect reading accuracy
- Compatible with DTHA2
- Wireless connection to a Free Printer App (iOS® and Android™ Compatible)
- · Room CO test
- Differential Pressure
- · Heat Exchange test
- · Protective water trap



LINK to wireless Flow and Return pipe clamp probes.





Includes

- Flue Probe (CP2)
- Rechargeable Batteries, 3 (AA)
- USB Charging Cable (AACA5)
- Wireless Pipe Clamp Probes, 2 (WPC2)
- Tubing w/ connector (11000)
- K-Type Thermocouples, 2 (ATT29)
- Smoke Pump Test Kit (SPT1)
- Particle Filter (spare) (17631)
- Carrying Case (AC509)
- Quick Start Guide

See reverse side kit options.



Residential/Commercial Combustion Analyzer for Oil-Fired Appliances

C165+0IL

Specifications

TEMPERATURE MEASUREMENT

Parameter	Range	Resolution	Accuracy
Flue temperature	32° to 1112°F	0.1°F	±(0.3% rdg +3.6°F (2°C))
Inlet temperature (internal sensor)	32° to 112°F	0.1°F	+1.8°C +0.3% rdg
Inlet temperature (external sensor)	32° to 1112°F	0.1°F	+3.6°F +0.3% rdg

FLUE GAS

Parameter	Range	Resolution	Accuracy
Oxygen	0 to 21%	0.1%	+0.3% Volume
Carbon Monoxide	0 to 2000ppm		±3ppm or ±5% of rdg
	2000 to 9999ppm	1ppm	±10% of rdg
	2000 to 9999ppm		Unspecified
Carbon Dioxide	0 to 20%	0.1%	0.3% rdg
Efficiency (Net or Gross)	0 to 99.9%	0.1%	+1.0% rdg
Efficiency High (C)	0 to 119.9%	0.1%	+1.0% rdg
Excess Air	0 to 250%	0.1%	+0.2% rdg
CO/CO2 ratio	0 to 0.999%	0.0001	+5% rdg

PRESSURE (DIFFERENTIAL)

Parameter	Range	Resolution	Accuracy	
Pressure (Differential)	±80mbar	±80mbar 0.1mbar		
PRE-PROGRAMMED FUELS	Natural Gas, Propane, Butane, LPG, Light Oils (28/35sec), Wood Pellets, Town Gas, Coke Gas, Bio Oil, Bio Gas			
USER PROGRAMMED FUELS	5 User defined fuels			
STORAGE CAPACITY	30 tests			

C165+OIL Available Kits Options	C165+N	C165+NKIT	C165+0IL	C165+NOILKIT
UPC#	053533509175	053533509205	053533509199	053533509229
Analyzer / flue probe	•	•	•	•
Batteries / USB charging cable	•	•	•	•
Quick start guide	•	•	•	•
Hard case	•	•	•	•
2 K-type thermocouples / spare particle filter	•	•	•	•
Pressure tubing	•	•	•	•
2 Wireless pipe clamp probes	•	•	•	•
IR thermal printer w/ spare paper roll		•		•
Smoke pump test kit			•	•