


HIOKI

CLAMP METER Series




CLAMP METERS

Find Quality Products Online at:

www.GlobalTestSupply.com

sales@GlobalTestSupply.com



Remarkable Ease of Use New "Slim Jaw" Design

Innovative slim jaw resolves worksite issues such
as crowded wiring to deliver safe,
accurate and high-performance testing.

CM4375-50



Traditional design



Easily Clamp Within Crowded Cables with
New Slim Jaw Design



CM4375-50

34 mm=1.34 in



CM4141-50

55 mm=2.17 in



CM3289

33 mm=1.30 in



CM3281
CM3291

46 mm=1.81 in



CM4001

24 mm=0.94 in

Safe, Durable, Reliable

**-25°C to 65°C
operating temperature^{*1}**



CM4000 Series can be used in freezing temperatures or on the hottest summer days.

CAT IV 600V^{*1}



Safely measure embedded cables and electric panels with a maximum rated voltage to earth of 600V

**Dustproof and
waterproof performance^{*2}**




International Protection Code: IP54 (while in storage, or when measuring the current in an insulated conductor). Measurement functionality is maintained despite exposure to sand or dust as well as water droplets.

NEW

**DC HIGH VOLTAGE PROBE P2000
for CAT III 2000 V^{*3}**



Safe Inspection of Solar Installations with High Voltage



Solar installations (also known as photovoltaic or PV installations) are becoming increasingly high-voltage in order to reduce costs and improve the efficiency of power generation systems. As a result, it is important to select measuring instruments that support higher voltage measurement to protect the safety of inspection workers. The P2000 enables high voltage measurement up to CAT III 2000 V by simply connecting to a compatible Hioki clamp meter or digital multimeter.

Why is CAT III 2000 V capability necessary?



According to the standards for Photovoltaic (PV) module safety qualification (IEC 61730-1), PV modules are treated as the overvoltage category III, and a measuring instrument in the measurement category III is required. Using instruments that can accommodate the appropriate measurement category serves to protect workers and equipment from serious accidents such as electric shock and burnout. Currently, adoption of 1500 V solar installation is growing, but instruments that can accommodate even higher voltages will be necessary in the future as larger and even more efficient systems enter into use. Hioki developed the P2000 to support CAT III 2000 V measurement in response to the near-term prospect of such applications.

^{*1} Supported models : CM4371-50, CM4373-50, CM4375-50, CM4141-50, CM3286-50

^{*2} Supported models : CM4371-50, CM4373-50, CM4375-50

DC High Voltage Probe P2000

Compatible models with DC HIGH V PROBE mode

(DC HIGH V PROBE mode: conversion display in terms of partial pressure ratio)



CM4371-50



CM4373-50



CM4375-50



CM4141-50

So much more than just wireless

Wireless connectivity leading to versatility

Using Bluetooth® communication with the Z3210*1

Install the Wireless Adapter Z3210 to enable Bluetooth® communications.

With the Z3210, you can transfer data directly to an Excel® file and pair the instrument with GENNECT Cross.



Attach to enable Bluetooth® wireless technology



Transport to the Excel® file




Transport to GENNECT Cross



Z3210
For more details

Manage measurement data using GENNECT Cross*2

Pair clamp meters built in with Bluetooth(R) wireless technology with the free GENNECT Cross mobile app to upload data to your mobile device for further data management, processing and reporting.



- Save data and create reports right on the App
- Share data via cloud services or E-mail

Bluetooth® communications



Transfer data to a tablet wirelessly



Take a picture of the test location and map measured values on it



Verify current waveforms on your mobile device



Visualize intermittent GFCI and RCD trips
Review trip times and maximum current values



Harmonic analysis for troubleshooting

*1 Supported models : CM4371-50, CM4373-50, CM4375-50, CM4141-50, CM3286-50, CM4001, CM4002, CM4003

*2 Supported models : When the Z3210 is installed on a compatible model described above*1

Downloading GENNECT Cross

Data can be downloaded to tablets and smartphones using Hioki's dedicated apps available from the Google Play or App Store.

Search for "HIOKI" and download the "GENNECT Cross" app.

*Android, Google Play and the Google Play logo are trademarks of Google Inc.

*iOS is a registered trademark of Apple Technology, Inc. and/or its affiliates in the United States and certain other countries.

*iPhone, iPad, iPad mini, iPad Pro and iPod touch are trademarks of Apple Inc.

*Apple and the Apple logo are trademarks of Apple Inc. App Store is a service mark of Apple Inc.

*Microsoft, Windows, Windows Vista, and Excel are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

*Company names and Product names appearing in this catalog are trademarks or registered trademarks of various companies.

*The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by HIOKI E.E. CORPORATION is under license.

*For the latest information about countries and regions where wireless operation is currently supported, please visit the Hioki website.



GENNECT
Cross
For more details



Lineup

Measurement type		AC / DC Current				
Model		CM4371-50	CM4373-50	CM4375-50	3287	3288 3288-20
Appearance						
Core jaw diameter		φ33 mm (1.30 in)	φ55 mm (2.17 in)	φ34 mm (1.34 in)	φ35 mm (1.38 in)	φ35 mm (1.38 in)
AC measurement system		True RMS	True RMS	True RMS	True RMS	MEAN Value True RMS (-20)
Frequency characteristics		10 Hz to 1 kHz	10 Hz to 1 kHz	10 Hz to 1 kHz	10 Hz to 1 kHz	10 Hz to 500 Hz
Measurement parameters	AC current (Resolution) Guaranteed accuracy range	600 A (0.01) 1 A to 600 A	2000 A (0.1) 1 A to 2000 A	1000 A (0.1) 1 A to 999.9 A	100 A (0.01) Full display range ³	1000 A (0.1) Full display range ³
	DC current (Resolution)	600 A (0.01)	2000 A (0.1)	999.9 A (0.1)	100 A (0.01)	1000 A (0.1)
	AC Voltage	1000 V	1000 V	1000 V	600 V	600 V
	DC Voltage	2000 V ¹	2000 V ¹	2000 V ¹	600 V	600 V
	Power	1200 kVA (DC) ¹	4000 kVA (DC) ¹	2000 kVA (DC) ¹	N / A	N / A
	Resistance	6 MΩ	6 MΩ	6 MΩ	42 MΩ	42 MΩ
	Temperature	-40°C to 400°C	-40°C to 400°C	-40°C to 400°C	N / A	N / A
	Electrostatic capacity	✓	✓	✓	N / A	N / A
	Frequency	999.9 Hz	999.9 Hz	999.9 Hz	N / A	N / A
	Rush current	✓	✓	✓	N / A	N / A
	Continuity check	✓	✓	✓	✓	✓
	Diode check	✓	✓	✓	N / A	N / A
	Non-Contact Voltage	✓	✓	N / A	N / A	N / A
Low-pass filter		✓	✓	✓	N / A	N / A
Auto power off		✓	✓	✓	✓	✓
Auto range		✓	✓	✓	✓	✓
Data hold		AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	MANUAL	MANUAL
Automatic AC/DC detection		✓	✓	✓	N / A	N / A
MAX / MIN / AVG		✓	✓	✓	N / A	N / A
Output		N / A	N / A	N / A	N / A	N / A
Bluetooth® communication		✓ (with Z3210)	✓ (with Z3210)	✓ (with Z3210)	N / A	N / A
Backlight		✓	✓	✓	N / A	N / A
Display refresh rate		5 times / s	5 times / s	5 times / s	2.5 times / s	2.5 times / s
Safety standard category		CAT IV 600 V CAT III 1000 V	CAT IV 600 V CAT III 1000 V	CAT IV 600 V CAT III 1000 V	V: CAT III 300 V A: CAT III 600 V	V: CAT III 300 V A: CAT III 600 V
Safety standard category (with P2000)		CAT IV 1000 V CAT III 2000 V	CAT IV 1000 V CAT III 2000 V	CAT IV 1000 V CAT III 2000 V	N / A	N / A
CE		✓	✓	✓	✓	✓
Dustproof and waterproof		IP54 ²	IP54 ²	IP54 ²	N / A	N / A
Drop proof		N / A	N / A	N / A	N / A	N / A
Power supply		LR03 x2 Alkaline	LR03 x2 Alkaline	LR03 x2 Alkaline	CR2032 x1 Coin type	CR2032 x1 Coin type
Dimensions (W × H × D)		65 × 215 × 35 mm 2.56 × 8.46 × 1.38 in	65 × 250 × 35 mm 2.56 × 9.84 × 1.38 in	65 × 242 × 35 mm 2.56 × 9.53 × 1.38 in	57 × 180 × 16 mm 2.24 × 7.09 × 0.63 in	57 × 180 × 16 mm 2.24 × 7.09 × 0.63 in
Weight		340 g / 12.0 oz	530 g / 18.7 oz	350 g / 12.3 oz	170 g / 6.0 oz	150 g / 5.3 oz

Size comparison



*1: Only when DC HIGH VOLTAGE PROBE P2000 is used *2: While in storage, or when measuring the current in an insulated conductor. Do not use when wet. 3: displayed 0 with below 0.06

Measurement type		AC Current					Leakage Current		AC Power
Model		CM4141-50	3280-10F	CM3289	CM3281	CM3291	CM4001	CM4002 CM4003	CM3286-50
Appearance									
Core jaw diameter		φ55 mm (2.17 in)	φ33 mm (1.30 in)	φ33 mm (1.30 in)	φ46 mm (1.81 in)	φ46 mm (1.81 in)	φ24 mm (0.94 in)	φ40 mm (1.57 in)	φ46 mm (1.81 in)
AC measurement system		True RMS	MEAN Value	True RMS	MEAN Value	True RMS	True RMS	True RMS	True RMS
Frequency characteristics		45 Hz to 1 kHz	50 / 60 Hz	40 Hz to 1 kHz	50 / 60 Hz	40 Hz to 1 kHz	40 Hz to 1 kHz	15 Hz to 2 kHz	45 Hz to 1 kHz
Measurement parameters	AC current (Resolution) Guaranteed accuracy range	2000 A (0.01) 1 A to 2000 A	1000 A (0.01) 4 A to 1000 A	1000 A (0.01) 4 A to 1000 A	2000 A (0.01) 4 A to 1999 A	2000 A (0.01) 4 A to 1999 A	600 A (0.01mA)) 0.6 mA to 600 A	200 A (0.001mA) 0.06 mA to 200 A	600 A (0.001) 0.06 A to 600 A
	DC current (Resolution)	N / A	N / A	N / A	N / A	N / A	N / A	N / A	N / A
	AC Voltage	1000 V	600 V	600 V	600 V	600 V	N / A	N / A	600 V
	DC Voltage	2000 V ¹	600 V	600 V	600 V	600 V	N / A	N / A	N / A
	Power	N / A	N / A	N / A	N / A	N / A	N / A	N / A	360 kW (AC)
	Resistance	6 MΩ	42 MΩ	42 MΩ	42 MΩ	42 MΩ	N / A	N / A	N / A
	Temperature	-40°C to 400°C	N / A	N / A	N / A	N / A	N / A	N / A	N / A
	Electrostatic capacity	✓	N / A	N / A	N / A	N / A	N / A	N / A	N / A
	Frequency	999.9 Hz	N / A	N / A	N / A	N / A	999.9 Hz	2000 Hz	999.9 Hz
	Rush current	✓	N / A	N / A	N / A	N / A	✓	✓	N / A
	Continuity check	✓	✓	✓	✓	✓	N / A	N / A	N / A
	Diode check	✓	N / A	N / A	N / A	N / A	N / A	N / A	N / A
	Non-Contact Voltage	N / A	N / A	N / A	N / A	N / A	N / A	N / A	N / A
Low-pass filter		✓	N / A	N / A	N / A	N / A	✓	✓	N / A
Auto power off		✓	✓	✓	✓	✓	✓	✓	✓
Auto range		✓	✓	✓	✓	✓	✓	✓	✓
Data hold		AUTO / MANUAL	MANUAL	MANUAL	MANUAL	MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL
Automatic AC/DC detection		✓ (Voltage only)	N / A	N / A	N / A	N / A	N / A	N / A	N / A
MAX / MIN / AVG		✓	N / A	N / A	N / A	N / A	✓	✓	✓
Output		N / A	N / A	N / A	N / A	N / A	N / A	✓ (CM4003 only)	N / A
Bluetooth® communication		✓ (with Z3210)	N / A	N / A	N / A	N / A	✓ (with Z3210)	✓ (with Z3210)	✓ (with Z3210)
Backlight		✓	N / A	N / A	N / A	N / A	✓	✓	✓
Display refresh rate		5 times / s	2.5 times / s	2.5 times / s	2.5 times / s	2.5 times / s	5 times / s	5 times / s	2 times / s
Safety standard category		CAT IV 600 V CAT III 1000 V	V: CAT III 300 V A: CAT IV 300 V	V: CAT III 300 V A: CAT IV 300 V	V: CAT III 300 V A: CAT IV 300 V	V: CAT III 300 V A: CAT IV 300 V	CAT III 300 V	CAT IV 300 V (CM4002) CAT III 600 V (CM4002) CAT III 300 V (CM4003)	CAT IV 600 V CAT III 1000 V
Safety standard category (with P2000)		CAT IV 1000 V CAT III 2000 V	N / A	N / A	N / A	N / A	N / A	N / A	N / A
CE		✓	✓	✓	✓	✓	✓	✓	✓
Dustproof and waterproof		IP50 ²	IP40	N / A	N / A	N / A	N / A	IP40	IP50 ²
Drop proof		N / A	✓	✓	✓	✓	N / A	N / A	N / A
Power supply		LR03 x2 Alkaline	CR2032 x1 Coin type	CR2032 x1 Coin type	CR2032 x1 Coin type	CR2032 x1 Coin type	LR03 x1 Alkaline	LR6 x2 Alkaline	LR03 x2 Alkaline
Dimensions (W × H × D)		65 × 247 × 35 mm 2.56 × 9.72 × 1.38 in	57 × 175 × 16 mm 2.24 × 6.89 × 0.63 in	57 × 181 × 16 mm 2.24 × 7.13 × 0.63 in	57 × 198 × 16 mm 2.24 × 7.80 × 0.63 in	57 × 198 × 16 mm 2.24 × 7.80 × 0.63 in	37 × 160 × 27 mm 1.46 × 6.30 × 1.06 in	64 × 233 × 36 mm 2.52 × 9.17 × 1.41 in	65 × 241 × 35 mm 2.56 × 9.49 × 1.38 in
Weight		300 g / 10.6 oz	100 g / 3.5 oz	100 g / 3.5 oz	103 g / 3.6 oz	103 g / 3.6 oz	115 g / 4.1 oz	400 g / 14.1 oz	450 g / 15.9 oz

New L9300 test leads with integrated cap for greater convenience and safety



L9300
Video



L9300
3D view




Test leads L9300 now incorporate integrated caps. The design lets you change the

AC/DC Current



AC/DC CLAMP METER CM4371-50, CM4373-50, CM4375-50

Product warranty for 3 years
Accuracy guaranteed for 1 year



Included accessories



L9300 C0203

- LR03 Alkaline battery x2
- Instruction manual



WIRELESS ADAPTER
Z3210 (Option)

Attach to enable Bluetooth®
wireless technology

φ35 mm = 1.30 in



NEW
CM4371-50

600 A AC/DC

True RMS

CAT IV 600 V
CAT III 1000 V

With P2000

CAT IV 1000 V DC
CAT III 2000 V DC

With Z3210

Bluetooth®

Please see www.hioki.com
for list of supported regions.

GENNECT Cross

φ55 mm = 2.17 in



NEW
CM4373-50

2000 A AC/DC

True RMS

CAT IV 600 V
CAT III 1000 V

With P2000

CAT IV 1000 V DC
CAT III 2000 V DC

With Z3210

Bluetooth®

Please see www.hioki.com
for list of supported regions.

GENNECT Cross

φ34 mm = 1.34 in



NEW
CM4375-50

1000 A AC/DC

True RMS

CAT IV 600 V
CAT III 1000 V

With P2000

CAT IV 1000 V DC
CAT III 2000 V DC

With Z3210

Bluetooth®

Please see www.hioki.com
for list of supported regions.

GENNECT Cross



DC HIGH VOLTAGE PROBE
P2000 (Option)

Available to measure 2000 V DC

CLAMP ON AC/DC HiTESTER 3287, 3288, 3288-20



Product warranty for 3 years
Accuracy guaranteed for 1 year



Included accessories



L9208 9398

- Coin type lithium battery CR2032x1
- Instruction manual

φ35 mm = 1.38 in



3287

100 A AC/DC

True RMS

V: CAT III 300 V
A: CAT III 600 V

φ35 mm = 1.38 in



3288

1000 A AC/DC

True RMS

V: CAT III 300 V
A: CAT III 600 V

φ35 mm = 1.38 in



3288-20

1000 A AC/DC

True RMS

V: CAT III 300 V
A: CAT III 600 V



For more details

CATS   DISPLAY HOLD AUTO OFF TRUE RMS NCV   MIN MAX PEAK FILTER AUTO AC/DC INRUSH							
Model	CM4371-50	CM4373-50	CM4375-50			Basic accuracy	
Measurement parameters	AC Current	✓	N / A	N / A	20.00 A/600.0 A (guaranteed accuracy range: 1.00 A to 600.0 A)		±1.3% rdg ±0.08 A
		N / A	✓	N / A	600.0 A/2000 A (guaranteed accuracy range: 1.0 A to 2000 A)		±1.3% rdg ±0.3 A
		N / A	N / A	✓	1000 A (guaranteed accuracy range: 1.0 A to 999.9 A)		±1.3% rdg ±0.3 A
	DC Current	✓	N / A	N / A	20.00 A/600.0 A (guaranteed accuracy range: ±1.00A to ±600.0 A)		±1.3% rdg ±0.08 A
		N / A	✓	N / A	600.0 A/2000 A (guaranteed accuracy range: ±1.0A to ±2000 A)		±1.3% rdg ±0.3 A
		N / A	N / A	✓	1000 A (guaranteed accuracy range: ±1.0 A to ±999.9 A)		±1.3% rdg ±0.3 A
	AC + DC Current	✓	N / A	N / A	20.00 A/600.0 A (guaranteed accuracy range: 1.00 A to 600.0 A)		±1.3% rdg ±0.13 A
		N / A	✓	N / A	600.0 A/2000 A (guaranteed accuracy range: 1.0 A to 2000 A)		±1.3% rdg ±1.3 A
		N / A	N / A	✓	1000 A (guaranteed accuracy range: 1.0 A to 999.9 A)		±1.3% rdg ±1.3 A
	AC Voltage	✓	✓	✓	6.000 V/60.00 V/600.0 V/1000 V		±0.9% rdg ±0.003 V
	DC Voltage	✓	✓	✓	600.0 mV/6.000 V/60.00 V/600.0 V/1000 V/2000 V ²		±0.5% rdg ±0.5 mV
	AC + DC Voltage	✓	✓	✓	6.000 V/60.00 V/600.0 V/1000 V		±1.0% rdg ±0.013 V
	DC Power	✓	N / A	N / A	0.0 VA to ±1200 kVA ²		±2.0% rdg ±20 dgt
		N / A	✓	N / A	0.000 kVA to ±4000 kVA ²		±2.0% rdg ±20 dgt
		N / A	N / A	✓	0.000 kVA to ±2000 kVA ²		±2.0% rdg ±0.020 kVA
		Resistance	✓	✓	✓	600.0 Ω/6.000 kΩ/60.00 kΩ/600.0 kΩ/6.000 MΩ	
Temperature	✓	✓	✓	-40.0°C to 400.0°C		±0.5% rdg ±3.0°C	
Electrostatic capacity	✓	✓	✓	1.000 μF/10.00 μF/100.0 μF/1000 μF		±1.9% rdg ±0.005 μF	
Frequency	✓	✓	✓	9.999 Hz/99.99 Hz/999.9 Hz		±0.1% rdg ±0.003 Hz	

Other	Display refresh rate	5 times/s ³				Order code	CM4373-91			
	Operating temperature	-25°C to 65°C, 90% RH or less (non-condensating)					Order code	CM4371-50	CM4371-90	CM4375-91
	Storage temperature	-30°C to 70°C, 90% RH or less (non-condensating)						CM4373-50	CM4373-90	CM4373-92
	Dustproof and waterproof	IP54 ⁴						CM4375-50	CM4375-90	CM4375-92
	Power supply	Alkaline battery LR03 ×2								
	Continuous operating time	40 hours ⁵								
	Dimensions (W × H × D)	CM4371-50: 65 × 215 × 35 mm (2.56 × 8.46 × 1.38 in) CM4373-50: 65 × 250 × 35 mm (2.56 × 9.84 × 1.38 in) CM4375-50: 65 × 242 × 35 mm (2.56 × 9.53 × 1.38 in)								
	Weight	CM4371-50: 340 g (12 oz) CM4373-50: 530 g (18.7 oz) CM4375-50: 350 g (12.3 oz)				Model CM437x-90 includes Z3210 as a set Model CM437x-91 includes P2000 as a set Model CM437x-92 includes P2000, Z3210 as a set				

*1: Excludes CM4375-50 *2: Only when DC HIGH VOLTAGE PROBE P2000 is used *3: Excludes electrostatic capacity, frequency, and temperature

*4: While in storage, or when measuring the current an insulated conductor. Do not use when wet. *5: With backlight and Bluetooth[®] communications turned OFF


CATS   DISPLAY HOLD AUTO OFF TRUE RMS NCV   MIN MAX PEAK FILTER AUTO AC/DC INRUSH						
Model	3287	3288	3288-20	Basic accuracy		
Measurement parameters	AC Current	✓	N / A	N / A	10.00 A/100.0 A (Display range: 0A to 10.00 A/100.0 A)	±1.5% rdg ±5 dgt
		N / A	✓	✓	100.0 A/1000 A (Display range: 0A to 100.0 A/1000 A)	±1.5% rdg ±5 dgt
	DC Current	✓	N / A	N / A	10.00 A/100.0 A	±1.5% rdg ±5 dgt
		N / A	✓	✓	100.0 A/1000 A	±1.5% rdg ±5 dgt
	AC Voltage	✓	✓	✓	4.200 V/42.00 V/420.0 V/600 V	±2.3% rdg ±8 dgt
	DC Voltage	✓	✓	✓	420.0 mV/4.200 V/42.00 V/420.0 V/600 V	±1.3% rdg ±4 dgt
Resistance	✓	✓	✓	420.0 Ω/4.200 kΩ/42.00 kΩ/420.0 kΩ/4.200 MΩ/42.00 MΩ	±2.0% rdg ±4 dgt	
Other	Display refresh rate	2.5 times/s				
	Operating temperature	0°C to 40°C, 80% RH or less (non-condensating)				
	Storage temperature	-10°C to 50°C, 80% RH or less (non-condensating)				
	Dustproof and waterproof	N / A				
	Power supply	Coin type lithium battery CR2032 ×1				
	Continuous operating time	25 hours				
	Dimensions(W × H × D)	57 × 180 × 16 mm (2.24 × 7.09 × 0.63 in)				
Weight	3287: 170 g (6.0 oz), 3288, 3288-20: 150 g (5.3 oz)					
				Order code	3287	
				Order code	3288	
				Order code	3288-20	

AC Current

AC CLAMP METER CM4141-50



Product warranty for 3 years
Accuracy guaranteed for 1 year



Included accessories



L9300 C0203

- LR03 Alkaline battery x2
- Instruction manual



WIRELESS ADAPTER
Z3210 (Option)
Attach to enable Bluetooth®
wireless technology



DC HIGH VOLTAGE PROBE
P2000 (Option)
Available to measure 2000 V DC

φ55 mm = 2.17 in



NEW
CM4141-50

2000 A AC

True RMS

CAT IV 600 V
CAT III 1000 V

With P2000

CAT IV 1000 V DC
CAT III 2000 V DC

With Z3210

Bluetooth®

Please see www.hioki.com
for list of supported regions.

GENNECT Cross

AC CLAMP METER 3280-10F, CM3289, CM3281, CM3291



Product warranty for 3 years
Accuracy guaranteed for 1 year



Included accessory



L9208

- CARRYING CASE (models vary as shown on right)
- Coin type lithium battery CR2032x1
- Instruction manual



φ33 mm = 1.30 in

3280-10F
3280-70F

1000 A AC

MEAN Value

V: CAT III 300 V
A: CAT IV 300 V



L9398 (-10F)
C0205 (-70F)




φ33 mm = 1.30 in

CM3289

1000 A AC

True RMS

V: CAT III 300 V
A: CAT IV 300 V



L9398



φ46 mm = 1.81 in

CM3281
CM3291

2000 A AC

CM3281: MEAN Value
CM3291: True RMS

V: CAT III 300 V
A: CAT IV 300 V



CARRYING CASE

Leakage Current

AC LEAKAGE CLAMP METER CM4001, CM4002, CM4003



Product warranty for 3 years
Accuracy guaranteed for 1 year



WIRELESS ADAPTER
Z3210 (Option)
Attach to enable Bluetooth®
wireless technology



φ24 mm = 0.94 in

CM4001

0.6 mA to 600 A AC

True RMS

CAT III 300 V

Included accessory



CARRYING CASE

- STRAP
- LR03 Alkaline battery x1
- Instruction manual

With Z3210

Bluetooth®

Please see www.hioki.com
for list of supported regions.

GENNECT Cross



φ40 mm = 1.57 in

CM4002

0.06 mA to 200 A AC

True RMS

CAT IV 300 V
CAT III 600 V

Included accessory



C0203

- LR6 Alkaline battery x2
- Instruction manual

With Z3210

Bluetooth®

Please see www.hioki.com
for list of supported regions.

GENNECT Cross



φ40 mm = 1.57 in

CM4003

0.06 mA to 200 A AC

True RMS

CAT III 300 V

Included accessories



C0203 L9097

- LR6 Alkaline battery x2
- Instruction manual
- USB cable

With Z3210

Bluetooth®

Please see www.hioki.com
for list of supported regions.

GENNECT Cross

Functions

For more details



													
Model		CM4141-50					Basic accuracy						
Measurement parameters	AC Current	✓	60.00 A/600.0 A/2000 A (guaranteed accuracy range: 1.00A to 2000 A)					±1.5% rdg ±0.08 A					
	AC Voltage	✓	6.000 V/60.00 V/600.0 V/1000 V					±0.9% rdg ±0.003 V					
	DC Voltage	✓	600.0 mV/6.000 V/60.0 V/600.0 V/1000 V/2000 V ⁻¹					±0.5% rdg ±0.5 mV					
	AC + DC Voltage	✓	6.000 V/60.00 V/600.0 V/1000 V					±1.0% rdg ±0.013 V					
	Resistance	✓	600.0 Ω/6.000 kΩ/60.0 kΩ/600.0 kΩ/6.000 MΩ					±0.7% rdg ±0.5 Ω					
	Temperature	✓	-40.0°C to 400.0°C					±0.5% rdg ±3.0°C					
	Electrostatic capacity	✓	1.000 μF/10.00 μF/100.0 μF/1000 μF					±1.9% rdg ±0.005 μF					
	Frequency	✓	9.999 Hz/99.99 Hz/999.9 Hz					±0.1% rdg ±0.003 Hz					

Display refresh rate	5 times/s ^{*2}
Operating temperature	-25°C to 65°C, 90% RH or less (non-condensating)
Storage temperature	-30°C to 70°C, 90% RH or less (non-condensating)
Dustproof and waterproof	IP50 ^{*3}
Power supply	Alkaline battery LR03 x2
Continuous operating time	48 hours ^{*4}
Dimensions(W × H × D)	65 × 247 × 35 mm (2.56 × 9.72 × 1.38 in)
Weight	300 g (10.6 oz)

Order code **CM4141-50**Order code **CM4141-90**

Model CM4141-90 includes Z3210 as a set

*1: Only when DC HIGH VOLTAGE PROBE P2000 is used *2: Excludes electrostatic capacity, frequency, and temperature

*3: While in storage, or when measuring resistance or current in an insulated conductor in a completely dry condition. Do not use when wet. *4 With backlight and Bluetooth[®] communications turned OFF

CATs   DISPLAY HOLD AUTO OFF TRUE RMS NCV   MIN MAX PEAK FILTER AUTO AC/DC INRUSH													
Model		3280-10F	CM3289	CM3281 · CM3291	Basic accuracy								
Measurement items	AC Current	✓	✓	N / A	42.00 A/420.0 A/1000 A (guaranteed accuracy range: 4.00A to 1000 A)								
	AC Voltage	N / A	N / A	✓	42.00 A/420.0 A/2000 A (guaranteed accuracy range: 4.00A to 1999 A)								
	DC Voltage	✓	✓	✓	4.200 V/42.00 V/420.0 V/600 V								
	Resistance	✓	✓	✓	420.0 mV/4.200 V/42.00 V/420.0 V/600 V								
		✓	✓	✓	420.0 Ω/4.200 kΩ/42.00 kΩ/420.0 kΩ/4.200 MΩ/42.00 MΩ								

Display refresh rate	2.5 times/s
Operating temperature	-25°C to 65°C, 80% RH or less (non-condensating)
Storage temperature	-25°C to 65°C, 80% RH or less (non-condensating)
Dustproof and waterproof	IP40 (EN60529)*2
Power supply	Coin type lithium battery CR2032 x1
Continuous operating time	3280-10F, CM3281: 120 hours CM3289: 70 hours CM3291: 70 hours
Dimensions (W × H × D)	3280-10F: 57 × 175 × 16 mm (2.24 × 6.89 × 0.63 in) CM3289: 57 × 181 × 16mm (2.24 × 7.13 × 0.63 in) CM3281, CM3291: 57 × 198 × 16 mm (2.24 × 7.80 × 0.63 in)
Weight	3280-10F: 100 g (3.5 oz) CM3289: 100 g (3.5 oz) CM3281, CM3291: 103 g (3.6 oz)



3280F, CM3289, CM3291 are compatible with the CT6280 AC Flexible Current Sensor

Φ130mm (5.1 in), 4200 A AC

Model 3280-70F includes 3280-10F AC Clamp Meter and CT6280 AC Flexible Sensor as a set

Order code **3280-10F**Order code **3280-70F**Order code **CM3289**Order code **CM3291**Order code **CM3281**

*1 Excludes 3280F *2 Excludes CM3289, CM3281, CM3291

CATS   DISPLAY HOLD AUTO OFF TRUE RMS NCV   MIN MAX PEAK FILTER AUTO AC/DC INRUSH														
Model		CM4001	CM4002-CM4003	Basic accuracy										
Measurement lists	AC Current	✓	N / A	60.00 mA/600.0 mA/6.000A/60.00A/600.0A (guaranteed accuracy range: 0.60 mA to 600.0A)										±1.5% rdg ±0.05 mA
		N / A	✓	6.000 mA/60.00 mA/600.0 mA/6.000A/60.00A/200.0A (guaranteed accuracy range: 0.060 mA to 200.0A)										±1.0% rdg ±0.005 mA
	Frequency	✓	N / A	999.9 Hz										±1.5% rdg ±0.1 Hz
		N / A	✓	999.9 Hz/2000 Hz										±0.1% rdg ±0.1 Hz

Display refresh rate	5 times/s
Operating temperature	-10°C to 65°C (non-condensating)
Storage temperature	CM4001: -10°C to 65°C (non-condensating) CM4002, CM4003: -30°C to 70°C (non-condensating)
Dustproof and waterproof	CM4002, CM4003: IP40
Power supply	CM4001: LR03 Alkaline battery × 1, 32 hours CM4002, CM4003: LR6 Alkaline battery × 2, 48 hours (LR6 without Z3210)
Continuous operating time	CM4003: AC ADAPTER Z1013 (Option)
Dimensions(W × H × D)	CM4001: 37 × 160 × 27 mm (1.46 × 6.30 × 1.06 in) CM4002, CM4003: 64 × 233 × 36 mm (2.52 × 9.17 × 1.41 in)
Weight	CM4001: 115 g (4.1 oz) CM4002, CM4003: 400 g (14.1 oz)

Includes external output function (CM4003 Only)

Pair with a recorder to capture instantaneous or current waveforms



*Using CONNECTION CABLE L9097 (Accessories)

RMS value output
(RMS mode)

DC 600 mV/f.s.

Waveform output
(WAVE mode)

AC 600 mV/f.s.

Order code **CM4001**Order code **CM4001-90**Order code **CM4002**Order code **CM4002-90**Order code **CM4003**Order code **CM4003-90**Order code **Z3210**

Model CM4001-90, CM4002-90, CM4003-90 includes Z3210 as a set



AC CLAMP POWER METER CM3286-50

Product warranty for 3 years
Accuracy guaranteed for 1 year

φ46 mm=1.81 in



NEW

CM3286-50

AC 600 A

True RMS

CAT IV 600 V
CAT III 1000 V

With Z3210

Bluetooth

Please see www.hioki.com
for list of supported regions.

GENNECT Cross



**WIRELESS ADAPTER
Z3210 (Option)**

**Attach to enable Bluetooth®
wireless technology**

Included accessories



L9257

C0203

- LR03 Alkaline battery x2
- Instruction manual

*1: Harmonics can be displayed using dedicated application software (GENNECT Cross)

*2: While in storage, or when measuring resistance or current in an insulated conductor in a completely dry condition. Do not use when wet.

Order code **CM3286-50**

Order code **CM3286-90**

Model CM3286-90
includes Z3210 as a set

Power (Active/ reactive/ apparent)	Single phase	3.600 kW/36.00 kW/360.0 kW Guaranteed accuracy range: 0.005 kW to 360.0 kW Basic accuracy: $\pm 2.0\%$ rdg ± 7 dgt
	Balanced three-phase 3-wire	7.200 kW/72.00 kW/720.0 kW guaranteed accuracy range: 0.020 kW to 623.5 kW Basic accuracy: $\pm 3.0\%$ rdg ± 10 dgt
	Balanced three-phase 4-wire	10.80 kW/108.0 kW/1080 kW guaranteed accuracy range: 0.040 kW to 1080 kW Basic accuracy: $\pm 2.0\%$ rdg ± 3 dgt
AC Current		6.000 A/60.00 A/600.0 A Basic accuracy: $\pm 1.0\%$ rdg ± 3 dgt
AC Voltage		600.0 V Basic accuracy: $\pm 0.7\%$ rdg ± 3 dgt
Power factor		Single-phase, Balanced three-phase 4-wire: [Regeneration] -1.000 to -0.001, [Consumption] 0.000 to 1.000 Balanced three-phase 3-wire: [Regeneration] -0.001, [Consumption] 0.000 to 1.000
Phase angle		Single-phase, Balanced three-phase 4-wire : [lead] -180.0° to -0.1°, [lag] 0.0° to 179.9° Balanced three-phase 3-wire: [lead] -90.0° to -0.1°, [lag] 0.0° to 90.0°
Frequency		45.0 Hz to 999.9 Hz
Simple Active Energy Consumption (Single-phase)		99.99 Wh/999.9 Wh/9.999 kWh/ 99.99 kWh/999.9 kWh/9999 kWh/
Harmonic ^{*1} (With Z3210)		Voltage or current harmonic levels up to 30th order, content factor, total harmonic distortion ratio
Display refresh rate		2 times/s
Operating temperature		-25°C to 65°C, 80% RH or less (non-condensating)
Storage temperature		-25°C to 65°C, 80% RH or less (non-condensating)
Dustproof and waterproof		IP50 ^{*2}
Power supply		LR03 Alkaline battery x2
Continuous operating time		25 hours
Dimensions (W × H × D)		65 × 241 × 35 mm (2.56 × 9.49 × 1.38 inch)
Weight		450 g (15.9 oz)

Options

**3280-10F
CM3289
CM3291
3287*, 3288*
3288-20***

**CM4371-50
CM4373-50
CM4375-50
CM4141-50
CM3286-50**

1 L9208 Cable length 70 cm (2.3 ft) With the Cap (Red x1, Black x1)

2 CT6280^{*1} $\Phi 130$ mm (5.12 in) 4200 A AC

^{*1}: Not available to use with 3287, 3288, 3288-20

3 L9300 Cable length 95 cm (3.12 ft)

2 L9207-10 Cable length 90 cm (2.95 ft) With the Cap (Red x1, Black x1)

3 L4930 Cable length 120 cm (3.94 ft)

4 L4931 Cable length 150 cm (4.92 ft) with the coupling connector

L4930, L4931 can be used to extend the cable

5 P2000^{*4} Cable length 150 cm (4.92 ft) (Probe side)

^{*4}: Not available to use with CM3286-50

6 DT4910^{*4} -40 to 260°C Sensor length: 80 cm (2.62 ft)

3 L4933² 48 mm (1.89 in)

4 L4934² *2: Remove the cap of L9208 before attaching it

7 L4933³ 48 mm (1.89 in)

8 L4934³ *3: Remove the cap of L9207-10 before attaching it. Slide the guard of the L9300 and attach it in the measurement CAT II.

9 L9243 97 mm (3.82 in)

10 L4932 With the Cap (Red x1, Black x1)

11 L4935

12 L4936

13 L4937 30 mm (1.18 in) Magnet : $\phi 6$ mm (0.24 in)

14 9804 Magnet : $\phi 11$ mm (0.43 in)

15 L4938 With the Cap (Red x1, Black x1) 22 mm (0.87 in), $\phi 3.7$ mm (0.15 in)

16 L4939 1 22 mm (0.87 in) $\phi 3.7$ mm (0.15 in) 2 48 mm (1.89 in) $\phi 2.6$ mm (0.1 in)

17 9290-10

3280-10F, CM3289, CM3281, CM3291, 3287, 3288, 3288-20

- | | |
|---|--|
| 1 | TEST LEAD L9208 |
| 2 | AC FLEXIBLE CURRENT SENSOR CT6280 For 3280-10F, CM3289, CM3281, CM3291 |
| 3 | CONTACT PIN SET L4933 |
| 4 | SMALL ALLIGATOR CLIP SET L4934 |
| 5 | CARRYING CASE 9398 For 3280-10F, CM3289, 3287, 3288, 3288-20 |
| 6 | CARRYING CASE C0205 Bundled accessory for CT6280 |
| 7 | TEST LEADS HOLDER 9209 For 3280-10F, CM3289, 3287, 3288, 3288-20 |



CM4371-50, CM4373-50, CM4375-50, CM4141-50, CM3286-50

- | | |
|----|---|
| 1 | TEST LEAD L9300 |
| 2 | TEST LEAD L9207-10 |
| 3 | CONNECTION CABLE SET L4930 |
| 4 | EXTENSION CABLE SET L4931 |
| 5 | DC HIGH VOLTAGE PROBE P2000 |
| 6 | THERMOCOUPLES(K) DT4910 For CM437x-50 series, CM4141-50 |
| 7 | CONTACT PIN SET L4933 |
| 8 | SMALL ALLIGATOR CLIP SET L4934 |
| 9 | GRABBER CLIP L9243 |
| 10 | TEST PIN SET L4932 |
| 11 | ALLIGATOR CLIP SET L4935 |
| 12 | BUS BAR CLIP SET L4936 |
| 13 | MAGNETIC ADAPTER SET L4937 |
| 14 | MAGNETIC ADAPTER SET 9804 |
| 15 | TEST PIN SET L4938 |
| 16 | BREAKER PIN SET L4939 |
| 17 | CLAMP ON ADAPTER 9290-10 For CM3286-50 |
| 18 | CONNECTION CORD L9257 Combination of L4930 and L4935 |
| 19 | CARRYING CASE C0203 |



CM4002, CM4003

- | | |
|---|-------------------------|
| 1 | CONNECTION CABLE L9097 |
| 2 | CONVERSION ADAPTER 9704 |
| 3 | AC ADAPTER Z1013 |
| 4 | CARRYING CASE C0203 |



About the Marks

	Safety standard measurement categories*
	Drop proof Robust design capable of withstanding a drop from a height of 1 m onto concrete
	Backlight
	Auto power OFF Automatically turns off after a certain time
	Display hold
	True RMS True RMS measurement for accurate measurement of even distorted current waveforms
	Low-pass filter Cuts high frequency content to provide stable numerical values for measurement
	AUTO AC/DC Automatically detects and measures AC and DC voltage
	MAX/MIN/AVG value* Displays the maximum, minimum, and average of the displayed values
	Peak measurement* Displays the wave maximum and minimum peak values
	Flexible current sensor can be connected

*For more detailed information, please refer to the next page.

	AC voltage
	DC voltage
	DCV + ACV
	Frequency
	Resistance
	Capacitance
	Temperature
	ACA current
	DCA current
	DCA + ACA
	DC Power
	Continuity check Buzzer sounds when continuity is detected
	Diode check Displays voltage if in the correct direction, and OVER if in the reverse direction
	Non-Contact Voltage Buzzer sounds when AC voltage is detected
	Inrush (Rush current) Measures inrush current when power is turned on, etc.

*The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by HIOKI E.E. CORPORATION is under license.
Note: Company names and product names appearing in this brochure are trademarks or registered trademarks of various companies.

HIOKI
HIOKI E. E. CORPORATION

HEADQUARTERS

81 Koizumi,
Ueda, Nagano 386-1192 Japan
<https://www.hioki.com/>



Scan for all
regional contact

DISTRIBUTED BY

Find Quality Products Online at:

www.GlobalTestSupply.com

sales@GlobalTestSupply.com