

Mini Feed-Through 15mm

For wire-to-wire connecting in control, automation, instrumentation and power distribution applications.

Altech "miniature" terminal blocks offer tremendous space advantage as demanded by certain wiring configurations.



Terminal Width

Height x Length

Stripping Length

Insulation Material

Type of Connection

Approvals

Wire Range

Voltage Rating

Current Rating

Torque

Other Approvals

Terminal Block

End Plate



Isolation Partition



DIN Rail
for ordering information
refer to pages 90-91

End Stop
for ordering information
refer to page 92



Internal
Jumper




2 pole
3 pole
4 pole
10 pole

Insulated
Internal
Jumper



2 pole
3 pole
4 pole
10 pole

Current
Bars



2 pole
3 pole
4 pole
10 pole
10 pole (breakable)
100 pole

Shorting Sleeve & Screw



External
Jumper




2 pole
3 pole
4 pole
10 pole

Marking Tags



CMT4



6 mm

29 x 27 mm

9 mm

Polyamide 6.6

2 screw clamps & 1 tapped hole
for cross connection



22-10 AWG

0.2-4 sq.mm

22-10 AWG

300 V

500 V

300 V

35 A

32 A

35 A

7 lb-in

0.5 Nm

7 lb-in



Cat. No.

Std. Pk.

CMT4

100

EPCMT4

50

PPCMT4

50



CA602

100

CA727/2

100

CA727/3

100

CA727/4

100

CA727/10

10

CA747/2

100

CA747/3

100

CA747/4

100

CA747/10

10

CA703/1

100

CA704/1

100

CA705/1

100

CA732/10

100

CA732/10-A

100

CA732/100

10

CA607/S/Q

100

CA714/2

100

CA714/3

100

CA714/4

100

CA714/10

20

MT2

100

CGMT4



6 mm

28.5 x 27 mm

9 mm

Polyamide 6.6

2 screw clamps



22-10 AWG

0.2-4 sq.mm

22-10 AWG

400 V

32 A

7 lb-in

0.5 Nm

7 lb-in



AEx eII
Ex eII U

Cat. No.

Std. Pk.

CGMT4

50



MT2

100

COLOR BLOCKS

(other than standard grey)

When ordering please add
color suffix to Cat. No.

Example for color Red: **Cat.No./R**

Color	Ordering Suffix
Red	R
Yellow	Y
Blue	BU
Green	G

Consult Altech for availability:

Orange	O
Beige	BG
Dark Brown	DB
Black	BL
White	W