

CX SERIES

SPRING TERMINAL BLOCKS

SIDE ENTRY FEED THROUGH TERMINAL BLOCKS

CXS2.5



CXSG2.5



Dimensions

Width	5 mm	5 mm
Length	43 mm	43 mm
Height w DIN Rail	35 x 7.5 mm 35 x 15 mm	43.5 mm 51 mm

GROUND TYPE

Technical Data/Ratings

Approvals	   	   E22051460947-7-1	   E22051460947-7-1	
Wire Size (solid stranded)	24-12 AWG	0.2-2.5 mm ²	24-12 AWG	0.2-2.5 mm ²
Voltage Rating	600 V	1000 V	600 V	1000 V
Current Rating	20A	24A	—	—
Insulation Material	Polyamide 66		Polyamide 66	

Installation Instructions

Wire Stripping Length	10 mm	10 mm
Screwdriver	0.5x3 mm	0.5x3 mm

Terminal Blocks

	Cat. No.	Std. Pk.		Cat. No.	Std. Pk.
Grey (standard)	CXS2.5	50	Yellow / Green	CXSG2.5	50
Red R	CXS2.5/R	50			
Blue BU	CXS2.5/BU	50			
Black BL	CXS2.5/BL	50			
Orange O	CXS2.5/O	50			
Green G	CXS2.5/G	50			
Yellow Y	CXS2.5/Y	50			
White W	CXS2.5/W	50			

Accessories

	Cat. No.	Std. Pk.		Cat. No.	Std. Pk.
End Plate	EPCXS2.5	50		EPCXS2.5	50
Partition Plate	—	—		—	—
DIN Rail	2511120 CA701-15/S	20 20		2511120 CA701-15/S	20 20
End Stop	CA702 CA802 CA103	50 50 50		CA702 CA802 CA103	50 50 50
Shorting Link/ Jumpers	2 pole JX2.5/2 3 pole JX2.5/3 4 pole JX2.5/4 10 pole JX2.5/10	100 50 50 10		2 pole JX2.5/2 3 pole JX2.5/3 4 pole JX2.5/4 10 pole JX2.5/10	100 50 50 10
Warning Label	WLX2.5	100		WL2.5	100
Test Plug	TX2.5	50		TX2.5	50
Marking Tag	MT5	100		MT5	100