## VOLTAGE TESTERS

### **ET60**

**Electronic AC/DC Voltage Tester** 





#### **ET250**

Digital AC/DC Voltage and Continuity Tester










#### **ET60 Electronic AC/DC** Voltage Tester

ET60 is a solid-state, low impedance, electronic voltage tester. It measures AC/DC voltages up to 600V. The ET60 does NOT require batteries; it is powered by the applied voltage. It is an excellent choice for testing voltage in electrical circuits, at outlets, in light fixtures or anywhere else where AC/DC voltage testing is required.

- Modern solid-state design
- Does NOT use a battery
- Low impedance
- Integrated test-lead holders (on back)
- TOUGH METER design is water and dust resistant and withstands 9.8 ft. (3m) drops







Voltage Indicator **LEDs** 

LCD Display — with Backlight

Power On/Off

DC Polarity Indicators (indicates AC when both are illuminated)

Worklight Backlight

GFCI Test-Button

**BOTH MODELS WORK WITH MOST** STANDARD REPLACEABLE **TEST-LEADS\*** 

> Test-lead input jacks



Integrated Flashlight

CE LISTEO US

 Automatically selects measurement mode Auto-powers on when

Digital AC/DC Voltage

and Continuity Tester

ET250 is a solid-state, digital

voltage and continuity tester. It

measures AC/DC voltages up to

Additionally, the ET250 tests GFCI

appropriately. The tester includes

flashlight for working in reduced

600V and tests for continuity.

protected circuits to verify that

the GFCI device is functioning

a backlight and integrated

ambient lighting conditions.

- a voltage/continuity measurement is attempted
- Modern solid-state design
- Tests GFCI protected circuits
- Built-in test lead holders
- Backlit LCD display
- Integrated flashlight
- TOUGH METER design is water and dust resistant and withstands 9.8 ft. (3m) drops

IER VOLTAGE

3 3

S

RS







ET60	FEATURES	ET250
9.8 ft. (3m)	Drop Protection	9.8 ft. (3m)
IP54	Ingress Protection	IP53
CAT IV 600V		CAT IV 600V
600V	AC Voltage (Volts)	600V
600V	DC Voltage (Volts)	600V
_	Audible Continuity	•
_	- Backlight	•
•	Low Impedance	_
•	GFCI GFCI-Protected Circuit Testing	•
_	<b>Flashlight</b>	•
_	APO Auto-Power Off	•
Not Required	Battery	3 x AAA
-	LCD Display with Backlight	•

Find Quality Products Online at:

Cat. No.

UPC# 0-92644+

**Batteries** 

Not required

www.GlobalTestSupply.com

Width

2.35" (59.7 mm)

Depth

1.44" (36.6 mm)

sales@GlobalTestSupply.com

Weight (oz.)

3.2 (92 g)

# Tested Tough. Trust Klein.



See our complete line of Test & Measurement products at www.kleintools.com







© 2017 Klein Tools, Inc.