

Low / High Range Conductivity pH and TDS Testers from HANNA

HI-98129

HI-98130

Popular multi purpose pocket meters

Key Features



Replaceable sensor, extendable junction

Large, easy read display



FLOATS to aid retrieval

Supplied with full pack of accessories

The HI-98129 and HI-98130 are two of Hanna's most popular meters. With their high specifications and sensible pricing, they offer excellent value for money.

Each meter has the ability to measure conductivity, total dissolved solids, pH and temperature in one compact instrument. Fast, efficient and accurate, they are also fully waterproof and will float if dropped in water.

Main Benefits

- LCD indicates % battery power remaining on start-up
- Automatic calibration with two sets of memorised buffers for greater accuracy
- Choice of different Conductivity to TDS conversion ratios
- Dual level display shows pH or Conductivity / TDS with temperature



Product Uses



Hydroponics



Beer and brewing



Water quality



Hanna Instruments Ltd

The difference between the two meters lies in the Conductivity and TDS range

HI-98129 - low range

Range: 0 to 3999 $\mu\text{S}/\text{cm}$; 0 to 2000 ppm plus pH & temperature

HI-98130 - high range

Range: 0.00 to 20.00 mS/cm ; 0.00 to 10.00 ppt plus pH & temperature

Product Specifications

Product Code	HI-98129	HI-98130
Range	pH	0.00 to 14.00
	EC	0 to 20.00 mS/cm
	TDS	0 to 2000 ppm
	Temperature $^{\circ}\text{C}$	0.0 to 60.0
Resolution	Temperature $^{\circ}\text{F}$	30.0 to 140.0
	pH	0.01
	EC	1 $\mu\text{S}/\text{cm}$
	TDS	1 ppm
Accuracy	Temperature	0.1 $^{\circ}\text{C}$
	pH	± 0.05
	EC/TDS	$\pm 2\%$ F.S.
	Temperature $^{\circ}\text{C}$	± 0.5
Calibration	Temperature $^{\circ}\text{F}$	± 1
	pH Automatic	1 or 2 points with 2 sets of memorised buffers, (pH 4.01/7.01/10.1 or pH 4.01/6.86/9.18)
	EC/TDS Automatic	1 point at 1413 $\mu\text{S}/\text{c}$, or 12.88 mS/cm
		1 or 2 points with 2 sets of memorised buffers, (pH 4.01/7.01/10.1 or pH 4.01/6.86/9.18)

Find Quality Products Online at:

www.GlobalTestSupply.com

sales@GlobalTestSupply.com

AUTO-OFF	After 8 minutes	After 8 minutes
Dimension	163 x 40 x 26 mm	163 x 40 x 26 mm
Weight	100 g	100 g