

30 Series Calibrator **ACCURACY—PRESSURE MEASUREMENT**0 to 110% of Range: **$\pm(0.05\% \text{ of Reading} + \text{Floor Term})$** *Includes all effects of linearity, hysteresis, repeatability, temperature, and stability for one year.*Floor Term: **0.005% of FS or display resolution, whichever is greater***All models indicate vacuum, but vacuum specification applies to 16 psi, 36 psi, and 300 psi models only.*Vacuum: **$\pm(0.25\% \text{ of Reading} + \text{Vacuum Floor Term})$** *Not recommended for continuous use below -14.5 psi. Refer to**XP2i-DP data sheet for gauges that are intended for continuous high vacuum use.*Vacuum Floor Term: **0.004 psi for 16 and 36 psi
0.01 psi for 300 psi****ACCURACY—MILLIAMPERES**Accuracy: **$\pm(0.025\% \text{ of Reading} + 0.001 \text{ mA})$** *Includes all effects of linearity, hysteresis, repeatability, temperature, and stability for one year.*Range: **0 to 55 mA***mA can be displayed as a percentage, where 0 to 100% corresponds to either 4 to 20 mA or 10 to 50 mA.*Resolution: **0.001 mA***Jacks are compatible with safety sheathed banana plugs.***OPERATING TEMPERATURE**Temperature Range: **0 to 50°C (32 to 122°F)***Non-condensing. No change in accuracy over operating temperature range. Gauge must be zeroed to achieve rated specification.***DISPLAY**Screen: **2 lines of up to 6 digits,
5 mm (0.2") high**

4534.M 2107 • 30 Series psi

AMETEK
SENSORS, TEST & CALIBRATIONDisplay Rate: **2 readings/second (Adjustable to
1, 3, or 3.7 readings/second)**

30 Series Calibrator 

POWER

The 30 Series is Intrinsically Safe only if powered by one of the following battery types.

ATEX/IECEx:	Approved Battery Type	Ta=	Marking
	Duracell Alkaline 9V, MN 1604		
	Energizer Alkaline 9V, 522	0 to 50°C	
	Energizer Lithium 9V, LS22		Ex ia IIC T4 Gb
	Varta High Energy Alkaline 9V, 4922	0 to 45°C	

CSA:	Approved Battery Type	Marking
	Duracell Alkaline 9V, MN 1604	
	Energizer Alkaline 9V, 522	Class I, Division 1, A, B, C, D T4
	Energizer Lithium 9V, LS22	
	Varta High Energy Alkaline 9V, 4922	Class I, Division 1, A, B, C, D T3C

1 x 9V: **90 hours, typical**

Uses one alkaline 9V battery. Use of USB interface reduces operating time.

For hazardous location product warnings, refer to the operation manual.

DATA/COMMUNICATION

Digital Interface: **micro-USB**

Free Labview drivers available online.

For hazardous location product warnings, refer to the operation manual.

ENCLOSURE

Model 31≤300 psi: **342 g (12.0 oz)**

Weight includes batteries.

*Model 31≤300 psi: **428 g (15.0 oz)**

*SPSS optional manifold.

Model 31≥1500 psi: **360 g (13.0 oz)**

Nylon carry case included.

Model 33: **400 g (14.0 oz)**

*Model 33: **485 g (17.0 oz)**

Housing: **Extruded aluminum**

Keypad and Labels: **UV resistant polyester**

CERTIFICATIONS



II 2G Ex ia IIC T4
FTZU 06 ATEX 0010X



II 2G Ex ia IIC T4 Gb
IECEx FTZU 10.0018X



Exia Intrinsically Safe and Non-incendive for Hazardous Locations: Class I, Division 1, Groups A, B, C and D, Temperature Code T4 or T3C. For hazardous location product warnings, refer to the operation manual.



30 Series complies with the Electromagnetic Compatibility and the Pressure Equipment Directives.



30 Series complies with the Australian Radiocommunications (Electromagnetic Compatibility) Standard 2008



30 Series is approved for use as a portable test instrument for Marine use and complies with Det Norske Veritas' Rules for Classification of Ships, High Speed & Light Craft and Offshore Standards.

30 Series Calibrator **psi**

SENSOR ≥ 1500 psi

Wetted Materials: **316 stainless steel** *All welded with a permanently filled diaphragm seal.*
Diaphragm Seal Fluid: **Silicone Oil**
Connection: **Bottom, 1/8" female NPT**

SENSOR ≤ 300 psi

Wetted Materials: **316 stainless steel, Viton® (o-ring)** *Viton o-ring is internal.*
Anodized aluminum penetrated with PTFE (polytetrafluoroethylene) *All welded with a permanently filled diaphragm seal.*
Diaphragm Seal Fluid: **Silicone Oil**
Connection: **Bottom, 1/8" female NPT**

STORAGE TEMPERATURE

Temperature Range: **-20 to 70°C (-4 to 158°F)** *Batteries should be removed if stored for more than one month.*

SPECIAL FEATURES

The following requires the use of **ConfigM30** software

User Defined Unit: Allows the user to define and display any pressure units not included, or to use the gauge to display force, level, or other pressure related parameters. Reduce or increase displayed resolution.

Remove: Unwanted pressure units from Units button.

Password Protect: **Changes to configuration or users span**  **factor(s).**

Save: **Configuration to a file.**

Copy: **Configuration to other calibrators.**

STANDARD DELIVERY

- 30 Series Calibrator
- CD Manual
- ISO 17025 Accredited Calibration Certificate, NIST Traceable
- Carry Case and Strap (P/N 2490)

ACCESSORIES

Magnetic Hanging Strap [P/N 5203](#)

Test Lead Kit [P/N 1351](#)

USB A to Micro USB Cable [P/N 4431](#)

Waterproof Carrying Case [P/N 2888](#)

COMPLEMENTARY PRODUCTS

Crystal Engineering offers a wide range of products that work with the 30 Series:

- Fittings that connect without tools, safely and without leaks
- Lightweight, super flexible high pressure hoses
- Pneumatic hand pumps
- Hydraulic hand pumps
- Portable pressure comparators
- Software, for the quickest way to calibrate pressure transmitters and gauges

Viton is a registered trademark of DuPont Performance Elastomers.

30 Series Calibrator psi

Crystal[®]
pressure

RANGE & RESOLUTION TABLE

P/N	Range (psi)	Over-pressure	Display Resolution										
			psi	in H ₂ O	in Hg	mm Hg	mm H ₂ O	cm H ₂ O	kg/cm ²	bar	mbar	kPa	MPa
16	16	6.5 x	0.001	0.01	0.001	0.01	1		0.0001		0.1	0.01	
36	36	3.0 x	0.001	0.01	0.001	0.01	1		0.0001		0.1	0.01	
300	300	2.0 x	0.01	0.1	0.01	0.1		1	0.001	0.001		0.1	
1500	1500	2.0 x	0.1						0.01	0.01		1	0.001
3000	3000	1.5 x	0.1						0.01	0.01		1	0.001
5000	5000	1.5 x	0.1						0.01	0.01		1	0.001

• Model 31 calibrators are not available in this range.

ORDERING INFORMATION

Intrinsic Safety	Model	—	1st Pressure Range P/N	/	2nd Pressure Range P/N	Pressure Unit	Pressure Manifold	Pump System*	Carrying Case~
IS	—	—	—	—	—	PSI	—	—	—
			Single Sensor ...31				Standard.....(omit)	No Pump....(omit)	
			Dual Sensor33				Stainless Steel ...SPSS	System A -AXX	Aluminum ... (omit)
								System A -AHX	Waterproof..... -W
								System B -BXX	
								System B -BHX	
								System C -CXX	
								System C -CHX	
								System D -DOX	
								System D -DWX	
								System E -EOX	
								System F -FOV	
								System F -FWV	
								System G -GOX	
								System G -GWX	
								System H -HOX	

SAMPLE PART NUMBERS

IS31-36PSI Calibrator with one sensor (36 psi).
 IS33-16/1500PSI-SPSS Calibrator with two sensors (16 psi and 1500 psi) with two stainless steel manifolds.
 IS33-36/3000PSI-SPSS-HOX-W Calibrator with two sensors (36 psi and 3000 psi) and two stainless steel manifolds with a System H pump system and a waterproof carrying case.

► Ordering a Pump System Only

Any pump system, carrying case, and connection fittings for a 30 Series calibrator may be ordered separately from the calibrator. Enter IS30-NONE followed by the Pump System part number and the Carrying Case option code.

SAMPLE PART NUMBER

IS30-NONE-HOX-W System H pump system with a waterproof carrying case.

DUAL PRESSURE SENSORS

Model 33 callibrators have dual pressure sensors. This chart shows all of the available sensor combinations. ■

First Pressure Ranges	Second Pressure Ranges			
	300 psi	1500 psi	3000 psi	5000 psi
16 psi	■	■	■	■
36 psi	■	■	■	■

AMETEK offers a variety of solutions for pressure generation and measurement. Our line of products for pressure generation includes everything from small pneumatic hand pumps to a precision, hydraulic pressure comparator capable of generating up to 15 000 psi / 1000 bar / 100 MPa.

All of our pumps may be ordered as part of a Pump System, complete with a 30 Series and delivered in a sturdy carrying case with custom insert.

* Refer to the following page for a more detailed description of each pump system.

30 Series Calibrator psi

PUMP SYSTEMS OVERVIEW

Crystal pressure	Pump System	Part Number	Pressure Range	Pneumatic	Hydraulic	Hand Pump	Bench Top	Included Pump	Case Options	
									Aluminum	Waterproof (Pelican Case)
System A	AXX	0 to 30psi / 2 bar		■		■		T-960-CPF	■	■
	AHX	0 to 580 psi / 40 bar		■		■		T-970-CPF	■	■
System B	BXX	-25 inHg to 30 psi / -0.85 to 2 bar		■		■		T-965-CPF	■	■
	BHX	-27 inHg to 580 psi / -0.91 to 40 bar		■		■		T-975-CPF	■	■
System C	CXX	0 to 3000 psi / 200 bar			■ (Oil)	■		T-620-CPF	■	■
	CHX	0 to 5000 psi / 350 bar			■ (Oil)	■		T-620H-CPF	■	■
System D	DOX	0 to 5000 psi / 350 bar			■ (Oil)		■	P-018-CPF	■	
	DWX	0 to 5000 psi / 350 bar			■ (Water)		■		■	
System E	EOX	0 to 10 000 psi / 700 bar			■ (Oil)		■	P-014-CPF	■	
System F	FOV	0 to 15 000 psi / 1000 bar			■ (Oil)		■	T-1-CPF	■	
	FWV	0 to 15 000 psi / 1000 bar			■ (Water)		■		■	
System G	GOX	0 to 15 000 psi / 1000 bar			■ (Oil)		■	GaugeCalHP		■
	GWX	0 to 15 000 psi / 1000 bar			■ (Water)		■			■
System H	HOX	-27 inHg to 580 psi / -0.91 to 40 bar	■			■		T-975-CPF — (and) — T-620H-CPF		■
		0 to 5000 psi / 350 bar			■ (Oil)	■				■