AC/DC Clamp Meters

MODEL IA167 - WITH LARGE DIAMETER JAWS

- Measures AC and DC current up to 2000 A, plus AC and DC voltage up to 750 V and 1000 V respectively
- Measures resistance up to 4000Ω
- Peak hold function
- Shielded banana plugs and recessed input terminals
- Output terminal
- Tear drop shaped jaws facilitates use in tight places and crowded cable areas

MODEL IA168 - THE SMALLEST CLAMP METER ON THE MARKET

- · Capable of both AC and DC measurements
- Measures AC and DC current up to 200 A, plus AC and DC voltage up to 500 V and 200 V respectively
- Measures resistance up to 200 Ω
- Resolution of 0.01 A AC/DC
- Pocket-sized
- Includes: test leads and carrying case

MODEL IA169 - OPEN CLAMP CURRENT SENSOR

- Ideal for use in crowded connection boxes where space is too limited for traditional clamp meters
- Non-contact voltage detection
- True RMS AC current measurement to 100 A
- Zero adjust function
- Auto power off
- Data hold



IA167

Mfg. No.

KFW2003A

KFW2004

KEW2300R

Model No.

ΙΔ167

IA168

IA169



AC/DC Clamp Meter





Milliamp Process Clamp Meters

- · Measure 4-20 mA DC without breaking the electrical circuit
- Employs a remotely connected
- clamp via an extension cable
- Best in class accuracy of 0.2% Percentage span (0 to 100%)
- Electronic zero
- Display hold and backlight
- Measurement spotlight LED
- Auto power off
- Conforms to Cat. II 300 V
- Includes: batteries and soft carrying case
- Current Range: ±20.99 mA, ±99.9 mA




Model No.	Mfg. No.	Description P	rice/Each
IA522	771	Milliamp Process Clamp Meter	606.00



AC Clamp Meters

- Permits current measurements on a live conductor without circuit interruption
- Rotary switch selects one range at a time
- · Analog scale
- Includes: test leads, two fuses, single AA battery, and carrying case
- Voltage Ranges: 150/300/600 VAC
- Current Ranges: 6/20/60/200/600 AAC • Resistance Range: 2 kΩ (25 Ω mid-scale)







169.00