

Quality and reliability is our tradition.



KYORITSU

NEW



HIGH PERFORMANCE AND WIDE RANGE DIGITAL MULTIMETER

- Display : 4000 counts
- Auto range and manual range selector provided. (with range hold feature)
- Diode test feature.
- Capacitance test feature.
- Relative measurement.
- Resistance range provides audible continuity test.
- Automatically turns power off in about 30 minutes to conserve battery life.
- Direct current measurement up to 10A AC and DC.
- With Holster.
- Designed to international safety standard IEC61010-1 CAT. III 300V.



Specifications

DC V	400mV / 4 / 40 / 400 / 600V (Input Impedance 10M Ω) $\pm 0.6\%rdg \pm 4dgt$ (400mV / 4 / 40 / 400V) $\pm 0.1\%rdg \pm 4dgt$ (600V)
AC V	400mV / 4 / 40 / 400 / 600V (Input Impedance 10M Ω) $\pm 1.6\%rdg \pm 4dgt$ (20 – 400mV) $\pm 1.3\%rdg \pm 4dgt$ (4 / 40V) $\pm 1.6\%rdg \pm 4dgt$ (400 / 600V)
Hz	5.12 / 51.2 / 512Hz / 5.12 / 51.2 / 512kHz / 5.12 / 10MHz
DC A	400 / 4000 μ A / 40 / 400mA / 4 / 10A $\pm 2.0\%rdg \pm 4dgt$ (400 / 4000 μ A) $\pm 1.0\%rdg \pm 4dgt$ (40 / 400mA) $\pm 1.6\%rdg \pm 4dgt$ (4 / 10A)
AC A	400 / 4000 μ A / 40 / 400mA / 4 / 10A $\pm 2.6\%rdg \pm 4dgt$ (400 / 4000 μ A) $\pm 2.0\%rdg \pm 4dgt$ (40 / 400mA / 4 / 10A)
Ω	400 Ω / 4 / 40 / 400k Ω / 4 / 40M Ω $\pm 1.0\%rdg \pm 4dgt$ (400 Ω / 4 / 40 / 400k Ω / 4M Ω) $\pm 2.0\%rdg \pm 4dgt$ (40M Ω)
Diode Test	4V Release Voltage : Approx. 0.4mA Test Current
Capacitance Test	40nF / 400nF / 4 μ F / 40 μ F / 100 μ F
Continuity buzzer	400 Ω (Buzzer sounds below 50 Ω)
Withstand Voltage	3700V AC for 1 minute
Standard	IEC 61010-1 CAT. III 300V IEC 61010-2-031 IEC 61326-1
Power Source	R6P(1.5V) $\times 2$
Dimensions	155(L) \times 75(W) \times 33(D)mm
Weight	260g approx.
Accessories	Test Leads, 0.5A / 250V fuse $\times 1$, 10A / 250V fuse $\times 1$ R6P $\times 2$, Instruction Manual

COMPACT DIGITAL MULTIMETER

MODEL 1009

KYORITSU ELECTRICAL INSTRUMENTS WORKS, LTD.