

Datasheet: Validate Network Connectivity in Less Than 10 Seconds-China

Key features include:

- Quick and simple to use
- Understand if a network connectivity issue is in the PC or the network and if it's the network, where
- Zero touch reporting automatically sends every test to Link-Live Cloud Service saving time and ensuring accuracy in reporting
- Priced to fit every IT budget as a personal tool everyone can have allowing teams to solve problems faster without the need for a shared device



Robert Barker, Enterprise Systems Coordinator, Lebanon R-III School District. Read his success story at flukenetworks.com/LinkSprinter



LinkSprinter is a pocket-sized Ethernet tester that provides complete end-to-end network connectivity testing and automated cloud based reporting all with the touch of a button. LinkSprinter is used by PC help desk, front line technicians, network engineers and many others, to validate network connectivity, cable, and that power is correctly being applied to PoE powered devices.

Simply connect an Ethernet cable and the LinkSprinter goes to work checking the connection path from wall jack to internet and in less than 10 seconds, you'll know that status of the connection path through color coded LEDs.



LinkSprinter Awards

Big Things Come In Small Packages

Don't let LinkSprinter's small stature fool you, it's packed with capability and provides several custom configuration options that can be set per tester or within Link-Live Cloud Service Job Pro and the setting is pushed to all units enabling better workforce automation.

LinkSprinter runs a series of standardized tests to ensure consistency in workflow and documentation across team members regardless of skill level.

- **Power Over Ethernet (PoE)**

Check to make sure you can power a phone, security camera or Access Point through a specific port. The LinkSprinter Network Tester can even run without batteries on PoE.

- **Link to the Switch**

Perform a switch test, which indicates switch name, model, slot, port and VLAN you are connected to using CDP/LLDP/EDP. Know your available speed and duplex settings.

- **DHCP Connection**

Confirm that the DHCP server is running and responsive. Request an IP address, get your subnet information, and identify the default gateway and DNS server.

- **Gateway Connection**

Verify the gateway/router address and reachability by pinging the device.

- **Internet Connection**

Confirm cloud connectivity or internal service reachability. Verify DNS server lookup and application port connectivity.

Quick Answers to Common Tasks

- **Moves, Adds, Changes**

Validate proper connectivity including IP subnet and VLAN so you're ready when devices arrive.

- **PoE Validation**

Ensure switch port provisioning and cabling before installing cameras, phones, or wireless access point.

- **PC Help Desk**

Is the problem in the PC or the Network? If it's the network, find out where so you can escalate with facts.

- **Gateway Connection**

Verify the gateway/router address and reachability by pinging the device.

- **Remote Site Network Connectivity Validation**

Leave one on site, even an office assistant can run a test while the NOC sees the detailed result appear on the Link-Live Cloud Service dashboard.



LinkSprinter 300

LinkSprinter Features by Model	300
Diagnose and test Power over Ethernet (PoE), Link to the switch, DHCP, Gateway, and Internet connection	X
Get VLAN, switch name, and port information via CDP/LLDP/EDP for your managed switches	X
Expert network troubleshooting techniques delivered to color graded LEDs	X
All test results are sent to the Link-Live Cloud Service	X
Get detailed test results sent directly to your email	X
Access your test results through your phone's browser by connecting to the built-in Wi-Fi access point	X
See cable fault and distance to open or short	X
Blink light on switch port	X

*Please note that the LinkSprinter 100 and 200 are not available for China

RESULT MANAGEMENT OPTIONS

Link-Live Cloud Service

Once the LinkSprinter is connected to the Link-Live Cloud service, basic network connectivity test results are automatically uploaded to the dashboard for project management and reporting. This internet-hosted service is available from anywhere at any time using any device with a browser and internet connection. It is especially useful for managers of remote teams that need visibility to test results instantly. In addition, teams that utilize companions to the LinkSprinter, such as the LinkRunner AT, AirCheck G2, or OneTouch AT have a single dashboard system to manage results from network connectivity tests.

Time	Test	File	Link	Access	Gateway	WWW
Feb 25, 16 Thursday 5:10:53pm	Name: Shamree Howard's AirCheck G2 MAC: 00C017-350086 Device: AirCheck G2 Test Type: wireless AutoTest: AC162196-shd11x5-9440-8x5G2800h Images: (i) Comments: (c)		PHY Data Rate: 48 Retry Rate: 0 Signal (dBm): -52 Noise (dBm): -96 SNR (dB): 44	SSID: Cisco4400 AP Name: Cisco1130-1Hunt BSSID: 00:17:0A:7B:00:00 Channel: 11 802.11 Type: lg	IP: 10.250.0.225 Server: 10.250.0.2 Subnet: 255.255.254.0 DNS1: 10.250.1.221 DNS2: 10.250.1.1 DNS3: 129.196.196.25 DNS4: PING (ms): -/-/-/-	IP: 10.250.0.1 PING (ms): 18.7, 7 Public IP: 74.202.20.243 URL: www.google.com/PING IP: 216.58.217.36 Time (ms): 11, 10, 13
Feb 25, 16 Thursday 5:23:23pm	Name: Shamree Howard's AirCheck G2 MAC: 00C017-350086 Device: AirCheck G2 Test Type: wireless Images: (i) Comments: Meeting Room, Colorado (c)	47x	Speed: 1000 Adv Speed: 10/100/1000 Duplex: FDX Adv Duplex: 10/4/10/4	Name: COS_DEV_SW1-Phet-ang Model: cisco W5-C2750S-48PS IP/MAC: 10.250.0.2 Port: GigabitEthernet1/0/38 VLAN: 500	IP: 10.250.0.151 Server: 10.250.0.2 Subnet: 255.255.254.0 DNS1: 10.250.1.221 DNS2: 129.196.196.254	IP: 10.250.0.1 PING (ms): 21.3, 2 Public IP: 74.202.20.243 URL: www.google.com/PING IP: 216.58.217.36 Time (ms): 5, 3, 3
Feb 25, 16 Thursday 1:03:23pm	Name: Shamree Howard's AirCheck G2 MAC: 00C017-350086 Device: AirCheck G2 Test Type: wireless Images: (i) Comments: (c)		PHY Data Rate: 48 Retry Rate: 2 Signal (dBm): -49 Noise (dBm): -96 SNR (dB): 47	SSID: Cisco4400 AP Name: Cisco1130-1Hunt BSSID: 00:17:0A:7B:00:00 Channel: 11 802.11 Type: lg	IP: 10.250.0.225 Server: 10.250.0.2 Subnet: 255.255.254.0 DNS1: 10.250.1.221 DNS2: 10.250.1.1 DNS3: 129.196.196.25 DNS4: PING (ms): -/-/-/-	IP: 10.250.0.1 PING (ms): 11.67, 3 URL: www.google.com/PING IP: 216.58.217.36 Time (ms): 5, 4, 4
Sep 25, 15 Friday 12:52:53pm	Name: Shamree's LinkSprinter 200 MAC: 00C017-523713 Device: LinkSprinter Firmware: Spiceworks Images: (i) Comments: Spiceworks (c)	48x	Speed: 100 Adv Speed: 10/100 Duplex: FDX Adv Duplex: 10/4/10/4 RX Pair: 1,2 Polarity: Normal	Name: NETGEAR ProSafe Main Type: LLDP Model: Netgear Gigaset Smart Switch IP/MAC: 192.168.0.167 Port: g1/switch Port 1	IP: 192.168.0.100 Server: 192.168.0.1 Subnet: 255.255.255.0 DNS: 192.168.0.1	IP: 192.168.0.1 PING (ms): 1, 2, 1 Public IP: 107.77.100.125 URL: www.google.com/80 IP: 74.125.227.210 Time (ms): 26, 120, 96
Sep 25, 15 Friday 12:54:23pm	Name: Shamree's LinkSprinter 200 MAC: 00C017-523713 Device: LinkSprinter Firmware: Spiceworks Images: (i) Comments: Spiceworks (c)	47x	Speed: 1000 Adv Speed: 10/100/1000 Duplex: FDX Adv Duplex: 10/4/10/4 RX Pair: A0 Polarity: Normal	Name: Test Drive Switch Type: LLDP Model: Netgear Gigaset Smart Switch IP/MAC: 192.168.0.153 Port: g1/TO Port 5	IP: 192.168.0.127 Server: 192.168.0.1 Subnet: 255.255.255.0 DNS: 192.168.0.1	IP: 192.168.0.1 PING (ms): 1, 1, 1 Public IP: 107.77.100.125 URL: www.google.com/80 IP: 173.194.121.18 Time (ms): 26, 120, 96
Sep 25, 15 Friday 12:55:23pm	Name: Shamree's LinkSprinter 200 MAC: 00C017-523713 Device: LinkSprinter Firmware: Spiceworks Images: (i) Comments: (c)	48x	Speed: 100 Adv Speed: 10/100 Duplex: FDX Adv Duplex: 10/4/10/4 RX Pair: 3,6	Name: NETGEAR ProSafe Main Type: LLDP Model: Netgear Gigaset Smart Switch IP/MAC: 192.168.0.167 Port: g1/switch Port 1	IP: 192.168.0.100 Server: 192.168.0.1 Subnet: 255.255.255.0 DNS: 192.168.0.1	IP: 192.168.0.1 PING (ms): 1, 1, 1 Public IP: 107.77.100.125 URL: www.google.com/80 IP: 216.58.216.100 Time (ms): 291, 100, 279

Link-Live dashboard

Technical Specifications

Environmental	
Operating Temperature and Relative Humidity	32°F to 122°F (0°C to 50°C), Relative Humidity 5% to 90% Non-condensing
Storage Temperature	-4°F to 140°F (-20°C to 60°C)
Shock and Vibration	Random 2g, 5 Hz – 500 Hz (class 2), 1 m drop
Safety	CAN/CSA-C22.2 No. 61010-1-12, UL Std. No. 61010-1 (3rd Edition), IEC61010-1:2010, Pollution degree 2
Altitude	Operating: 13,123 ft. (4,000 m) Storage: 39,370 ft. (12,000 m)
EMC	EN 61326-1:2006
Certifications and Compliance	Conforms to relevant European Union directives Conforms to relevant Australian standards Listed by the Canadian Standards Association Conforms to relevant FCC standards

General	
Dimensions	4.36" x 1.6" x 1.28" (11.07 cm x 4.06 cm x 3.25 cm)
Weight with batteries	Model 100: 0.250 lb (0.113 kg) Model 200/300: 0.255 lb (0.116 kg)
Battery	2 AA Alkaline

Wi-Fi Access Point (Model 200 and 300)	
Specification Compliance	IEEE 802.11b/g
Frequency Channels	802.11 Channels 1 thru 11 default is 11
Operating Frequency	2.412 ~ 2.484 GHz, ISM Band
Regulatory Domain	EN 301 489-1/17
Browser	Internet Explorer 9.0, Firefox 3.6, Chrome 5.0, Safari 5.1 (minimum revision)

Ordering Guide

Item Name	Description
LSPRNTR-100	Includes 1 LinkSprinter 100, wrist strap, Link-Live Cloud Service Essentials
LSPRNTR-100-10PK	Includes 10 LinkSprinter 100's for the price of 9, wrist straps, Link-Live Cloud Service Essentials
LSPRNTR-100-5PK	Includes 5 LinkSprinter 100's at a reduced price, wrist straps, Link-Live Cloud Service Essentials
LSPRNTR-200	Includes 1 LinkSprinter 200, wrist strap, Link-Live Cloud Service Essentials
LSPRNTR-200-10PK	Includes 10 LinkSprinter 200's for the price of 9, wrist straps, Link-Live Cloud Service Essentials
LSPRNTR-200-5PK	Includes 5 LinkSprinter 200's at a reduced price, wrist straps, Link-Live Cloud Service Essentials
LSPRNTR-300	Includes 1 LinkSprinter 300, wrist strap, Link-Live Cloud Service Essentials
LSPRNTR-300-10PK	Includes 10 LinkSprinter 300's for the price of 9, wrist straps, Link-Live Cloud Service Essentials
LSPRNTR-300-5PK	Includes 5 LinkSprinter 300's at a reduced price, wrist straps, Link-Live Cloud Service Essentials
LSPRNTR-HOLSTER	Belt attachable holster carries one LinkSprinter and includes short patch cable and business card holder
LINKSOLUTIONS-KIT	Includes 1 LinkRunner AT 2000 with standard components, 2 LinkSprinter 300's, 2 LinkSprinter Holsters, Link-Live Cloud Service Essentials

For a complete listing of LinkSprinter models and accessories, visit: www.enterprise.netscout.com/enterprise-network/network-testing/linkssprinter