

# Product data sheet

Specifications

SQUARE D



PowerLogic EM3500 DIN rail meter - BACnet without logging - flexible transducer

METSEEM3561A

## Main

Range	PowerLogic
range of product	PowerLogic EM3500
Device short name	EM3561A
Product or component type	Energy meter
Metering type	Current I1, I2, I3, Iavg Peak demand power PM, QM, SM Demand power P, Q, S Voltage U21, U32, U13, V1, V2, V3

## Complementary

Poles description	3P + N
Type of measurement	Active and reactive power total Active and reactive power per phase Apparent power total Apparent power per phase Power factor total Power factor per phase Peak demand power Current Voltage Frequency
Device application	Sub billing Partial meter
Accuracy class	Class 0.5S power IEC 62053-22 Class 0.5S energy IEC 62053-22 Class 0.5S power ANSI C12.20 Class 0.5S energy ANSI C12.20
Measurement accuracy	Power +/- 0.5 % Energy +/- 0.5 %
input type	Rogowski coil 50...5000 A
Rated voltage	90...347 V
Network frequency	60 Hz 50 Hz
Technology type	Electronic
Display type	Backlit LCD
Measurement current	20...5000 A
Display digits	5

<b>Information displayed</b>	Status and alert Communication with system Input/output status Error Tx activity Rx activity Instant power per usage
<b>Tamperproof of settings</b>	Protected by access code
<b>Communication port protocol</b>	BACnet MS/TP 9600 bauds...115200 bauds (automatic detection) - 2-wire
<b>Communication port support</b>	Screw terminal block RS485
<b>Communication service</b>	Total cumulated energy Total cumulated active energy
<b>Data recording</b>	Energy consumption logs
<b>Demand intervals</b>	Fixed or rolling block External synchronisation to communication
<b>Local signalling</b>	Red LED threshold reached Green flashing LED output signal
<b>number of accumulator inputs</b>	2 pulse
<b>[Ue] rated operational voltage</b>	90...347 V AC 50/60 Hz between phase and neutral UL 156...600 V AC 50/60 Hz between phases UL 90...300 V AC 50/60 Hz between phase and neutral CE 125...300 V DC
<b>Power consumption in VA</b>	5 VA 347 V AC between phase and neutral) 5 VA 600 V AC between phases)
<b>Power consumption in W</b>	3 W 300 V
<b>Ride-through time</b>	100 ms 120 V AC
<b>Mounting mode</b>	By screws Clip-on
<b>Mounting support</b>	DIN rail
<b>Standards</b>	CSA C22.2 No 14-05 IEC 61010-1 UL 508
<b>Product certifications</b>	CE conforming to IEC 61010 CULus conforming to UL 508

## Environment

<b>Relative humidity</b>	0...95 %
<b>Ambient air temperature for operation</b>	-22...158 °F (-30...70 °C)
<b>Ambient air temperature for storage</b>	-40...185 °F (-40...85 °C)
<b>Colour</b>	Dark grey
<b>9 mm pitches</b>	12
<b>Width</b>	4.2 in (107 mm)
<b>Height</b>	3.6 in (91 mm)
<b>Depth</b>	2.3 in (59 mm)

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	3.80 in (9.65 cm)

<b>Package 1 Width</b>	8.30 in (21.08 cm)
<b>Package 1 Length</b>	9.50 in (24.13 cm)
<b>Package 1 Weight</b>	19.200 oz (544.311 g)



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)

84

### Use Better

#### Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant with Exemptions

SCIP Number

7e026619-91b4-4741-a9c3-c4a1c1c83d61

REACH Regulation

[REACH Declaration](#)

### Use Again

#### Repack and remanufacture

Recyclability potential, in %

0

Take-back

No