



10 Pressure Gauges in 1 Device



meriGauge® plus

The meriGauge® plus Digital Pressure Gauge is

the perfect solution for multi-range pressure measurement needs.

As the only modular gauge on the market, the meriGauge plus delivers significant cost savings by allowing

Intrinsically Safe

users to purchase a single gauge and add only the pressure ranges they need. With 22 interchangeable Smart Sensors available (15 psi – 3,000 psi), the meriGauge plus is actually multiple gauges in one device, creating the flexibility and lowest cost of ownership only Meriam can provide.

Easy to Use

- · Icon based, simple buttons
- Gauge works with all meriSense sensors
- Portable or fixed installation, even in narrow spaces

Easy to Read

- Concisely displays more info at a glance
- · High visibility from a distance
- Crisp digital readout in any or no light

meriSense[™]

Smart Sensor Modules

- 10 Interchangeable Smart Sensor Modules
- Compound Gage Pressure Range
 -14.5 to 3000 PSIG
- Absolute Pressure Range 0 to 100 PSIA
- Isolated Sensors for fluids compatible with 316SS
- NIST Traceable Calibration
- Hot Swappable



meriGauge® plus

meriSense

Display	6-digit main height, 17.8 mm (0.701 in) 10-character height, 7.65 mm (0.301 in) White LED backlight (3 intensities and O) Red (beacon) error backlight	Body	Stainless Steel, 25.1 mm × 82.8 mm × 22.2 mm (0.989 in × 3.26 in × 0.875 in) Approx. weight 0.1 kg (0.22 lbs)
Keyboard	5-dedicated keys, plus information key Intuitive, icon-based keys for internationalization	Accuracy	316SS Isolated Compound Isolated, –14.5 psi to FS, where FS is 15 psi to 3 000 psi Absolute Isolated, 0 psi to FS, where FS is 15 psi to 100 psi Compound 0 to 110 % of Range: ± (0.02 % of Full Scale) + 0 to 110 % of Range: (0.005 % of Reading) Vacuum*: ± (0.02 % of Full Scale) *Vacuum = –14.5 psi Absolute 0 to 110 % of Range: ± (0.02 % of Full Scale) +
Body	Powder coated T6 aluminum, 120.7 mm \times 167.3 mm \times 40.1 mm (4.75 in \times 6.59 in \times 1.58 in) body only Approx. weight with batteries 0.608 kg (1.34 lbs)		
meriSense Receptacle	Easy insertion/removal without tools Impossible to insert meriSense incorrectly Industrial stainless- steel release pin O-rings for alignment and vibration isolation Gold connection pins good for >1M cycles		
Power and Battery Life	4 x 1.5 V AA alkaline Approx. 350+ hours with alkaline (no backlight)		0 to 110 % of Range: (0.005 % of Reading)
Communication	USB mini 2.0 compliant, for conguration, update, user calibration and data log	Vent	1 mm Gortex, shielded when installed in meriGauge plus (cap provided)
	Data Log Pro*** provides a maximum 128 files or 100,000	Process Connection	1/4 inch NPT
Storage	data points Real-time clock calendar w/7 year battery backup	Electrical Connections	Hardened gold (30 micron) connection good for >1M cycles
Features	Modes: Min, Max, Accuracy, Tare, Average, Rate of change, DataLog Lite**, Ambient temperature/time Fully congurable via meriLink* PC Software Update rate, 5 measurements per second	Features	32 engineering units, two custom units, User calibration, fully congurable via meriLink PC Software
Operating Conditions	Conditions: −10 °C to 50 °C (14 °F to 122 °F)	Operating Conditions	Conditions: –10 °C to 50 °C (14 °F to 122 °F)
Shock Condition	Tested to survive a 39.4 inch [1 m] drop onto concrete	Shock Condition	Tested to survive a 39.4 inch [1 m] drop onto concrete
Ingress Protection	IP66	Ingress Protection	IP67
Intrinsically Safe	C € 0539	Intrinsically Safe	C € 0539
Environmental Protection	RoHS, WEEE	Environmental Protection	RoHS, WEEE
EMC Compatibility	For Handheld Class A device	EMC Compatibility	For Handheld Class A device

^{*} meriLink configuration software is included with each meriGauge plus.

 $[\]ensuremath{^{**}}$ Data Log Lite is included with every meriGauge plus.

^{***} Data Log Pro is an option you may purchase.