

## The MPC-Rex Combo Kit offers both pipe & cable and magnetic locating

This kit includes a **GA-92XTd Magnetic Locator** and a **Rex Multi-Frequency Pipe & Cable Locator** and accessories. The entire system fits easily into a custom shoulder bag. The MPC-Rex Combo Kit is the one kit designed for all locating professionals in a range of utility industries.

### Optimized for:

- ▶ Water & Sewer
- ▶ Gas
- ▶ Electric
- ▶ Telecomm



*"I work in the oil and gas industry in West Virginia and Ohio. I use Schonstedt products to locate private and public utilities on a daily basis. I would recommend them to anyone looking for professional quality equipment that is easy to learn."*  
—Scott Hoffer Utility Coordinator, Antero Resources

# GA-92XT<sup>d</sup>

## MAGNETIC LOCATOR




Retracts for easier carrying



### GA-92XTd Receiver Specifications

Battery Indicator:	4-segment LCD
Gain:	4-Level LCD: Low (L), Medium (M), High (H), Extra High (XH)
Volume:	3 Levels: Muted, Medium and Maximum
Input Power:	One 9V Battery
Battery Life:	24 Hours (intermittent usage)
Operating Temperature:	-13° F to 140° F (-25° C to 60° C)
Overall Length:	Open – 26" (66 cm), Closed 15.5" (39 cm)
Nominal Sensor Spacing:	9.5" (24 cm)
Weight:	2.4 lbs (1.1 Kg)
Water and Dust Resistance:	Rated IP54



Extends for greater sensitivity



### Rex Receiver Specifications

Operating Frequency:	Active: 512 Hz, 33 kHz and 82 kHz; Passive: 50 or 60 Hz; Sonde: 512 Hz
Battery:	One 9V Battery
Battery Life:	12 Hours (intermittent usage)
Weight (incl. battery):	2.8 lbs (1.25 kg)
Operating Temperature:	-4°F to 140°F (-20°C to 70°C)
Overall Dimensions:	Closed: 17" (44 cm); Extended: 27.7" (70 cm)
Max. Depth Capability:	Approximately 19' (5.8 m) Sonde mode - approximately 5' - 15' (1.5 m to 4.2 m)
Water and Dust Resistance:	Rated IP54

# MPC-Rex<sup>LITE</sup>

## DUAL-FREQUENCY COMBO KIT

NEW!



### Ultra Lightweight Transmitter:

1.9 lbs (0.9 kg)

### Dual Frequency:

Active: 33 kHz and 512 Hz (33kHz model),  
82 kHz and 512 Hz (82 kHz model);

Passive: 50 or 60 Hz; Sonde: 512 Hz

### Max. Output Power:

Conductive mode, 33 kHz and 512 Hz - 1 W Max @ 1000 Ω load; 82 kHz - 1/2 W or 1 W (FCC limited)

### Battery Type:

10 AA Alkaline (1.5 V nominal)

All other features, specifications, and components as per MPC-Rex



Rex Transmitter: 3.5 lbs (1.6 kg)



Rex LITE Transmitter: 1.9 lbs (0.9 kg)

### Rex Transmitter Specifications

Operating Frequency:	512 Hz, 33 kHz and 82 kHz
Operating Modes:	Conductive, Inductive, and Inductive Clamp
Max. Output Power: (Conductive mode @ 1000 Ω load)	512 Hz and 33 kHz: 1/2, 1, 2 or 5 W 82 kHz: 1/2 or 1 W
Battery Type:	Rechargeable NiMH pack (12V)
Battery Life:	8 Hours (intermittent usage)
Charging:	Internal Smart Charger powered by AC/DC power adapter
Dimensions:	10"W x 10.25"D x 1.75" H (25.4 cm x 26 cm x 4.5 cm)
Weight:	3.5 lbs (1.6 kg)
Operating Temp.:	-4°F to 140°F (-20°C to 70°C)
Water and Dust Resistance:	Rated IP54

Copyright © 2021 Schonstedt Instrument Company. All rights reserved. Schonstedt is a subsidiary of SPX Corporation. Due to a policy of continued development, we reserve the right to alter or amend any published specification without notice. This document may not be copied, reproduced, transmitted, modified or used, in whole or in part, without the prior written consent of Schonstedt Instrument Company.