

Data Sheet



No hassle warranty

No waiting.





(note: \$500 MSLP limit)

MT-10 Moisture Meter

Measure moisture content for wall board, wood or other building materials to determine places of harmful mold growth or unseen water damage.

Typical application also include checking moisture of concrete slab and wood before installation of floors, determining wood moisture content during drying process, and checking wood moisture before material is used for woodworking applications.

- Checks for moisture content in wood, paper or cardboard and building materials such as sheetrock, concrete, mortar, plaster etc...
- **■** Measurement Ranges:
 - Wood/ Paper: 8 ~ 60%
 - Building Material: 0.3 2.0%
 - Temperature: 0°C ~ 40°C or 32°F ~ 99°F
- Used in indoor air quality applications for detecting moisture in the walls, floors and ceilings stimulating mold growth
- LCD Display provides moisture or temperature measurement
- Three color LED provides quick moisture indication:
 - Green "air-dry" conditions
 - Yellow increased moisture
 - Red excess moisture
- Backlight for operation in dark areas
- Low battery indication
- Auto power off





MT-10 Mini-vane Anemometer

Data Sheet

Specifications

- p	
Measurement Range	
Wood	8 ~ 60%
Building Material	0.3-2.0%
Temperature	0 ~ 40°C or 32 ~ 99°F
Resolution	
Wood	0.1%
Building Material	0.01%
Temperature	0.1°C / 0.2°F
Accuracy	
Wood	±2%
Building Material	±0.1%
Temperature	±1°C/±2°F
Low Battery Indication	Symbol " "shown on the display (Automatic Power-Off)
Battery	9V, 6F22
Operating Environment	Temperature 0°C ~ 40°C (32°F to 104°F)
	Relative Humidity < 85%
Storage Environment	Temperature -10°C ~ -50°C (14°F to -58°F)
	Relative Humidity < 85%
Dimensions	145(L) × 60(W) × 31(H)mm (5.73 x 2.37 x 1.21 in)
Weight	Approx. 95g (0.37 lb)

©2009 Amprobe Test Tools. All rights reserved. 7/2009 3520463 Rev A