

## 23 Liter Polycarbonate Open Bath System



MX23P100

### Key Specifications

Description	23 L Open Bath System
Controller Type	MX
Display	3.25" LCD
Languages Supported	English
Working Temperature Range °C	Ambient +10° to 85°
Temperature Stability °C	±0.07°
Temperature Calibration Capability	1-point
Working Access (L x W x D) (cm)	21 x 30.5 x 20.3 cm
Pump Type	Pressure
Flammability Class (DIN 12876-1)	I (NFL)

### Key Features

POLYCARBONATE OPEN BATHS

Features

- Advanced Programmable or MX Temperature Controller
- 8, 11, 14, 17, 23 or 28 liter reservoir
- Transparent polycarbonate reservoir lets you keep samples in clear view
- Elevated tank bottom provides secure hand holds when lifting or relocating bath, remains stable on uneven surfaces
- Controller bridge removes easily for tank cleaning, rests securely on reservoir top edge when in use
- Included bath cover reduces evaporation and improves temperature stability
- DuraTop™ chemical resistant bridge
- Lidded opening for optional cooling coil (17, 23 and 28 liter models)
- Drain port (17, 23 and 28 liter models)
- Complies with DIN 12876-1 Class I safety requirements for use with non-flammable liquids

#### Select a Controller

	<b>Advanced Programmable (AP)</b>	<b>MX</b>
<b>Temperature Stability</b>	±0.01°C	±0.07°C
<b>Pump Type</b>	Pressure/Suction, Variable-Speed	Pressure Only, 1-Speed
<b>Programmability</b>	Ten 100-step programs	N/A
<b>Connectivity</b>	USB A & B, Ethernet, RS-232/RS-485, External Temperature Probe	

#### Select a Reservoir

	<b>8 Liter</b>	<b>11 Liter</b>
<b>Maximum Temperature</b>	85°C	85°C
<b>Working Access (L x W x D)</b>	4.1 x 6.1 x 8 in 10.5 x 15.6 x 20.3 cm	8.3 x 6.1 x 8 in 21 x 156 x 20.3 cm

### Common Specifications

Working Temperature Range °F	Ambient +20° to 185°
Working Temperature Range °C	Ambient +10° to 85°
Reservoir Capacity (gallons)	6.08

Reservoir Capacity (liters)	23
Reservoir/Tank Material	Polycarbonate
Reservoir Cover	Included
DuraTop	Yes
Working Access (L x W x D) (inches)	8.3 x 12 x 8 in
Working Access (L x W x D) (cm)	21 x 30.5 x 20.3 cm
Temperature Stability °F	±0.13°
Temperature Stability °C	±0.07°
Display	3.25" LCD
Display Resolution (Set)	0.1
Display Resolution (Read)	0.1
Pump Type	Pressure
Pump Speed	One
Process Connections	1/2" O.D. Barbed Tubes
Flammability Class (DIN 12876-1)	I (NFL)
Over-Temperature Protection / Failsafe Heater Control	Yes
Low Liquid Level Protection	Yes
Reservoir Drain	Yes
Cooling Coil	Accessory
Maximum Ambient Temperature °F	95°
Maximum Ambient Temperature °C	35°
Overall Dimensions (L x W x H) (inches)	18 x 13.6 x 17.4 in
Overall Dimensions (L x W x H) (cm)	45.7 x 34.5 x 44.1 cm
Environmental Compliance	RoHS, WEEE
Shipping Weight (pounds)	45.0
Shipping Weight (kilograms)	20.4
Catalog Page Number	64-65

## 60 Hz Only

Part Number	MX23P100-A11B
Maximum Pressure (psi)	2.3
Maximum Pressure (bar)	0.16
Maximum Pressure Flow Rate (gpm)	3.60

Maximum Pressure Flow Rate (l/min)	13.5
Included Hardware	Fitting Kit for External Applications
Heater Wattage	1100
Electrical Requirements (VAC/Hz/Ph/A)	120/60/1/10
Regulatory Approvals	ETL

## 50 Hz Only

Part Number	MX23P100-A12E
Maximum Pressure (psi)	1.8
Maximum Pressure (bar)	0.12
Maximum Pressure Flow Rate (gpm)	3.10
Maximum Pressure Flow Rate (l/min)	11.9
Included Hardware	Fitting Kit for External Applications
Heater Wattage	1100
Electrical Requirements (VAC/Hz/Ph/A)	240/50/1/6
Regulatory Approvals	CE