



Empowering you to work smarter

NH5S

Charging Hose Set
w/o Ball Valve



NH5SC

Charging Hose Set
with Ball Valve



NH5R

NH5B

NH5Y

NH5L

Individual Charging Hose
w/o Ball Valve



NH5L
A2L
Compatible

NH5CR

NH5CB

NH5CY

Individual Charging Hose
with Ball Valve



1/4" Color Hoses, 5 Ft Long

Main Features for All Models


- Suitable for R-410A, R-134a, R-22 and other refrigerants
- 1/4" SAE fittings with 45° bend on one end
- Leak-proof eight-sided crimp
- 800 psi working pressure, 4000 psi burst pressure
- Universal, replaceable gasket
- Adjustable depressor

Ball Valve Models

- Ball valve for reduced refrigerant loss
- Metal valve handle

NH5L

- Reverse threaded for A2L



The valve core depressor can be adjusted up or down to optimize its access to valve core. Use a valve core depressor adjuster to turn the depressor. To lower, turn clockwise; to raise, turn counterclockwise.



Model		NH5S	NH5R	NH5B	NH5Y	NH5L	NH5SC	NH5CR	NH5CB	NH5CY				
Color		Red, Yellow, Blue	Red	Blue	Yellow	Orange	Red, Yellow, Blue	Red	Blue	Yellow				
Quantity	pc	3	1	1	1	1	3	1	1	1				
Ball Valve		Without ball valve					With ball valve							
Pressure Scale	psi	0-800 psi												
Length	ft	5												
Connector	in	1/4" - 1/4"												

1-YEAR WARRANTY

Find Quality Products Online at:

www.GlobalTestSupply.com

sales@GlobalTestSupply.com