



P2000 Specifications

Maximum input voltage (max. rated voltage between INPUT H-INPUT L)	DC 2000 V
Maximum rated voltage to earth	2000 V (Measurement Category III) 1000 V (Measurement Category IV)
Input resistance	20 M Ω ±1.0% (between INPUT H – INPUT L)
Output ratio	Depends on the input impedance of the connected device (example: 1/10 when a device with an input impedance of 10 MΩ is connected)
Overload protection	DC/AC 2200 V 1 minutes (between INPUT H – INPUTO L) DC/AC 600 V 1 minutes (between OUTPUT H – OUTPUT L)
Secondary terminal	4 mm banana terminal
Operating environment	Indoor use, pollution degree 2, altitude up to 2000 m
Operating temperature and humidity range	Temperature: -25°C to 65°C Humidity: -25°C to 40°C, up to 80% RH (non-condensing) 40°C to 65°C, (the operation humidity limit falls linearly from 40°C 80% RH to 65°C 25% RH, given that there is no condensation)
Storage temperature and humidity range	-30° C to 70° C 90% RH or less (non-condensing)
Applicable standards	Safety EN 61010

	Product warranty period	3 years (probe body and cable part are not covered by warranty)
		L4943 connection cable, Strap belt, Strap buckle ×2, C0205 carrying case, "Instruction Manual", "Usage Precautions"

Accuracy in combination with the DT4261 or CM series

Models	Combination Accuracy Specifications (Representative value)
DT4261	±0.5% rdg. ±5 dgt.
CM4375-50	
CM4373-50	±1.0% rdg. ±3 dgt.
CM4371-50	
CM4141-50	

Model

Model : AC HIGH VOLTAGE PROBE P2000

Model No. (Order Code) P2000

P2000 Compatible Models



DIGITAL MULTIMETER DT4261



AC/DC CLAMP METER CM4375-50



AC/DC CLAMP METER CM4373-50



AC/DC CLAMP METER CM4371-50



AC CLAMP METER CM4141-50



DISTRIBUTED BY