

Features

- Easy to use, intuitive design
- Large, 4-digit LCD display
- Data hold function
- Zero adjustment screw
- Tripod mountable
- Kick stand
- Over range and low battery indicators
- Includes detachable sensor, sensor cover, and battery

Specifications

Measuring Range:	Lux: 0 to 20,000
Accuracy:	±(5% rdg.+ 4 dgt)
Resolution:	1, 10 lux
Response Time:	<1 sec.
Sensor Type:	Photo diode & color correction filter
Autoranging:	No (Manual)
Display:	4-digit LCD
Data Hold:	Yes
Auto Zero:	Yes
Overrange Indicator:	Yes
Sampling Rate:	2 times/sec.
Kick Stand:	Yes
Tripod Mountable:	Yes
Low Battery Indicator:	Yes
Power Supply:	9V battery
Product Certifications:	CE
Operating Temperature:	32 to 122°F (0 to 50°C)
Storage Temperature:	14 to 140°F (-10 to 60°C)
Operating Humidity Range:	10-80%
Dimensions:	7.9 x 2.7 x 1.2" (200 x 68 x 30mm)
Weight:	9.8 oz (280g)

TECHNICAL DATA



Model	Description
R8120	Lux Light Meter
CA-05A	Soft Carrying Case
R1500	Lightweight Tripod
R8120-NIST	Lux Light Meter & NIST