Reveal Shield PRO

HANDHELD THERMAL CAMERA
DESIGNED FOR LAW ENFORCEMENT

KEY CAMERA SPECS

320 x 240 Thermal Sensor

24°Field of View



Works Day & Night

🔥 IP67 Rating





Highly durable and easy to use, RevealShieldPRO combines a high-performance 320 x 240 thermal sensor with intuitive user interface. When you need it, a powerful 300-lumen LED light is available at the touch of a button. RevealShieldPRO was specifically designed for Law Enforcement Professionals. Built with a rugged over-mold housing and IP67 rating, RevealShieldPRO is fit to withstand the elements.

Thermal Imaging helps you safeguard land and borders, quickly clear a room, find discarded evidence at night, and track perpetrators without a flashlight giving your position away. Even the most elusive suspects can't hide their heat signature.

KEY FEATURES

320 x 240 Thermal Sensor

Excellent image clarity and sensitivity with 76,800 pixels

Long-Range Detection

Detect a human at long distances in complete darkness

3.5 Hour Runtime

Long-Lasting rechargeable battery

Durable Design

Designed for the outdoors with IP67 rating

Lightweight & Easy-to-use

Intuitive, 3 button controls provide easy operation of your camera

BENEFITS

Safeguard Buildings, Land, and Borders

Tactical surveillance technology that's affordable

Better Than Night Vision

Even the most elusive perpetrators can't hide their heat signature

Personal Safety

Clear a room without putting yourself in harm's way

Situational Awareness

It's a lot easier to stay safe when you can see in the dark

Recover Evidence

Recover discarded or hidden evidence invisible to the human eye



TECHNICAL SUMMARY

SPECIFICATIONS	DESCRIPTION
Thermal Sensor	320 x 240
Detection Distance	825 Yards (758 Meters)
Recognize Distance	200 Yards (190 Meters)
Identify Distance	115 Yards (108 Meters)
Field of View	24 Degree FOV
Frame Rate	9 Hz or 30 Hz
Zoom	4X Digital Zoom
IP Rating	IP67 Waterproof
Display	2.4" Color with Corning® Gorilla® GlassUncooled
Microbolometer	Vanadium Oxide
Startup Time	2-3 Seconds
Spectral Range	7.5 – 14 Microns
User Interface	Self-Contained Device with 3 Button Navigation
Storage Temp	-40 to 140F (-40 to 60C)
Operating Temp	-40 to 120F (-20 to 50C)
Runtime	Up to 3.5 Hours Thermal Imaging
Battery	Rechargeable Lithium Battery

LIGHTWEIGHT & EASY-TO-USE



ACCESSORIES

- Lanyard attachment
- Nylon Holster with tactical clip

















